



30CPQ035PbF  
30CPQ040PbF  
30CPQ045PbF

SCHOTTKY RECTIFIER

30 Amp

$$I_{F(AV)} = 30\text{Amp}$$
$$V_R = 35/45\text{V}$$

Major Ratings and Characteristics


Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	30	A
$V_{RRM}$	35/45	V
$I_{FSM}$ @tp=5µs sine	1020	A
$V_F$ @15Apk, $T_J=125^{\circ}\text{C}$ (per leg)	0.50	V
$T_J$	-55 to 150	$^{\circ}\text{C}$

Description/ Features


The 30CPQ...PbF center tap Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150° C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 150° C  $T_J$  operation
- Center tap TO-247 package
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free ("PbF" suffix)

Case Styles



TO-247AC



# 30CPQ035PbF, 30CPQ040PbF, 30CPQ045PbF

Bulletin PD-20784 rev. A 11/06

International  
IOR Rectifier

## Voltage Ratings

Part number	30CPQ035PbF	30CPQ040PbF	30CPQ045PbF
$V_R$ Max. DC Reverse Voltage (V)	35	40	45
$V_{RWM}$ Max. Working Peak Reverse Voltage (V)			

## Absolute Maximum Ratings

Parameters		30CPQ...	Units	Conditions		
$I_{F(AV)}$	Max. Average Forward Current * See Fig. 5	30	A	50% duty cycle @ $T_c = 124^\circ\text{C}$ , rectangular wave form		
$I_{FSM}$	Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	1020	A	5 $\mu\text{s}$ Sine or 3 $\mu\text{s}$ Rect. pulse	Following any rated load condition and with rated $V_{RRM}$ applied	
		265		10ms Sine or 6ms Rect. pulse		
$E_{AS}$	Non-Repetitive Avalanche Energy (Per Leg)	20	mJ	$T_J = 25^\circ\text{C}$ , $I_{AS} = 3$ Amps, $L = 4.4$ mH		
$I_{AR}$	Repetitive Avalanche Current (Per Leg)	3	A	Current decaying linearly to zero in 1 $\mu\text{sec}$ Frequency limited by $T_J$ max. $V_A = 1.5 \times V_R$ typical		

## Electrical Specifications

Parameters		30CPQ...	Units	Conditions	
V <sub>FM</sub>	Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.54	V	@ 15A	T <sub>J</sub> = 25 °C
		0.68	V	@ 30A	
		0.50	V	@ 15A	T <sub>J</sub> = 125 °C
		0.64	V	@ 30A	
I <sub>RM</sub>	Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	1.75	mA	T <sub>J</sub> = 25 °C	V <sub>R</sub> = rated V <sub>R</sub>
		70	mA	T <sub>J</sub> = 125 °C	
C <sub>T</sub>	Max. Junction Capacitance (Per Leg)	900	pF	V <sub>R</sub> = 5V <sub>DC</sub> (test signal range 100Khz to 1Mhz) 25°C	
L <sub>S</sub>	Typical Series Inductance (Per Leg)	7.5	nH	Measured lead to lead 5mm from package body	
dv/dt	Max. Voltage Rate of Change	10000	V/ μs	(Rated V <sub>R</sub> )	

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle <2%

## Thermal-Mechanical Specifications

Parameters		30CPQ...	Units	Conditions
T <sub>J</sub>	Max. Junction Temperature Range	-55 to 150	°C	
T <sub>stg</sub>	Max. Storage Temperature Range	-55 to 150	°C	
R <sub>thJC</sub>	Max. Thermal Resistance Junction to Case (Per Leg)	2.20	°C/W	DCoperation      * See Fig. 4
R <sub>thJC</sub>	Max. Thermal Resistance Junction to Case (Per Package)	1.10	°C/W	DCoperation
R <sub>thCS</sub>	Typical Thermal Resistance, Case to Heatsink	0.24	°C/W	Mounting surface , smooth and greased
wt	Approximate Weight	6(0.21)	g(oz.)	
T	Mounting Torque	Min. 6(5)	Kg-cm (lbf-in)	Non-lubricated threads
		Max. 12(10)		
CaseStyle		TO-247AC(TO-3P)		JEDEC
Device Marking		30CPQ035		
		30CPQ040		
		30CPQ045		




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)






Fig. 8 - Unclamped Inductive Test Circuit

## Outline Table



## Marking Information



Ordering Information Table

## Device Code

30	C	P	Q	045	PbF
1	2	3	4	5	6

- 1** - Current Rating (30 = 30A)
- 2** - Circuit Configuration  
C = Common Cathode
- 3** - Package  
P = TO-247
- 4** - Schottky "Q" Series
- 5** - Voltage Code
- 6** -
  - none = Standard Production
  - PbF = Lead-Free

035 = 35V

040 = 40V

045 = 45V

Tube Standard Pack Quantity : 25 pieces

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level and Lead-Free.  
Qualification Standards can be found on IR's Web site.



### Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.