



Get your Position!

A1037-A Simplified, Miniaturized Full NMEA GPS Module

Value for money is the driving force behind this full NMEA GPS receiver module. The miniaturized, single sided SMD module offers high accuracy position information and a precise one Pulse Per Second (1PPS) signal synchronized to Universal Time (UTC). WAAS and EGNOS are supported in order to improve position accuracy. All modules are electrically tested prior to packaging.

Get your highly accurate PVT (Position, Velocity and Time) information in the

Highly sensitive ■ -153 dBm tracking
Accurate positioning ■ 3 m CEP

Fast TTFF (Time To First Fix) ■ < 60 s under cold start condition (typical)

Very small footprint ■ 19 x 16 mm

Temperature fluctuations compensated ■ TCXO technology

SBAS support WAAS, EGNOS

A-GPS support Almanac, Ephemeris, Position, Time



most cost effective way.

1 CHOIMance	
Channels	12 parallel tracking
Frequency	L1 - 1575 MHz
Sensitivity	
Tracking	-153 dBm
Reacquisition	-147 dBm
Position accuracy (horizontal)	3 m CEP
Time to first fix	
Obscuration recovery ¹⁾	1 s
Hot start ²⁾	< 3 s
Warm start ³⁾	< 32 s
Cold ⁴⁾	< 60 s

Communications

Standard GPS software	
NMEA message switchable	GGA, GSA, GSV, VTG, RMC
Baudrate (in baud)	4,800/57,600 default 9,600/19,200 by software
Serial ports	3.3 V CMOS compatible
TxO	NMEA output
RxO	NMEA input

Environment

Temperature	
Operating	-30°C to +70°C
Storage	-40°C to +85°C
Humidity	Non-condensing

Power

Input voltage	3.3 to 3.6 VDC
Current draw	
Operation	< 55 mA (typical)
Standby	12 µA (typical)
	36h standby by using 1F
	Supercap
Antenna supply via VANT	
Voltage range	up to 5.2 V
Max. allowed current ⁵⁾	50 mA

Mechanicals

Dimensions	16.2 mm x 19 mm x 3.0 mm
	0.75" x 0.64" x 0.12"
Weight	1 g, < 0.05 oz

- The receiver's calibrated clock is not stopped, thus it knows precise time (to the µs level).
 The receiver has estimates of time/date/position and valid almanac and ephemeris data.
- 3) The receiver has estimates of time/date/position and almanac.
- 4) The receiver has estimates of time/date/position, and no recent almanac.
- 5) An external current limiter is suggested to avoid damage in fault conditions.

Positioning Receiver Portfolio

With the mission to support our customers to implement GPS functionality into their systems, Tyco Electronics is offering a large product portfolio to cover almost all integration possibilities in an easy way. A dedicated R&D team located in Ottobrunn, Germany develops sensitive positioning solutions based on state of the art technologies. All GPS products are manufactured in our ISO9001 and TS16949 certified factory inside the EU. Beyond that our modules follow RoHS standard and are 100% electrically and functionally tested prior packaging. This way we constantly guarantee high quality products.


Products shown in actual size











A1037-A

A1029-A/-C

A1080-A

A1030-A

A1035-C/-D

	1 PPS	Antenna active	Antenna passive	Antenna patch onboard	Antenna status detection	Assisted GPS	Connection plug-in	Connection solderable	Data logging	Dead reckoning	Differential GPS RTCM input	Flash, programmable	GPIO	GPS/UTC raw data	I2C interface	Memory free flash (byte) free SRAM (byte)	Processor:	available power	ROM	SBAS support	SPI interface	TCXO	UART NMEA	USB interface	UTM projection
A1037-A	•	•				•		•											•	•		•	•		
A1029-A	•	•	•		•	•		•		•	•	•		•		80k/16k	3 N	1IPS		•	•		•		•
A1029-B	•	•	•		•	•	•				•	•		•		80k/16k	3 N	1IPS		•	•		•		•
A1029-C	•	•	•		•	•		•		•	•	•		•		80k/16k	3 N	1IPS		•	•	•	•		•
A1029-D	•	•	•		•	•	•			•	•	•		•		80k/16k	3 N	1IPS		•	•	•	•		•
A1080-A	•	•				•		•						•					•	•		•	•		
A1030-A	•	•	•		•	•	•		•		•	•		•		4M/2M	3 N	1IPS		•	•		•		•
A1035-C		•		•		•	•					•		•		80k/16k	3 N	1IPS		•	•	•	•		•
A1035-D				•		•	•							•					•	•		•			

The information provided herein is believed to be reliable at press time. Tyco Electronics Power Systems assumes no responsibility for inaccuracies or omissions. Tyco Electronics Power Systems assumes no responsibility for the use of this information, and all such information shall be entirely at the users own risk. Prices and specifications are subject to change without notice. Tyco Electronics Power Systems does not authorize or warrant any of its products for use in life-support devices and / or systems.

Headquarters EMEA: Tyco Electronics Power Systems Finsinger Feld 1 85521 Ottobrunn, Germany

Tel.: +49 (0)89 6089-838 Fax: +49 (0)89 6089-835

gps@tycoelectronics.com www.tycoelectronics.com/gps **Your Partner:**



Copyright © 2007, Tyco Electronics, Raychem GmbH, Power Systems · Printed in Hungary · TEC.PS-011-0507.2-E