



Zero Charge Anti-Stat Coating

1726

Techspray's ESD-safe products can help maintain work areas within the ANSI/ESDS20.20 standards set by the ESD Association (www.esda.com). In a static-free environment, the work area, tools and personnel form a circuit (see diagram to right). Electrostatic Discharge (ESD) occurs when the charges of two surfaces with a large electronic potential (difference) equalize instantaneously. The resulting discharge or spark can cause catastrophic or latent damage to electronic components. ESD programs maintain an equal potential by maintaining continuous contact with ground, avoiding ESD damage. Cleaners, lotions, and coatings are an integral part of an ESD control program.



Fast drying anti-static coating

Fast drying, anti-static coating eliminates static charge and reduces triboelectric generation from flexible surfaces. Ideal for plastics, fabrics, and carpet.

- All-purpose static control
- Non-flammable
- Non-ozone depleting
- For plastics, fabrics, and carpet
- Fast drying



Specifications:

- Meets or exceeds MIL-B-81705B
- NFPA 56A
- USDA: approved A-4 rated

Product Packaging

1726-QT
Zero Charge Anti-Stat
1 qt
12 units/case



Techspray
P.O. Box 949, Amarillo, TX 79105
800-858-4043 • www.techspray.com



Technical Information

Chemical & Physical Properties

Appearance	Clear, colorless liquid
Odor	Pleasant
Flash Point	none
VOC (EPA)	58.14 g/l
Boiling Point	100°C (212°F)
Density	0.978 at 25°C

Chemical Composition

CHEMICAL NAME	CAS #
Ethylbis (hydroxyethyl) tallow alkyl, ethoxylated, Et sulfates	68071-95-4
Ethanol	64-17-5
2-Propanol	67-63-0
Methanol	67-56-1

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
Email: tsales@techspray.com

Europe

ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
Email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country.



Techspray
P.O. Box 949, Amarillo, TX 79105
800-858-4043 • www.techspray.com



Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2014 Techspray, A Division of ITW



Techspray
P.O. Box 949, Amarillo, TX 79105
800-858-4043 • www.techspray.com