



■ Typical Specifications

Items		Specifications
Rating (max.)(Resistive load)		10mA 5V DC
Switch ON position (8-direction)		Each direction 7° max.
Travel (Center-push)		0.3±0.2mm
Operating life	Each direction	500,000 cycles
	Center-push	500,000 cycles


■ Product Line

Product No.	Maximum resolution	Operating force (N)		Minimum order unit (pcs.)	
		Direction	Center-push	Japan	Export
RKJS1004001	8-direction	0.8±0.5	2.5±1.5	3,800	3,800

■ Packing Specifications

Taping

Number of packages (pcs.)			Tape width (mm)	Export package measurements(mm)
1 reel	1 case / Japan	1 case / export packing		
950	3,800	3,800	24	405×405×162



■ Dimensions

[illegible]


■ Output Relation Chart Between Lever Position and ON Position.

Term. The direction of the operation	1	2	3	4	C	P	E
a	△	△	●	△	●	●	○
b	△	△	●	●	●	●	○
c	△	△	△	●	●	●	○
d	●	△	△	●	●	●	○
e	●	△	△	△	●	●	○
f	●	●	△	△	△	●	○
g	△	△	△	●	●	●	○
h	△	●	●	△	●	●	○
Center Push	△	△	△	△	●	●	○
Free	○	○	○	○	○	△	○

● : ON
 △ : OFF
 ○ : Not specified
 ※ Term. E : Ground terminal









Operating direction of lever.

■ Circuit Diagram



Multi Control Devices

List of Varieties

Type		Switch type			
Series		RKJXL	RKJXS	SKRH	
				SKRHAA/AB	SKRHAC/AD
Photo					
Dimensions (typical value) (mm)	W	13	11.7	7.35/7.45	
	D			7.5	
	H	6.4	2.3	5	
Number of operating shafts		Single-shaft			
Shaft material		Metal	Resin		
Directional resolution		8-direction		4-direction	
Directional operating feeling (tactile feeling)		Without	With		
Lever return mechanism		With			
Center-push switch		With			
Encoder		Without			
Operating temperature range		−30℃ to +70℃	−20℃ to +70℃	−40℃ to +85℃	
Operating life	Directional operation	total with 8-direction 100,000 cycles	500,000 cycles for each direction	200,000 cycles for each direction	1,000,000 cycles for each direction
	Center-push	100,000 cycles	500,000 cycles	200,000 cycles	1,000,000 cycles
	Encoder	—	—	—	
Automotive use			—	—	
Life cycle (availability)					
Rating (max.) (Resistive load)		10mA 5V DC		50mA 12V DC	
Electrical performance	Output voltage	—	 1V max. at 1mA 5V DC (Resistive load)	—	
	Encoder resolution	—	—	—	
	Insulation resistance	100MΩ min. 250V DC	50MΩ min. 50V DC	100MΩ min. 100V DC	
	Voltage proof	300V AC for 1min. or 360V AC for 2s	50V AC for 1min. or 60V AC for 2s	100V AC for 1min.	
Mechanical performance	Directional operating force		10±7mN·m	0.8±0.5N	1.23±0.69N 1.2±0.69N
	Push operating force		4.5±1N	2.5±1.5N	2.35±0.69N
	Encoder detent torque		—	—	—
	Terminal strength		—	—	—
	Actuator strength	Push / pull directions	100N (Push), 50N (Pull)	30N (Push), 10N (Pull)	—
Operating direction		100N	20N	29.4N	
Environmental performance	Cold		−40℃ 500h	−40℃ 96h	
	Dry heat		85℃ 500h	85℃ 96h	90℃ 96h
	Damp heat		60℃, 90 to 95%RH 500h	60℃, 90 to 95%RH 96h	
Page		442	443	444	

Switch Type Multi Control Devices Soldering Conditions 451
Switch Type Multi Control Devices Cautions 452

Note

● Indicates applicability to all products in the series.

Switch Type / Soldering Conditions

Reference for Manual Soldering


Series	Tip temperature	Soldering time	No. of solders
RKJXT1F, RKJXM, RKJXL, SLLB, SLLB5, SRBE, SKRH	350±5℃	3s max.	1 time
RKJXS	350±10℃	3 ⁺¹ ₋₀ s	2 time max.

Reference for Dip Soldering

Series	Preheating		Dip soldering		No. of solders
	Soldering surface temperature	Heating time	Soldering temperature	Soldering time	
RKJXT1F, RKJXM	100℃ max.	2 min. max.	260±5℃	5±1s	2 time max.
RKJXL	120℃ max.	70s max.	260℃ max.	6s max.	2 time max.

Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple $\phi 0.1$ to 0.2 CA (K) or CC (T) at soldering portion (copper foil surface).
A heat resisting tape should be used for fixed measurement.
3. Temperature profile



Series	A	B	C	D	E	F	G	H	I	No. of reflows
RKJXS	260℃	230℃	150℃	150℃	2 min.	—	10s	40s	4 min.	1 time
SLLB5	250℃	230℃	150℃	150℃	—	2 min.	—	30s	—	1 time
SKRH, SLLB, SRBE	260℃	230℃	180℃	150℃	2 min.	—	—	40s	—	1 time

Notes

1. The above temperature shall be measured on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the material, size thickness of PC boards and others. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Alps Alpine:](#)

[RKJXS1004001](#)