



KXPS5 Series

Accelerometers and Inclinometers

FEATURES

- Very Small Package - 3x5x0.9mm LGA
- I²C/SPI Interface and Analog Outputs
- Free-fall Interrupt Output
- High-g Motion Interrupt Output
- Low Noise
- Lead-free Solderability
- Excellent Temperature Performance
- High Shock Survivability
- Low Power Consumption
- Selectable Power Reduction Modes
- User Definable Bandwidth
- Factory Programmable Offset and Sensitivity
- Self-test Function

PROPRIETARY TECHNOLOGY

These high-performance silicon micromachined linear accelerometers and inclinometers consist of a sensor element and an ASIC packaged in a 3x5x0.9mm Land Grid Array (LGA). The sensor element is fabricated from single-crystal silicon with proprietary Deep Reactive Ion Etching (DRIE) processes, and is protected from the environment by a hermetically-sealed silicon cap at the wafer level.

The KXPS5 series is designed to provide a high signal-to-noise ratio with excellent performance over temperature. These sensors can accept supply voltages between 1.8V and 5.25V. Sensitivity is factory programmable allowing customization for applications requiring from $\pm 1.5g$ to $\pm 6.0g$ ranges. Sensor bandwidth is user-definable. Interrupts can be generated for acceleration on any axis above a threshold value (Motion Interrupt) or for acceleration on all three axes below a threshold value (Free-fall Interrupt).

The sensor element functions on the principle of differential capacitance. Acceleration causes displacement of a silicon structure resulting in a change in capacitance. An ASIC, using a standard CMOS manufacturing process, detects and transforms changes in capacitance into an analog output voltage, which is proportional to acceleration. This voltage is digitized by an on-board A/D converter and is accessed via an inter-integrated circuit (I²C) bus or serial peripheral interface (SPI).

MARKETS

APPLICATIONS

- Hard Disk Drives/Laptops*
 - Free-fall Detection
- Cell Phones and Handheld PDAs*
 - Gesture Recognition
- Game Controllers and Computer Peripherals*
 - Inclination and Tilt Sensing
- Cameras and Video Equipment*
 - Image Stabilization
- Sports Diagnostic Equipment/Pedometers*
 - Static or Dynamic Acceleration
- Personal Navigation Devices*
 - Inertial Navigation and Dead Reckoning



KXPS5 Series

Accelerometers and Inclinometers

PERFORMANCE SPECIFICATIONS

The performance parameters below are programmed and tested at 3.3 volts. However, the device can be factory programmed to accept supply voltages from 1.8 V to 5.25 V. Performance parameters will change with supply voltage variations.

PERFORMANCE SPECIFICATIONS			
PARAMETERS	UNITS	KXPS5-3157	CONDITION
Range ¹	g	±3.0	Factory programmable
Sensitivity	mV/g	440 typical (449 max)	12 bit operation
0g Offset vs. Temp.	mg/°C	±1 max	
Sensitivity vs. Temp	%/°C	±0.03 max	
Noise	$\mu\text{g} / \sqrt{\text{Hz}}$	175 (typical) 250 (max)	
Bandwidth ²	Hz	1000	-3dB
Non-Linearity	% of FS	0.1 typical (0.5 max)	% of full scale output
Ratiometric Error	%	3.5 max	Vdd=3.3V ± 10%
Cross-axis Sensitivity	%	2.0 typical (3.0 max)	
A/D Conversion Time	μS	200 typical	
SPI Communication Rate ³	MHz	1 typical	
I ² C Communication Rate	KHz	400 typical	
Power Supply	V	3.3	Standard
Current Consumption	μA	800 typical (1000 max)	Operating
	μA	0.0012 typical	Standby
ENVIRONMENTAL SPECIFICATIONS			
PARAMETERS	UNITS	KXPS5-3157	CONDITION
Operating Temperature	°C	-40 to 85	Powered
Storage Temperature	°C	-55 to 150	Un-powered
Mechanical Shock	g	5000	Powered or un-powered, 0.5 msec halversine
ESD	V	2000	Human body model

NOTES

¹ Custom ranges from 1.5g to 6g available.

² Internal 1 kHz low pass filter. Lower frequencies are user definable with external capacitors.

³ SPI communication rate can be optimized for faster communication.

ORDERING GUIDE

Product	Axis(es) of Sensitivity	Range (g)	Sensitivity (mV/g)	Offset (V)	Operating Voltage (V)	Temperature (°C)	Package
KXPS5-1050	XYZ	2	560	1.40	2.8	-40 to +85	3x5x0.9 LGA
KXPS5-2050	XYZ	2	660	1.65	3.3	-40 to +85	3x5x0.9 LGA
KXPS5-3157	XYZ	3	440	1.65	3.3	-40 to +85	3x5x0.9 LGA
KXPS5-4457	XYZ	3	240	0.90	1.8	-25 to +70	3x5x0.9 LGA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Kionix:](#)

[EVAL-KXPS5-2050](#)