Note: This datasheet may be out of date.
Please download the latest datasheet of PTGL07AR4R6H2B51B0 from the official website of Murata
Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=PTGL07AR4R6H2B51B0

PTGL07AR4R6H2B51B0














Appearance & Shape










- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

 Durable and strong against mechanical vibration and shock because it is a solid element.







Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. $\underline{ \text{Please download the latest datasheet of PTGL07AR4R6H2B51B0 from the official website of Murata} \\$ Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=PTGL07AR4R6H2B51B0

PTGL07AR4R6H2B51B0



Max. Voltage	30V
Hold Current	250mA
Measure Condition of Hold Current	(at +60°C)
Hold Current (2)	340mA
Measure Condition of Hold Current (2)	(at +25°C)
Trip Current	610mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	700mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	2A
Resistance (25°C)	4.6Ω
Resistance Value Tolerance (at 25°C)	±25%
Power Consumption(typ)	1.3W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	7.4mm
Thickness	4mm
F: Lead Space	5mm

d: Lead Diameter	0.6mm
Shape	Lead
Mass	0.27g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated :2018/12/22


PTGL07AR4R6H2B51B0







Resistance-Temperature Charac.



Protective Threshold Current Range

Operating Time (Typical Curve)

Overcurrent (A)

0.2

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

PTGL07AR4R6H2B51B0