SMD ONE PORT 423.22MHz SAW RESONATOR

ASR423.22E





> STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	423.145	423.220	423.295	
Tolerance from Fo		KHz		±75		
Insertion Loss		dB	-	1.3	2.5	
Quality Factor	Unloaded		-		12,300	
	50Ω loaded		-		1,900	
Temperature Stability	Turnover Temperature		°C	20.0	35.0	50
	Turnover Frequency		KHz		Fo	
	Freq. Temp. Coefficient		ppm/°C ²		0.037	
Frequency Aging			ppm/year		<±10	
DC Insulation Resistance			$M\Omega$	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		19	29
	Motional Inductance L ₁		μH		89.547	
	Motional Capacitance C ₁		fF		1.5808	
	Shunt Capacitance C ₀		pF		2.5	2.4
Operating temp.		°C		-40°C to +85°C		
Storage temp.		°C	-45°C to +85°C			
Max. Rating	DC voltage	DC voltage V ±10				
RF Power Dissipation		dBm	0			

Data measured with: Source Impedance: Zs= 50Ω , Load Impedance: ZL= 50Ω , TA= 25° C Electrostatic Sensitive Device. Handle with precaution.

> MARKING:

- A ZYX

- 423.22R


(423.22 Frequency in MHz) (ZY: Date code Z for month

from A to L; Y for year,


I.e. 4 for 2004

X: Traceability code)

PIN NO.	CONNECTIONS	
1	Input GND	
2	Input	
5	Output GND	
6	Output	
3,7	To be GNDed	
4.8	Case GND	



> OUTLINE DRAWING:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

ASR423.22N01-SD01 ASR423.22N01-SD02 ASR423.22N01-SE ASR423.17N01-SE ASR423.22E-T