Product Data Sheet

3M[™] Dual Conductor Thermoplastic Wrist Strap for Monitors 4720

The Dual Conductor Wrist Strap 4720 consists of an insulative exterior with a conductive interior and a 3.4mm dual conductor jack. Made of thermoplastic material, the Wrist Strap is light weight, low profile and safely makes contact with human skin. The "zipper" style latching mechanism easily adjusts to most wrist sizes. Made to be used in conjunction with all 3M[™] Workstation Monitors. Meets the resistance requirements of ANSI/ESD S20.20-2014.



WARNING

All 3M Wrist Straps should not be used in areas where the individual may come in contact with electrical circuitry exceeding 250 volts.

Specifications - Band	Typical Value
Material	Thermoplastic
Color	Blue
Plug Size	3.4mm
Cord Removal Force	< 5 lbs.
Size	Adjustable, small/large, 1.7 to 2.6 in. diameter
Resistance Inside	<10 ⁵ ohms
Resistance Outside	>10 ⁷ ohms
Easy to latch and unlatch	
Cleanable	Water/mild detergent or 10% isopropyl solution
Part Numbers	
4720	$3M^{\mathrm{TM}}$ Dual Conductor Thermoplastic Wrist Strap for Monitors
Related Products	
2360 3M [™] Dual Conductor C	coiled Cord, 5 ft. (1.5 m) practical length
2370 3M [™] Dual Conductor C	coiled Cord, 10 ft. (3.0 m) practical length
2371 3M [™] Dual Conductor C	coiled Cord, 20 ft. (6.1 m) practical length
2360R 3M [™] Dual Conductor Coiled Cord, 5ft. (1.5 m) practical length, with right angle mono plug connection (to be used only with 3M monitors)	
2370R 3M [™] Dual Conductor connection (to be used only	Coiled Cord, 10 ft. (3.0 m) practical length, with right angle mono plug with 3M monitors)
2371R 3M [™] Dual Conductor connection (to be used only	Coiled Cord, 20 ft. (6.1 m) practical length, with right angle mono plug with 3M monitors)
3M [™] Workstation Monitor 72	4
3M [™] Wrist Strap Monitor 72	5
3M [™] Wrist Strap and Ground	Monitor 773
3M [™] Static Monitor 790	
3M [™] Iron Man Plus Workstat	ion Monitor CTC331
3M [™] Ground Man Plus Groun	nd Monitor CTC334
Meets the wrist band requirement	s of ANSI/ESD S20.20-2014

Product Data Sheet

3M[™] Dual Conductor Thermoplastic Wrist Strap for Monitors 4720

3M is a trademark of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



Electronics Materials Solutions Division Static Control Products 926 JR Industrial Drive

Sanford, NC 27332-9733 Toll-Free: 866-722-3736 International: 919-718-0000 Email: 3mstaticinfo@mmm.com www.3Mstatic.com

Please recycle. Printed in USA. © 3M 2014. All rights reserved. 78-9102-1852-4 JHA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

