


EK-29842-049 SHEET 2.1 SENSITIVITY IN dB RELATIVE TO 1.0 VOLT/0.1 Pa (N/M 2) FOR CONDITIONS SHOWN BELOW. -40dB - 45 - 50 _ _ _ _ - 55 _ _ -60 -65 -70 -75 -80 5 2 3 4 2 3 4 6 7 8 9 5 6 7 8 9 00 1000 10000 FREQUENCY IN HERTZ <u>SENSITIVITY</u> <u>DEVICE CONFORMITY</u> <u>FREQUENCY</u> MIN. NOM. MAX. RANGE OF DEVIATION FROM IKHz 100 - - --62.5 - - --||.0 -4.0 -55.0 -50.5 1000 -57.0 -53.0 0.0 +1.5 0.0 ~4500 - - -- - -+7.5



NOTES:

- I. CASE CONNECTED TO NEGATIVE TERMINAL.
- 2. MICROPHONE TO BE FUNCTIONAL WITH 10 VDC SUPPLY.

DC	AMPLIFIER	SENSITIVITY CHANGE ON REDUCING SUPPLY TO 0.9VDC	"A" WEIGHTED NOISE (I kHz EQUIV. SPL)	OUTPUT IMPEDANCE OHMS			CAPACITANCE $\pm 50\%$		
SUPPLY	CURRENT DRAIN			MIN.	NOM.	MAX.	I - 2	- 3	
Ι.3V	50 µА МАХ.	3 dB MAX.	30.5 dB MAX.	2000	3800	6000	N / A	N / A	

	Revision	C.O. #	Implementation Date	RELEASE LEVEL		REVISION
	A	MI0100768	9 - 2 - 0 5	Released		
KNOWLES ELECTRONICS ITASCA, ILLINOIS U.S.A.	WHEN TEST LIMITS ARE USED TO ESTABLISH INCOMING INSPECTION ACCEPTANCE/REJECTION CRITERIA, CORRELATION OF TEST EQUIPMENT WITH KNOWLES IS ALSO REQUIRED FOR ELIMINATION OF EQUIPMENT AND TEST METHOD VARIATION			dr. by AB ck. by	date 9 - 2 - 0 5 date	
	TITLE:	MIC	ROPHONE	EK-29842-049	GJP app. by	9 - 7 - 0 5 Date
		PERFORMAN	NCE SPECIFICATION	SHT 2.1	GJP	9 - 7 - 0 5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Knowles: EK-29842-049