



SOWI-to-SOIC Adapter

FEATURES


- Allows the use of a wide package IC in place of a narrow one.

GENERAL SPECIFICATIONS

- LEADS: mechanically fastened to PCB as well as soldered
- PCB: FR-4, 0.062 [1.56] or 0.094 [2.39] thick
- MALE PIN: Brass 360 1/2-hard per UNS C36000, ASTM B16/B16M
- MALE PIN PLATING: 200 μ [5.08 μ] Sn/Pb 93/7 ASTM B579-73 over 100 μ [2.54 μ] Ni per SAE AMS-QQ-N-290
- OPERATING TEMPERATURE: 221°F [105°C]

MOUNTING CONSIDERATIONS

- Standard surface mounting to PCB
- Small package can be IR reflowed, vapor phased, or simply hand soldered



CUSTOMIZATION: In addition to the standard products shown on this page, Aries specializes in custom design and production. Special materials, platings, sizes, and configurations can be furnished, depending on the quantity. **NOTE:** Aries reserves the right to change product general specifications without notice.

ALL DIMENSIONS: INCHES [MILLIMETERS]

ALL TOLERANCES: ± 0.005 [0.13] UNLESS OTHERWISE SPECIFIED


CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

ORDERING INFORMATION

XX-665000-00-P

No. of Pins
8, 14, 16, 18, 20, 22, 24, 28
Series

Optional Panelized Form



ARIES
ELECTRONICS, INC.

Bristol, PA 19007-6810 USA
TEL (215) 781-9956 • FAX (215) 781-9845
WWW.ARIESELEC.COM • INFO@ARIESELEC.COM

PRINTOUTS OF THIS DOCUMENT MAY BE OUT OF DATE AND SHOULD BE CONSIDERED UNCONTROLLED

18045
Rev. AA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Aries Electronics:

[26-665000-00](#) [18-665000-00](#) [22-665000-00](#) [24-665000-00](#) [20-665000-00](#) [10-665000-00](#) [14-665000-00](#) [28-665000-00](#) [08-665000-00](#) [16-665000-00](#) [12-665000-00](#)