REV. Status

REVISION -04/06/98 TS

REVISION A ADDED RoHS 12/02/05 MP

REVISION B ADDED TEMP **RATING** 5/4/15 MP


AUDIO COUPLING MINIATURE ENCAPSULATED TRANSFORMER DESIGNED TO OPERATE 65mW MAX IN SECONDARY AND REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 1.6K $\Omega$ CT WITH 3.2 $\Omega$  LOAD ON SECONDARY.

- A. Electrical Specifications (@ 20°C)
  - 1. Pri Source Impedance; 1.6KΩCT
  - 2. Sec Load Impedance;  $3.2\,\Omega$
  - 3. Pri DC Current; 2.5mA MAX
  - 4. Operating Level; 65mW MAX @ 300Hz
  - 5. Frequency Response (relative to 1KHz); ±3.0dB, @ 300Hz to 100KHz
  - 6. Longitudinal Balance; 60dB MIN @ 1KHz
  - 7. DC Resistance;

(1-3) 230Ω MAX (4-5) 1.0Ω MAX

- 8. Turns Ratio; (1-3): (4-5) = 22.4 : 1 ±2%
- 9. Dielectric Strength;

60Hz 500Vrms 0.5 minute @ Pri - Sec



TOLERANCES (mm)  $4 \pm 0.2$  $4 \le 20 \pm 0.3$  $20 \le 50 \pm 0.4$ 

PREPARED BY:

C. POPPE

ENGINEER:	ļ
MATHI P.	

DRAWING CONTROL NO. REV P-A1-12008 В SAFETY ENGINEER

MODEL DESCRIPTION AUDIO COUPLING MINIATURE ENCAPSULATED XFMR CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE TAMURA CORPORATION OF AMERICA 1040 SOUTH ANDREASEN DRIVE, #100 ESCONDIDO, CA. 92029 (951) 699-1270 FAX 7607400536 MODEL SPECIFICATION MET-23

DIM: mm[ln] SCL: 2/1

APPROVED: M. PITCHAI

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tamura: