Tektronix[®]

Passive Voltage Probes

TPP1000 · TPP0500B · TPP0502 · TPP0250 Datasheet



The TPP1000, TPP0500B, TPP0502 and TPP0250 models are highbandwidth, general-purpose probes from Tektronix that offer breakthrough specifications previously unrealized in this product class. Designed for use with Tektronix MDO3000, MDO4000B, MSO/DPO4000B and MSO/ DPO5000B Series oscilloscopes, these probes provide up to 1 GHz of analog bandwidth with less than 3.9 pF of capacitive loading.

Key performance specs

- 1 GHz, 500 MHz and 250 MHz probe bandwidth models
- <4 pF input capacitance</p>
- 10X and 2X attenuation factor
- 300 V CAT II input voltage
- Designed for use with the MDO3000, MDO4000B, MSO/DPO4000B and MSO/DPO5000B series oscilloscopes

Key features

- Compact probe head for probing small-geometry circuit elements
- Small probe body for enhanced visibility to the device-under-test
- Rigid tip for secure device-under-test connectivity

- Replaceable probe tip cartridges
- Large accessory set for versatile connectivity

Connectivity

- Integrated oscilloscope and probe measurement system provides intelligent communication that automatically scales and adjusts units on the oscilloscope display to match the probe attenuation
- Built-in AC compensation optimizes signal path across the entire frequency range

Applications

- Low-power devices
- Service
- Manufacturing engineering test
- Research and development

Accurate high-speed passive probing

The extremely low capacitive loading limits adverse affects on your circuits and is more forgiving of longer ground leads. And with the probe's wide bandwidth, you can see the high-frequency components in your signal which is critical for high-speed applications. The TPP1000, TPP0500B and TPP0250 passive voltage probes offer all the benefits of general-purpose probes like high dynamic range, flexible connection options, and robust mechanical design, while providing the performance of active probes.

Accurate low voltage

The TPP0502 offers the industry's highest bandwidth (500 MHz) and lowest attenuation factor (2X) for making low-voltage measurements such as ripple, a common measurement on the output of power supplies. The low capacitive loading of the TPP0502 means long ground leads can also be used on this probe with minimal impact on measurement quality, providing today's engineer with the flexibility to move around their design without worrying about ground lead length.

Specifications

All specifications apply to all models unless noted otherwise.

Model overview

| | TPP1000 | TPP0500B | TPP0502 | TPP0250 |
|----------------------------------|--------------|--------------|---------------|--------------|
| Attenuation | 10X | 10X | 2X | 10X |
| Dynamic range | 300 V Cat II | 300 V Cat II | 300 V Cat II | 300 V Cat II |
| Bandwidth | 1 GHz | 500 MHz | 500 MHz | 250 MHz |
| Input impedance at the probe tip | 10 MΩ, <4 pF | 10 MΩ, <4 pF | 2 MΩ, 12.7 pF | 10 MΩ, <4 pF |
| Cable length | 1.3 m | 1.3 m | 1.3 m | 1.3 m |

Ordering information

Models

| TPP1000 | 1 GHz, 10X attenuation passive probe with $TekVPI^{\scriptscriptstyleTM}$ interface. |
|----------|--|
| TPP0500B | 500 MHz, 10X attenuation passive probe with $TekVPI^{\texttt{M}}$ interface. |
| TPP0502 | 500 MHz, 2X attenuation passive probe with $TekVPI^{\texttt{M}}$ interface. |
| TPP0250 | 250 MHz, 10X attenuation passive probe with $TekVPI^{M}$ interface. |

Standard accessories

| Description | Quantity included | Reorder part number |
|---------------------------------|-------------------|---------------------|
| Rigid tip 3.8 mm | 1 | 206-0610-00 |
| Flex ground spring SHORT 3.8 mm | 2 | 016-2034-00 |
| Long ground spring | 2 | 016-2028-00 |
| Alligator ground (6 in.) | 1 | 196-3521-00 |
| Hook tip (regular) | 1 | 013-0362-00 |
| Hook tip (micro) | 1 | 013-0363-00 |
| IC cap (universal) 3.8 mm | 1 | 013-0366-00 |

Recommended accessories

| Description | Quantity included | Reorder part number |
|---|-------------------|---------------------|
| Alligator ground (12 in.) | 1 | 196-3512-00 |
| 6 in. clip-on ground lead (with 0.025 in. pin receptacle) | 1 | 196-3198-01 |
| Microcircuit test tip | 1 | 206-0569-00 |
| Wire, 32 AWG (spool) | 1 | 020-3045-00 |
| BNC to probe tip adapter | 1 | 013-0367-00 |
| PCB to probe tip adapter, pack of 10 | 1 | 016-2016-00 |
| Compact probe tip chassis mount test jack | 1 | 131-4210-00 |
| Color bands (set of 4 color-coded bands) | 1 | 016-0633-00 |
| Tweaker tool | 1 | 003-1433-02 |

Options

Service options

Opt. SILV100 Standard warranty extended to 5 years

Opt. SILV200 Standard warranty extended to 5 years

Probes and accessories are not covered by the oscilloscope warranty and Service Offerings. Refer to the datasheet of each probe and accessory model for its unique warranty and calibration terms.

CE



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

Datasheet

ASEAN / Australasia (65) 6356 3900 Belgium 00800 2255 4835* Central East Europe and the Baltics +41 52 675 3777 Finland +41 52 675 3777 Hong Kong 400 820 5835 Japan 81 (3) 6714 3010 Middle East, Asia, and North Africa +41 52 675 3777 People's Republic of China 400 820 5835 Republic of Korea 001 800 8255 2835 Spain 00800 2255 4835* Taiwan 886 (2) 2722 9622

Austria 00800 2255 4835* Brazil +55 (11) 3759 7627 Central Europe & Greece +41 52 675 3777 France 00800 2255 4835* India 000 800 650 1835 Luxembourg +41 52 675 3777 The Netherlands 00800 2255 4835* Poland +41 52 675 3777 Russia & CIS +7 (495) 6647564 Sweden 00800 2255 4835* United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777 Canada 1 800 833 9200 Denmark +45 80 88 1401 Germany 00800 2255 4835* Italy 00800 2255 4835* Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90 Norway 800 16098 Portugal 80 08 12370 South Africa +41 52 675 3777 Switzerland 00800 2255 4835* USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com.

Copyright [©] Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies. 51W-26151-5 10 Feb 2014

www.tektronix.com



Updated 10 April 2013

to the second se

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 Tektronix:

 TPP0502
 TPP0500B