



Scale - 6:1

## Recommended P.C.B Layout



#### SCHEMATIC



### **SPECIFICATION**

>Rating: 50mA, 12VDC

>Contact Resistance :

Initial :  $100m\Omega$  max. After Life test :  $1\Omega$  max.

>Insulation Resistance :  $min. 100M\Omega$  at 500VDC >Dielectric Strength : 250VAC for 1 minute 0.2 + 0.2 / -0.1mm >Bounce : 10ms max.

## <u>Material</u>

>Cover: Stainless Steel >Stem: PA46 UL HB

>Frame : PA46 UL HB, color Black
>Contact : Stainless Steel with Silver
>Terminal : Copper Alloy with Silver

>Tape : Polyimide tape

#### Soldering Information

>Terminal in SMD version

>Reflow soldering according to JEDEC J-STD-020 Hot Air

>Hand soldering under 350°C for 3sec. max

>Flex board design not recommended

#### Environmental

Storage condition :  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$ Operation condition :  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$ 

Compliance : Lead Free , ROHS , Reach

## Packaging information

#### >Tape & Reel

Part number	Force	Color of Stem	Life cycle		
434 331 013 822	220g ±80gf	White	100.000		

				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions	CREATED DaF	CHECKED GENERAL TOLER JLi DIN ISO 2768		METI	ECTION IOD	SCALE 1:1
				│ ─ Max-Evth-Str. 1	DESCRIPTION TECHNICAL REFERENCE					
				74638 Waldenburg	,					
				Germany com. +49 79 42 945 - 0				ORDER CODE		
				-				434 331 013 822		
1.1	new information by Soldering Information	2015-07-23	DaF	www.we-online.de	SIZE	STATUS		DATE	BUSINESS UN	
REV.	FILE	DATE	BY	eiSos@we-online.de WÜRTH ELEKTRONIK	3.5x2.9x1.35m	nm Releas	ed	2015-04-27	eiSos	1 /1

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Wurth Electronics: 434331013822