

Custom High Performance Cooling Solutions w/ maxiGRIP™ Attachment

ATS PART # ATS-59003-C2-R0

Features & Benefits

- » Designed for flip-chip processors such as Freescale MPCs
- » maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- » Comes preassembled with high performance, phase changing, thermal interface material





*Image above is for illustration purposes only.

Thermal Performance

AIR VELOCITY				THERMAL RESISTANCE		
	FT/MIN N		/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)	
	200		.0	3.8	2.4	
300		1	.5	3		
400		2	.0	2.6		
	500	2	.5	2.3		
	600	3	.0	2.1		
700		3	.5	2		
	800	4	.0	1.9		

Product Details

DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	INTERFACE MATERIAL	FINISH
32 mm	50 mm	12 mm	71.3 mm	SAINT-GOBAIN C1100F	BLACK-ANODIZED

NOTES:

 ATS-59003-C1-R0 is a subsitute item available utilizing an equivalent phase change material (Chomerics T766).

3) Thermal beformance data are provided for reference only. Actual performance may vary

by application.
ATS reserves the right to update or change its products without notice to improve the design or performance.

Contact ATS to learn about custom options available.



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).

¹⁾ Dimension C = heat sink height from bottom of the base to the top of the fin field.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advanced Thermal Solutions: ATS-59003-C1-R0