



## GaAs MMIC DOUBLE-BALANCED SMT MIXER, 26 - 40 GHz

### Typical Applications


The HMC329LM3 is ideal for:

- Point-to-Point Radios
- Point-to-Multi-Point Radios
- SATCOM
- RADAR

### Features

- Passive: No DC Bias Required
- Input IP3: +19 dBm
- LO/RF Isolation: 35 dB
- Leadless SMT Package, 25 mm<sup>2</sup>

### Functional Diagram



### General Description

The HMC329LM3 is a 26 - 40 GHz surface mount, passive, double-balanced MMIC mixer in a SMT leadless chip carrier package. The mixer can be used as a downconverter or upconverter. Excellent isolations are provided by on-chip baluns. The chip requires no external components and no DC bias. All data is with the non-hermetic, epoxy sealed LM3 package mounted in a 50 Ohm test fixture. Utilizing the HMC329LM3 eliminates the need for wire-bonding, thereby providing a consistent connection interface for the customer.

### Electrical Specifications, $T_A = +25^\circ\text{C}$


Parameter	LO = +13 dBm, IF = 1 GHz			LO = +13 dBm, IF = 1 GHz			Units
	Min.	Typ.	Max.	Min.	Typ.	Max.	
Frequency Range, RF & LO	26 - 32			32 - 40			GHz
Frequency Range, IF	DC - 8			DC - 8			GHz
Conversion Loss		8	10		9	11	dB
Noise Figure (SSB)		8	10		9	11	dB
LO to RF Isolation	30	37		27	32		dB
LO to IF Isolation	29	35		24	30		dB
RF to IF Isolation	23	28		21	26		dB
IP3 (Input)	16	19		16	20		dBm
IP2 (Input)	45	55		46	56		dBm
1 dB Compression (Input)	9	11		7	10		dBm

\* Unless otherwise noted, all measurements performed as downconverter, IF = 1 GHz.




**GaAs MMIC DOUBLE-BALANCED SMT MIXER, 26 - 40 GHz**


**Conversion Gain vs. Temperature @ LO = +13 dBm**




**Isolation vs. Frequency @ LO +13 dBm**




**Conversion Gain vs. LO Drive**




**Upconverter Performance vs. LO Drive**



**IF Bandwidth and IF Return Loss @ LO = +13 dBm**



**LO and RF Return Loss @ LO = +13 dBm**




Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

For price, delivery, and to place orders: Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106 Phone: 781-329-4700 • Order online at [www.analog.com](http://www.analog.com) Application Support: Phone: 1-800-ANALOG-D




**GaAs MMIC DOUBLE-BALANCED SMT MIXER, 26 - 40 GHz**


**Input IP3 vs. LO Drive\***




**Input IP3 vs. Temperature @ LO = +13 dBm**




**Input IP2 vs. LO Drive\***



**Input IP2 vs. Temperature @ LO = +13 dBm**



**Input P1dB vs. Temperature @ LO = +13 dBm**



**MxN Spurious Outputs as a Down Converter**

		nLO				
mRF		0	1	2	3	4
0	xx	7				
1	19	0	41			
2		69	57	67		
3			74	69	71	
4				74	74	

RF = 31 GHz @ -10 dBm  
 LO = 32 GHz @ +13 dBm  
 All values in dBc below IF output power level.

\* Two-tone input power = -5 dBm each tone, 1 MHz spacing.




**Absolute Maximum Ratings**

RF / IF Input	+13 dBm
LO Drive	+27 dBm
IF DC Current	±2 mA
Storage Temperature	-65 to +150 °C
Operating Temperature	-40 to +85 °C
ESD Sensitivity (HBM)	Class 1B



**ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS**

**Outline Drawing**



**NOTES:**

1. MATERIAL: PLASTIC
2. PLATING: GOLD OVER NICKEL
3. ALL DIMENSIONS IN INCHES (MILLIMETERS)
4. ALL TOLERANCES ARE ±0.005 (±0.13)
5. ALL GROUNDS MUST BE SOLDERED TO PCB RF GROUND
6. ● INDICATES PIN 1

## GaAs MMIC DOUBLE-BALANCED SMT MIXER, 26 - 40 GHz




### Pin Descriptions

Pin Number	Function	Description	Interface Schematic
1, 2, 3	N/C	This pin may be connected to the PCB ground or left unconnected.	
4	RF	This pin is DC coupled and matched to 50 Ohm from 25 to 40 GHz.	
5	IF	This pin is DC coupled. For applications not requiring operation to DC, this port should be DC blocked externally using a series capacitor whose value has been chosen to pass the necessary IF frequency range. For operation to DC, this pin must not source or sink more than 2 mA of current or part non-function and possible part failure will result.	
6	LO	This pin is DC coupled and matched to 50 Ohm from 25 to 40 GHz.	
	GND	Package base must be soldered to PCB RF ground.	




**Evaluation PCB**



The grounded Co-Planar Wave Guide (CPWG) PCB input/output transitions allow use of Ground-Signal-Ground (GSG) probes for testing. Suggested probe pitch is 400 mm (16 mils). Alternatively, the board can be mounted in a metal housing with 2.4 mm coaxial connectors.

**Evaluation Circuit Board Layout Design Details**

Layout Technique	Micro Strip to CPWG
Material	Rogers 4003 with 1/2 oz. Cu
Dielectric Thickness	0.008" (0.20 mm)
Microstrip Line Width	0.018" (0.46 mm)
CPWG Line Width	0.016" (0.41 mm)
CPWG Line to GND Gap	0.005" (0.13 mm)
Ground Via Hole Diameter	0.008" (0.20 mm)




**LM3 package mounted to evaluation PCB**

**GaAs MMIC DOUBLE-BALANCED  
SMT MIXER, 26 - 40 GHz**



**Suggested LM3 PCB Land Pattern**





### Recommended SMT Attachment Technique

#### Preparation & Handling of the LM3 Millimeterwave Package for Surface Mounting

The HMC LM3 package was designed to be compatible with high volume surface mount PCB assembly processes. The LM3 package requires a specific mounting pattern to allow proper mechanical attachment and to optimize electrical performance at millimeterwave frequencies. This PCB layout pattern can be found on each LM3 product data sheet. It can also be provided as an electronic drawing upon request from Hittite Sales & Application Engineering.

#### Follow these precautions to avoid permanent damage:

**Cleanliness:** Observe proper handling procedures to ensure clean devices and PCBs. LM3 devices should remain in their original packaging until component placement to ensure no contamination or damage to RF, DC & ground contact areas.

**Static Sensitivity:** Follow ESD precautions to protect against ESD strikes.

**General Handling:** Handle the LM3 package on the top with a vacuum collet or along the edges with a sharp pair of bent tweezers. Avoiding damaging the RF, DC, & ground contacts on the package bottom. Do not apply excess pressure to the top of the lid.

**Solder Materials & Temperature Profile:** Follow the information contained in the application note. Hand soldering is not recommended. Conductive epoxy attachment is not recommended.

**Solder Paste:** Solder paste should be selected based on the user's experience and be compatible with the metallization systems used. See the LM3 data sheet Outline drawing for pin & ground contact metallization schemes.


**Solder Paste Application:** Solder paste is generally applied to the PCB using either a stencil printer or dot placement. The volume of solder paste will be dependent on PCB and component layout and should be controlled to ensure consistent mechanical & electrical performance. Excess solder may create unwanted electrical parasitics at high frequencies.

**Solder Reflow:** The soldering process is usually accomplished in a reflow oven but may also use a vapor phase process. A solder reflow profile is suggested above.

Prior to reflowing product, temperature profiles should be measured using the same mass as the actual assemblies. The thermocouple should be moved to various positions on the board to account for edge and corner effects and varying component masses. The final profile should be determined by mounting the thermocouple to the PCB at the location of the device.

Follow solder paste and oven vendor's recommendations when developing a solder reflow profile. A standard profile will have a steady ramp up from room temperature to the pre-heat temperature to avoid damage due to thermal shock. Allow enough time between reaching pre-heat temperature and reflow for the solvent in the paste to evaporate and the flux to completely activate. Reflow must then occur prior to the flux being completely driven off. The duration of peak reflow temperature should not exceed 15 seconds. Packages have been qualified to withstand a peak temperature of 235°C for 15 seconds. Verify that the profile will not expose device to temperatures in excess of 235°C.

**Cleaning:** A water-based flux wash may be used.





# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Analog Devices Inc.:](#)

[HMC329LM3](#) [105976-HMC329LM3](#) [HMC329LM3TR](#)