

COMPACT DESIGN



The JHT miniature series Hall Effect joystick's compact design and robust construction is the ideal solution where space is limited and precision control is required. Ideal applications include: robotics, construction equipment, hydraulic controls, medical and surgery equipment, security and surveillance video cameras. The JHT has been tested to five million cycles with no degradation of electrical performance or boot wear. Electronics are sealed to IP68S and the EMI/RFI withstand are per SAE J1113 specifications.

Features:

- Compact design excellent for armrest & panel mounting
- Proven contactless analog output Hall effect technology
- 5 million operational cycles in all directions
- Electronics sealed per IP68S
- Single or omni-directional & preferred feel options
- Optional pushbutton switch(es) available
- RoHS/WEEE/Reach compliant

Standard Characteristics/Ratings:

GENERAL:

Sensor Type: Hall effect analog, factory programmed ground and supply line break detection; over voltage and reverse voltage protection

Design: Contactless sensing

ELECTRICAL RATINGS: Rated at Vcc = 5V @ 20°C Load = 1ma (4.7KΩ)

Electrical

	Units	Min	Typ	Max
Supply Voltage	VDC	4.5	5	5.5
Output Voltage Tolerance at Center	VDC @ 5V Vcc	-.25	N/A	+.25
Output Voltage Tolerance Full Travel	VDC @ 5V Vcc	-.25	N/A	+.25
Supply Current* (B = 0, Vcc = 5V, Io = 0)	mA	N/A	10	12
Output Impedance	kΩ	N/A	1	N/A

*Single output per axis. Dual axis per output available. Supply current 20mA typical.

MECHANICAL:

Joystick Mechanical Life: 5,000,000 cycles in all directions

P9 Mechanical Life: 1,000,000 cycles

Travel Angle: 18° min to 22° max, 20° typical

Overtravel Angle: 0.5° min to 1.5° max, 1° typical

Joystick Operating Force: With bellows, at grip 0.5 lb. min to 1.5 lbs. max over temperature range

P9 Operating Force: @20°C 8 oz min to 16 oz max, 12 oz typical

ENVIRONMENTAL:

Operating Temp Range: -40°C to +85°C

Seal: Electronics seal to IP68S

RFI/EMI: Withstand per SAE J1113

MATERIALS:

Housing: Thermoplastic, black

Bellows: Silicone, black. Additional materials available, contact factory.

JHT PART NUMBER CODE

JHT	XX	X	X	XX	X	X	
Switch/Boot Style	Gating*	Operating Force	Output 1	Output 2	Termination	P9 Button Color**	
11. With P9 Pushbutton & Full Boot	1. Gated, Single axis – Return to Center	1. 1 lb	AA. 2.5 +/- 2.0VDC	NONE	1. 24 AWG Wire Leads	N. None	
12. With P9 Pushbutton & Half Boot	3. Omni-directional; Round Smooth Feel		BB. 2.5 +/- 2.0VDC	2.5 +/- 2.0VDC		1. Red	
21. Without Pushbutton & Full Boot	4. Omni-directional; On-Axis and Off-Axis Guided Feel		CC. 2.5 +/- 2.0VDC	2.5 +/- 2.0VDC		2. Black	
	5. Omni-directional; Round On-Axis Guided Feel		DD. 2.5 +/- 1.5VDC	NONE		3. Orange	
			EE. 2.5 +/- 1.5VDC	2.5 +/- 1.5VDC		4. Yellow	
			FF. 2.5 +/- 1.5VDC	2.5 +/- 1.5VDC		5. Green	
			GG. 0.5 - 4.5VDC	0.5 - 4.5VDC		6. Blue	
			HH. 1.0 - 4.0VDC	1.0 - 4.0VDC		7. Purple	
						8. Gray	
						9. White	

*Gated = Restricted movement in XY axis only. Gating icons appear on page 69.

**Applies only to half boot with pushbutton option




NOTES:

- Outputs are from the center to the full travel position in each direction.
- Options "AA," "BB," "CC," "DD," "EE" and "FF" provide increased voltage in +X, +Y; and decreasing voltage in -X, -Y direction from one output per axis.
- Options "GG" and "HH" provide increasing voltages in all directions (+X, +Y, -X, -Y) from 2 outputs per axis.
- Options "BB" and "EE" provide redundant output 2 which duplicates output 1. Options "CC" and "FF" provide redundant output 2 which is inverse of output 1.





MINIATURE HALL EFFECT JOYSTICK

JHT
MINI
JOYSTICK





COMPACT DESIGN



Full Boot Version Shown




JHT Switch/Style Boot Configuration




HALF BOOT

FULL BOOT


JHT and JHT Z-Axis Icons Demonstrating Feel*




Single Axis



Omnidirectional
Round Smooth Feel



Omnidirectional
On-Axis and Off-Axis
Guided Feel**



Omnidirectional
Round On-Axis
Guided Feel

*Feel defined by shading.


**Full output available in all directions. Contact factory for details.

MINIATURE HALL EFFECT JOYSTICK


JHT
MINI
JOYSTICK

COMPACT DESIGN


OPTION AA




OPTION BB




OPTION CC




OPTION DD




OPTION EE



OPTION FF



OPTION GG



OPTION HH

