

## PRODUCT DATASHEET Lisa2 series

OSRAM LED Light for you

last update 10/4/2012



Ordering number C12469
Description C12469\_LISA2-R-PIN

Family Type Reflector LED Oslon SSL 80 Color White Diameter 9.9 mm Height 6.5 mm Style Round PC Optic Material Holder Material Fastening Glue, pin Status Ready

FWHM 76 degrees
Efficiency 92 %
cd/lm 0.500
Gerber File Available

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



## PRODUCT DATASHEET Lisa2 series



last update 10/4/2012

## **GENERAL INFORMATION**

- Product series especially designed & optimized for Oslon SSL 80 series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Reflector is made of aluminium coated PC (120 degrees of Celcius / 248 degrees of Fahrenheit) with protective lacquer (110 degrees of Celcius / 230 degrees of Fahrenheit).
- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet\_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

## Relative intensity of C12469\_LISA2-R-PIN (Seoul Z5)



