


APPLICABLE STANDARD		USB3.0 SPECIFICATION AND MICRO-USB CABLE AND CONNECTORS SPECIFICATION.				
RATING	OPERATING TEMPERATURE RANGE	-30°C TO +85°C		STORAGE TEMPERATURE RANGE	-30°C TO +60°C	
	VOLTAGE	-		OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT	-		APPLICABLE CABLE	OUTER DIAMETER OF CABLE : 3.3	
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS		QT AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X
MARKING		CONFIRMED VISUALLY.				X X
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
0						
REMARK HIROSE will not guarantee the performance on these specifications In case this product will be mated with the others which is not HIROSE's. Unless otherwise specified, refer to USB2.0 or EIA 364 .				APPROVED	AO.SUZUKI	09.06.16
				CHECKED	KN. ICHIKAWA	09.06.16
				DESIGNED	TS.SAKAIZAWA	09.06.15
				DRAWN	TS.SAKAIZAWA	09.06.15
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-127030-00
	SPECIFICATION SHEET			PART NO.	ZX360-B-SLDA	
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL242-0502-7-00	0 1/1