



PRODUCT/PROCESS CHANGE NOTIFICATION

PCN IPD-IPC/12/7448
Dated 18 Sep 2012

Voltage Reference, SOT23 Cu Wire Qualification in Carsem Malaysia

Table 1. Change Implementation Schedule

Forecasted implementation date for change	23-Nov-2012
Forecasted availability date of samples for customer	11-Sep-2012
Forecasted date for STMicroelectronics change Qualification Plan results availability	11-Sep-2012
Estimated date of changed product first shipment	18-Dec-2012

Table 2. Change Identification

Product Identification (Product Family/Commercial Product)	see attached list
Type of change	Package assembly material change
Reason for change	to improve service to ST Customers and standardize processes
Description of the change	Progressing on the activities related to quality improvement and along the plan of rationalizing the manufacturing processes, ST is glad to extend the implementation of CU Wire for the SOT23 package in the Carsem subcontractor (Malaysia). For the complete list of the part numbers affected by the change, please refer to the attached Products list. Samples of TS2431AILT and TS431AILT are available right now for immediate customer qualification, while the availability of other samples will be upon request.
Change Product Identification	QA number
Manufacturing Location(s)	

Table 3. List of Attachments

Customer Part numbers list	
Qualification Plan results	



DOCUMENT APPROVAL

Name	Function
Riviera, Antonio	Marketing Manager
Naso, Lorenzo	Product Manager
Motta, Antonino	Q.A. Manager

WHAT:

Progressing on the activities related to quality improvement and along the plan of rationalizing the manufacturing processes, ST is glad to extend the implementation of CU Wire for the SOT23 package in the Carsem subcontractor (Malaysia).

For the complete list of the part numbers affected by the change, please refer to the attached Products list.

Samples of TS2431AILT and TS431AILT are available right now for immediate customer qualification, while the availability of other samples will be upon request.

WHY:

This manufacturing change will improve service to ST Customers, standardize processes for the affected package.

HOW:

The qualification program mainly consists of reliability tests and comparative electrical characterization.

The related reliability report is annexed to this document.

The changes here reported do not affect the electrical, dimensional and thermal parameters of the products, keeping unchanged all information reported on the relevant datasheets.

WHEN:

The implementation will be finalized within Q3

Marking and traceability:

Unless otherwise stated by customer specific requirement, the traceability of the parts assembled with the new material set will be ensured by the Q.A. number.

The changes here reported will not affect the electrical, dimensional and thermal parameters keeping unchanged all information reported on the relevant datasheets.

There is as well no change in the packing process or in the standard delivery quantities.

Lack of acknowledgement of the PCN within 30 days will constitute acceptance of the change. After acknowledgement, lack of additional response within the 90 day period will constitute acceptance of the change (Jedec Standard No. 46-C).

In any case, first shipments may start earlier with customer's written agreement.



Reliability Report

CARSEM MALAYSIA SOT23 3L CU WIRE QUALIFICATION

T.V.: TS2431AILT – Line: U782

General Information		Locations	
Product Line	U782	Wafer fab	SINGAPORE Ang Mo Kio
Product Description	Programmable shunt voltage reference	Assembly plant	CARSEM M
P/N	TS2431AILT	Reliability Lab	IMS Catania Reliability Lab
Product Group	IPD	Reliability assessment	Pass
Product division	Industrial & Power Conversion		
Package	SOT23 3L		
Silicon Process technology	BCD 2 - 2S		

DOCUMENT INFORMATION

Version	Date	Pages	Prepared by	Approved by	Comment
1.1	26-Mar-2012	9	Stefania Motta	Giovanni Presti	FINAL

Note: This report is a summary of the reliability trials performed in good faith by STMicroelectronics in order to evaluate the potential reliability risks during the product life using a set of defined test methods.

This report does not imply for STMicroelectronics expressly or implicitly any contractual obligations other than as set forth in STMicroelectronics general terms and conditions of Sale. This report and its contents shall not be disclosed to a third party without previous written agreement from STMicroelectronics.



Quality and Reliability

TABLE OF CONTENTS

1	APPLICABLE AND REFERENCE DOCUMENTS	3
2	GLOSSARY.....	3
3	RELIABILITY EVALUATION OVERVIEW.....	3
3.1	OBJECTIVES	3
3.2	CONCLUSION	3
4	DEVICE CHARACTERISTICS.....	4
4.1	DEVICE DESCRIPTION	4
4.2	CONSTRUCTION NOTE	4
5	TESTS RESULTS SUMMARY.....	5
5.1	TEST VEHICLE	5
5.2	TEST PLAN AND RESULTS SUMMARY	6
6	ANNEXES.....	7
6.1	DEVICE DETAILS.....	7
6.2	TESTS DESCRIPTION.....	9



1 APPLICABLE AND REFERENCE DOCUMENTS

Document reference	Short description
JESD47	Stress-Test-Driven Qualification of Integrated Circuits

2 GLOSSARY

SS	Sample Size
----	-------------

3 RELIABILITY EVALUATION OVERVIEW

3.1 Objectives

Evaluation Process Change on SOT23 3L Cu wire qualification.

3.2 Conclusion

Qualification Plan requirements have been fulfilled without exception. It is stressed that reliability tests have shown that the devices be have correctly against environmental tests (no failure) until the final step @ 1000h. Moreover, the stability of electrical parameters during the accelerated tests demonstrates the ruggedness of the products and safe operation, which is consequently expected during their lifetime.



4 DEVICE CHARACTERISTICS

4.1 Device description

The TS2431 is a programmable shunt voltage reference with guaranteed temperature stability over the entire temperature range of operation -40 to +105°C. The output voltage may be set to any value between 2.5 and 24 V with an external resistor bridge.

Available in a SOT23-3 surface mount package, the device can be implemented in applications where space-saving is of utmost importance.

4.2 Construction note

P/N TS2431AILT	
Wafer/Die fab. information	
Wafer fab manufacturing location	Singapore Ang Mo Kio
Technology	BCD 2 - 2S
Process family	BCD2S
Die finishing back side	Lapped Silicon
Die size	1420, 760 micron
Bond pad metallization layers	2
Passivation type	P-Vapox(SiO ₂) / Nitride (SiN)
Wafer Testing (EWS) information	
Electrical testing manufacturing location	Ang Mo Kio EWS
Tester	ASL1K
Test program	TU782_1_0100.nx4
Assembly information	
Assembly site	Carsem M
Package description	SOT 23 3 LDS
Molding compound	Molding Compound Hitachi CEL82
Frame material	HDLF 3SOT23(438638) Copper AG
Die attach process	GLUE
Die attach material	QMI519 EPOXY
Die pad size	4X38MILS
Wire bonding process	Thermosonic
Wires bonding materials/diameters	1.0mil Cu wire
Final testing information	
Testing location	Carsem S
Tester	ASL1K
Test program	U782_2.nx4



5 TESTS RESULTS SUMMARY

5.1 Test vehicle

Lot #	Diffusion Lot	Assy Lot	Package	Product Line	Comments
1	6133N2H	ENG14201	SOT 23 3L	U78201	1°lot AVG WB Parameters
2		ENG14204			2°lot AVG WB Parameters
3		ENG14205			3°lot AVG WB Parameters
4		ENG14202			High WB Parameters
5		ENG14203			Low WB Parameters



Quality and Reliability

5.2 Test plan and results summary

P/N TS2431AILT


Test	PC	Std ref.	Conditions	SS	Steps	Failure/SS					note
						Lot 1 1°QUAL LOT	Lot 2 2°QUAL LOT	Lot 3 3°QUAL LOT	Lot 4 LOT HH	Lot 5 LOT LL	
Die Oriented Tests											
HTS	N	JESD22 A-103	T _j = 150°C	45	168 H	0/45	0/45	0/45	0/45	0/45	
					500 H	0/45	0/45	0/45	0/45	0/45	
					1000 H	0/45	0/45	0/45	0/45	0/45	
HTOL	N	JESD22 A-108	T _j = 125°C, bias= +6.1V	77	168 H	0/77					
					500 H	0/77					
					1000 H	0/77					
Package Oriented Tests											
PC		JESD22 A-113	Drying 24 H @ 125°C Store 168 H @ Ta=85°C Rh=85% Oven Reflow @ Tpeak=260°C 3 times	231	Final	Pass	Pass	Pass	Pass	Pass	
AC	Y	JESD22 A-102	Pa=2Atm / Ta=121°C	25	168 H	0/25	0/25	0/25	0/25	0/25	
TC	Y	JESD22 A-104	Ta = -65°C to 150°C	25	100 cy	0/25	0/25	0/25	0/25	0/25	
					300 cy	0/25	0/25	0/25	0/25	0/25	
					500 cy	0/25	0/25	0/25	0/25	0/25	
THB	Y	JESD22 A-101	Ta = 85°C, RH = 85%, bias= +5V	50	168 H	0/77					
					500 H	0/77					
					1000 H	0/77					

6 ANNEXES


6.1 Device details

6.1.1 Pin connection


Pin connections (top view)



6.1.2 Block diagram



6.1.3 Package outline/Mechanical data



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.89		1.12	0.035		0.044
A1	0.01		0.10	0.0004		0.004
A2	0.88	0.95	1.02	0.035	0.037	0.040
b	0.30		0.50	0.012		0.020
c	0.08		0.20	0.003		0.008
D	2.80	2.90	3.04	0.110	0.114	0.120
E	2.10		2.64	0.083		0.104
E1	1.20	1.30	1.40	0.047	0.051	0.055
e		0.95			0.037	
e1		1.90			0.075	
L	0.40	0.50	0.60	0.016	0.020	0.024
L1		0.54			0.021	
k	0d		8d			

6.2 Tests Description

Test name	Description	Purpose
Die Oriented		
HTSL High Temperature Storage Life	The device is stored in unbiased condition at the max. temperature allowed by the package materials, sometimes higher than the max. operative temperature.	To investigate the failure mechanisms activated by high temperature, typically wire-bonds solder joint ageing, data retention faults, metal stress-voiding.
HTOL High Temperature Operative Life	The device is stressed in static or dynamic configuration, approaching the operative max. Absolute ratings in terms of junction temperature and bias condition.	To determine the effects of bias conditions and temperature on solid state devices over time. It simulates the devices' operating condition in an accelerated way. The typical failure modes are related to, silicon degradation, wire-bonds degradation, oxide faults.
Package Oriented		
PC Preconditioning	The device is submitted to a typical temperature profile used for surface mounting devices, after a controlled moisture absorption.	As stand-alone test: to investigate the moisture sensitivity level. As preconditioning before other reliability tests: to verify that the surface mounting stress does not impact on the subsequent reliability performance. The typical failure modes are "pop corn" effect and delamination.
AC Auto Clave (Pressure Pot)	The device is stored in saturated steam, at fixed and controlled conditions of pressure and temperature.	To investigate corrosion phenomena affecting die or package materials, related to chemical contamination and package hermeticity.
TC Temperature Cycling	The device is submitted to cycled temperature excursions, between a hot and a cold chamber in air atmosphere.	To investigate failure modes related to the thermo-mechanical stress induced by the different thermal expansion of the materials interacting in the die-package system. Typical failure modes are linked to metal displacement, dielectric cracking, molding compound delamination, wire-bonds failure, die-attach layer degradation.
THB Temperature Humidity Bias	The device is biased in static configuration minimizing its internal power dissipation, and stored at controlled conditions of ambient temperature and relative humidity.	To evaluate the package moisture resistance with electrical field applied, both electrolytic and galvanic corrosion are put in evidence.



Reliability Report

Voltage References

CARSEM MALAYSIA SOT23 5L CU WIRE QUALIFICATION

T.V.: TS431AILT

Line S43101

Technology BICMOS 2

Packages: SOT23 5L

General Information		Locations	
Product Line	S43101	Wafer fab	Ang Mo Kio
Product Description	LOW VOLTAGE ADJUSTABLE SHUNT REFERENCE	Assembly plant	Carsem
P/N	TS431AILT	Reliability Lab	IMS Catania Reliability Lab
Product Group	IPD IND.& POWER CONV	Reliability assessment	Pass
Product division	Linear Voltage Regulators & Vref		
Packages	SOT23 5L		
Silicon Process technology	BICMOS 2		

DOCUMENT INFORMATION

Version	Date	Pages	Prepared by	Approved by	Comment
1.0	20 June 2012	8	Angelo Basile	Giovanni Presti	Final report

Note: This report is a summary of the reliability trials performed in good faith by STMicroelectronics in order to evaluate the potential reliability risks during the product life using a set of defined test methods.

This report does not imply for STMicroelectronics expressly or implicitly any contractual obligations other than as set forth in STMicroelectronics general terms and conditions of Sale. This report and its contents shall not be disclosed to a third party without previous written agreement from STMicroelectronics. .



TABLE OF CONTENTS

1	APPLICABLE AND REFERENCE DOCUMENTS	3
2	GLOSSARY.....	3
3	RELIABILITY EVALUATION OVERVIEW.....	3
3.1	OBJECTIVES	3
3.2	CONCLUSION.....	3
3.3	DEVICE DESCRIPTION.....	4
4	TESTS RESULTS SUMMARY.....	5
4.1	TEST VEHICLE.....	5
4.2	TEST PLAN AND RESULTS SUMMARY.....	5
5	ANNEXES	6
5.1	DEVICE DETAILS.....	6
5.2	TESTS DESCRIPTION.....	8



1 APPLICABLE AND REFERENCE DOCUMENTS

Document reference	Short description
JESD47	Stress-Test-Driven Qualification of Integrated Circuits

2 GLOSSARY

SS	Sample Size
----	-------------

3 RELIABILITY EVALUATION OVERVIEW

3.1 Objectives

Carsem Malaysia SOT23 5L Cu Wire Qualification

3.2 Conclusion

Qualification Plan requirements have been fulfilled without exception. It is stressed that reliability tests have shown that the devices behave correctly against environmental tests (no failure in the available steps). Moreover, the stability of electrical parameters during the accelerated tests demonstrates the ruggedness of the products and safe operation

The evaluation results are positive

3.3 Device description

The TS431 is a low-voltage, three-terminal, programmable shunt voltage reference. The output voltage can be set to any value between Vref (1.24 V) and 6 V with two external resistors. The TS431 is able to operate at a lower voltage (1.24 V) and lower cathode current than the widely used TL431 and TL1431 shunt voltage reference. When driving an opt coupler, the TS431 is particularly useful for regulating 3.3 V switching power supplies

Construction note

P/N	
TS431AILT SOT23 5	
Wafer/Die fab. information	
Wafer fab manufacturing location	Carsem
Technology	BICMOS 2
Die finishing back side	Raw Silicon Back Grinding
Die size	900 x1350 um
Passivation type	P-Vapox(Sio2) / Nitride (Sin)
Wafer Testing (EWS) information	
Electrical testing manufacturing location	Singapore Ang Mo Kio
Tester	ASL1K
Test program	Vref_S431_0100.nx4
Assembly information	
Assembly site	Carsem
Package description	SOT 23-5
Molding compound	Hitachi CEL8240
Frame material	Copper Ag Spot (frame code 4)
Die attach process	Glue
Die attach material	QMI519 EPOXY
Wire bonding process	Thermosonic Bonding
Wires bonding materials/diameters	1.0mil Cu wire
Lead finishing process	Electroplating
Lead finishing/bump solder material	100% Pure Matter Tin
Final testing information	
Testing location	Carsem
Tester	ASL1K
Test program	TS431_1.nx4



4 TESTS RESULTS SUMMARY

4.1 Test vehicle

Lot #	Diffusion Lot	Assy Lot	Package	Product Line	Comments
1	61396X9	15205	SOT23 5L	S43101	1 st Lot
2		15201			2 nd Lot
3		15204			3 rd Lot
4		15203			Corner Lot HH
5		15202			Corner Lot LL

4.2 Test plan and results summary


P/N TL431IDT

Test	PC	Std ref.	Conditions	SS	Steps	Failure/SS				
						1 st Lot	2 nd Lot	3 rd Lot	Corner Lot HH	Corner Lot LL
Die Oriented Tests										
HTOL	N	JESD22 A-108	T _j = 125°C, BIAS=+5V		168 H	0/77				
					500 H	0/77				
					1000 H	0/77				
HTSL	N	JESD22 A-103	Ta = 150°C		168 H	0/25	0/25	0/25	0/25	0/25
					500 H	0/25	0/25	0/25	0/25	0/25
					1000 H	0/25	0/25	0/25	0/25	0/25
Package Oriented Tests										
AC	Y	JESD22 A-102	Pa=2Atm / Ta=121°C		96 H					
					168 H	0/25	0/25	0/25		
TC	Y	JESD22 A-104	Ta = -65°C to 150°C		100 cy	0/25	0/25	0/25	0/25	0/25
					200 cy	0/25	0/25	0/25	0/25	0/25
					500 cy	0/25	0/25	0/25	0/25	0/25
THB	Y	JESD22 A-101	Ta = 85°C, RH=85%, BIAS =+3V		168 H	0/25	0/25	0/25		
					500 H	0/25	0/25	0/25		
					1000 H	0/25	0/25	0/25		
Other Tests										
ESD	N	AEC Q101-001, 002 and 005	HBM	3	+/- 2KV	PASS				
			MM	3	+/- 0.3KV	PASS				
			CDM	3	+/-500V all pins+/-750V corner pins	PASS				
WBP	N	MIL-STD-883-2011	Wire Bond Pull	10	Final	0/5	0/5			

5 ANNEXES

5.1 Device details

5.1.1 Pin connection




* Do not connect this pin or
connect it to Anode

5.1.2 Package outline/Mechanical data

Table 4. SOT23-5 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.90		1.45	0.035		0.057
A1	0.00		0.15	0.00		0.006
A2	0.90		1.30	0.035		0.051
b	0.35		0.50	0.014		0.02
C	0.09		0.20	0.003		0.008
D	2.80		3.00	0.110		0.118
H	2.60		3.00	0.102		0.118
E	1.50		1.75	0.059		0.069
e		0.95			0.037	
e1		1.9			0.075	
L	0.35		0.55	0.014		0.022





5.2 Tests Description

Test name	Description	Purpose
Die Oriented		
HTOL High Temperature Operative Life	The device is stressed in static or dynamic configuration, approaching the operative max. absolute ratings in terms of junction temperature and bias condition.	To determine the effects of bias conditions and temperature on solid state devices over time. It simulates the devices' operating condition in an accelerated way. The typical failure modes are related to, silicon degradation, wire-bonds degradation, oxide faults.
HTSL High Temperature Storage Life	The device is stored in unbiased condition at the max. temperature allowed by the package materials, sometimes higher than the max. operative temperature.	To investigate the failure mechanisms activated by high temperature, typically wire-bonds solder joint ageing, data retention faults, metal stress-voiding.
Package Oriented		
AC Auto Clave (Pressure Pot)	The device is stored in saturated steam, at fixed and controlled conditions of pressure and temperature.	To investigate corrosion phenomena affecting die or package materials, related to chemical contamination and package hermeticity.
TC Temperature Cycling	The device is submitted to cycled temperature excursions, between a hot and a cold chamber in air atmosphere.	To investigate failure modes related to the thermo-mechanical stress induced by the different thermal expansion of the materials interacting in the die-package system. Typical failure modes are linked to metal displacement, dielectric cracking, molding compound delamination, wire-bonds failure, die-attach layer degradation.
THB Temperature Humidity Bias	The device is biased in static configuration minimizing its internal power dissipation, and stored at controlled conditions of ambient temperature and relative humidity.	To evaluate the package moisture resistance with electrical field applied, both electrolytic and galvanic corrosion are put in evidence.
Other Tests		
ESD Electro Static Discharge	The device is submitted to a high voltage peak on all his pins simulating ESD stress according to different simulation models. CBM: Charged Device Model HBM: Human Body Model MM: Machine Model	To classify the device according to his susceptibility to damage or degradation by exposure to electrostatic discharge.
WBP Wire Bond Pull	This test may be applied to the wire-to-die bond, wire-to-substrate bond, or the wire-to-package lead bond inside the package of wire-connected microelectronic devices bonded by soldering, thermo-compression, ultrasonic, or related techniques.	The purpose of this test is to measure bond strengths, evaluate bond strength distributions, or determine compliance with specified bond strength requirements of the applicable acquisition document.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND / OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners

© 2012 STMicroelectronics - All rights reserved.

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com



Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND / OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners

© 2012 STMicroelectronics - All rights reserved.

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com





Public Products List

PCN Title : Voltage Reference, SOT23 Cu Wire Qualification in Carsem Malaysia

PCN Reference : IPD-IPC/12/7448

PCN Created on : 01-OCT-2012

Subject : Public Products List

Dear Customer,

Please find below the Standard Public Products List impacted by the change:

ST COMMERCIAL PRODUCT

LM4041AELT-1.2	LM4041AILT-1.2	LM4041BELT-1.2
LM4041BILT-1.2	LM4041CELT-1.2	LM4041CILT-1.2
LM4041DELT-1.2	LM4041DILT-1.2	TL431ACL3T
TL431ACL5T	TL431AIL3T	TL431AIL5T
TL431CL3T	TL431CL5T	TL431IL3T
TL431IL5T	TL432AIL3T	TL432IL3T
TLVH431AIL3T	TLVH431AIL5T	TLVH431BIL3T
TLVH431BIL5T	TS2431AILT	TS2431BILT
TS2431ILT	TS3431AILT	TS3431BILT
TS3431CILT	TS3431ILT	TS4040DILT-2.5
TS4040EILT-2.5	TS4041CILT-1.2	TS4041DILT-1.2
TS4041EILT-1.2	TS431AILT	TS431BILT
TS431ILT	TS432AILT	TS432ILT
TS4431AILT	TS4431ILT	TS821AILT
TS821BILT	TS821ILT	TS822AILT
TS822ILT	TS824AILT-2.5	TS824ILT-1.2
TS824ILT-2.5		

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND / OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners

© 2012 STMicroelectronics - All rights reserved.

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com