



12500 TI Boulevard, MS 8640, Dallas, Texas 75243

**PCN# 20130801000
Datasheet update for CDCUN1208LP
Information Only**

Date: 8/5/2013
To: MOUSER PCN

Dear Customer:

This is an information-only announcement of a change to a device that is currently offered by Texas Instruments.

The changes discussed within this PCN are for your information only. Please see the attachment details for the planned implementation date.

This notification period is per TI's standard process. Any negotiated alternative change requirements will be provided via the customer's defined process. Customers with previously negotiated, special requirements will be handled separately. Any inquiries should be directed to your local Field Sales Representative.

For questions regarding this notice, contact your local Field Sales Representative or the PCN Manager (PCN_ww_admin_team@list.ti.com).

Sincerely,

PCN Team
SC Business Services
Phone: +1(214) 480-6037
Fax: +1(214) 480-6659


20130801000
Attachment: 1

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE	CUSTOMER PART NUMBER
CDCUN1208LPRHBT	null

Technical details of this Product Change follow on the next page(s).

PCN Number:	20130801000			PCN Date:	08/05/2013
Title:	CDCUN1208LP Data Sheet				
Customer Contact:	PCN Manager	Phone:	+1(214) 480-6037	Dept:	Quality Services
Change Type:	<input checked="" type="checkbox"/> Electrical Specification				
PCN Details					
Description of Change:					
<p>The product datasheet(s) is being updated to add slew rate note to RECOMMENDED OPERATING CONDITIONS, which describes that a minimum VDD slew rate must be obtained. Changed VIOpen1.8 from 0.9 V to 0.75 V in DIGITAL INPUT ELECTRICAL CHARACTERISTICS – OE (SCL), INSEL, ITP, OTTP, DIVIDE (SDA/MOSI), ERC(ADDR/CS), MODE and changed Figure 28.</p> <p>The product datasheet(s) is being updated:</p>					
 <div style="float: right;">CDCUN1208LP</div>					
www.ti.com <div style="float: right;">SCAS928B – MAY 2012–REVISED JULY 2013</div>					
Changes from Revision A (January 2013) to Revision B <div style="float: right;">Page</div>					
<ul style="list-style-type: none"> Added slew rate note to RECOMMENDED OPERATING CONDITIONS 5 Changed VIOpen1.8 from 0.9 V to 0.75 V in DIGITAL INPUT ELECTRICAL CHARACTERISTICS – OE (SCL), INSEL, ITP, OTTP, DIVIDE (SDA/MOSI), ERC(ADDR/CS), MODE 6 Changed Fast to Medium and Medium to Fast in Figure 28 19 					
The datasheet number will be changing.					
Device Family		Change From:	Change To:		
CDCUN1208LP		SCAS928A	SCAS928B		
The updated datasheet(s) can be accessed by the following link(s): http://www.ti.com/product/cdcun1208lp					
Reason for Change:					
To more accurately reflect device characteristics					
Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):					
Electrical specification performance changes as indicated above.					
Changes to product identification resulting from this PCN:					
None					
Product Affected:					
CDCUN1208LPRHBR		CDCUN1208LPRHBT			

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com