



12500 TI Boulevard, MS 8640, Dallas, Texas 75243

PCN#20141119000

**Qualification of Alternate Assembly/Test Sites for Selected devices in the TSSOP
Package
Change Notification / Sample Request**

Date: 12/3/2014
To: MOUSER PCN

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

We request you acknowledge receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If you require samples or additional data to support your evaluation, please request within 30 days.

The changes discussed within this PCN will not take effect any earlier than **90** days from the date of this notification, unless customer agreement has been reached on an earlier implementation of the change. This notification period is per TI's standard process.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice, contact your local Field Sales Representative or the PCN Manager (PCN_ww_admin_team@list.ti.com).

Sincerely,

PCN Team
SC Business Services
Phone: +1(214) 480-6037
Fax: +1(214) 480-6659

20141119000
Attachment: 1



Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE	CUSTOMER PART NUMBER
AM26C31IPWR	null
CD4066BPWR	null
CD4069UBPWR	null
CD4541BPWR	null
CD74HC123PWR	null
DRV8833PWP	null
DRV8833PWPR	null
LM239PWR	null
LM339APWR	null
MAX232ECPWR	null
MAX3232IPWR	null
SN74ACT08PWR	null
SN74AHCT125PWR	null
SN74HC00PWR	null
SN74HC02PWR	null
SN74HC04PWR	null
SN74HC05PWR	null
SN74HC08PWR	null
SN74HC125PWR	null
SN74HC138PWR	null
SN74HC14PWR	null
SN74HC164PWR	null
SN74HC166PWR	null
SN74HC174PWR	null
SN74HC259PWR	null
SN74HC32PWR	null
SN74HC595PWR	null
SN74HCT04PWR	null
SN74HCT138PWR	null
SN74HCT14PWR	null
SN74HCT32PWR	null
SN74HCU04PWR	null

Technical details of this Product Change follow on the next page(s).

PCN Number:	20141119000		PCN Date:	12/03/2014													
Title:	Qualification of ASE Shanghai as an alternate Assembly/Test Site for Selected devices in the TSSOP Package																
Customer Contact:	PCN Manager		Phone:	+1(214)480-6037													
Dept:	Quality Services																
Proposed 1st Ship Date:	03/03/2015		Estimated Sample Availability:	Provided upon Request													
Change Type:																	
<input checked="" type="checkbox"/>	Assembly Site	<input type="checkbox"/>	Assembly Process	<input checked="" type="checkbox"/>	Assembly Materials												
<input type="checkbox"/>	Design	<input type="checkbox"/>	Electrical Specification	<input type="checkbox"/>	Mechanical Specification												
<input checked="" type="checkbox"/>	Test Site	<input type="checkbox"/>	Packing/Shipping/Labeling	<input type="checkbox"/>	Test Process												
<input type="checkbox"/>	Wafer Bump Site	<input type="checkbox"/>	Wafer Bump Material	<input type="checkbox"/>	Wafer Bump Process												
<input type="checkbox"/>	Wafer Fab Site	<input type="checkbox"/>	Wafer Fab Materials	<input type="checkbox"/>	Wafer Fab Process												
	<input type="checkbox"/>	Part number change															
PCN Details																	
Description of Change:																	
<p>Texas Instruments is pleased to announce the qualification of ASE Shanghai (ASES) as an alternate Assembly and Test site for the devices listed below in Group 1 and TI Taiwan (TAI) as an additional Assembly site for the devices in Group 2. Group 2 devices will have identical BOMs between the 2 sites. For group 1, BOM differences are noted in the table below:</p> <table border="1"> <thead> <tr> <th>What</th> <th>MLA</th> <th>AP1</th> <th>ASESH</th> </tr> </thead> <tbody> <tr> <td>Mold Compound</td> <td>4206193</td> <td>SID# 101325962</td> <td>SID#EN2000508</td> </tr> <tr> <td>Mound Compound</td> <td>4042500</td> <td>SID#101306338</td> <td>SID#EY1000063</td> </tr> </tbody> </table> <p>Test coverage, insertions, conditions will remain consistent with current testing and verified with test MQ.</p>						What	MLA	AP1	ASESH	Mold Compound	4206193	SID# 101325962	SID#EN2000508	Mound Compound	4042500	SID#101306338	SID#EY1000063
What	MLA	AP1	ASESH														
Mold Compound	4206193	SID# 101325962	SID#EN2000508														
Mound Compound	4042500	SID#101306338	SID#EY1000063														
Reason for Change:																	
Continuity of Supply																	
Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):																	
None																	

Changes to product identification resulting from this PCN:		
Assembly Site		
Amkor Philippines	Assembly Site Origin (22L)	ASO: AKR
TI Malaysia	Assembly Site Origin (22L)	ASO: MLA
TI Taiwan	Assembly Site Origin (22L)	ASO: TAI
ASE Shanghai	Assembly Site Origin (22L)	ASO: ASH
Sample product shipping label (not actual product label)		
 TEXAS INSTRUMENTS MADE IN: Malaysia 2DC: 20: MSL 2 /260C/1 YEAR SEAL DT MSL 1 /235C/UNLIM 03/29/04 OPT: ITEM: 39 LBL: 5A (L)T0:1750		(1P) SN74LS07NSR (Q) 2000 (D) 0336 (31T) LOT: 3959047MLA (4W) TKY (1T) 7523483SI2 (P) (2P) REV: (V) 0033317 (20L) CSO: SHE (21L) CCO:USA (22L) ASO: MLA (23L) ACO: MYS

Topside Device marking:

Assembly site code for AKR= 4

Assembly site code for MLA= K

Assembly site code for TAI= T**Assembly site code for ASH= A****Product Affected****Qualification Group #1 Devices (ASESH assembly):**

AM26C31IPWR	MAX3232IPWR	SN74HC125PWR	SN74HC32PWR
CD4066BPWR	SN74ACT08PWR	SN74HC138PWR	SN74HC595PWR
CD4069UBPWR	SN74AHCT125PWR	SN74HC14PWR	SN74HCT04PWR
CD4541BPWR	SN74HC00PWR	SN74HC164PWR	SN74HCT138PWR
CD74HC123PWR	SN74HC02PWR	SN74HC166PWR	SN74HCT14PWR
LM239PWR	SN74HC04PWR	SN74HC174PWR	SN74HCT32PWR
LM339APWR	SN74HC05PWR	SN74HC259PWR	SN74HCU04PWR
MAX232ECPWR	SN74HC08PWR		

Qualification Group #2 Devices (TAI assembly):

DRV8833PWP	DRV8833PWPR
------------	-------------

Qualification Group #1 Data:**Qualification Report**

MAX232ECPWR Qual (ASESH 14 and 16 pins TSSOP Offload)

Approved 09/22/2014

Product Attributes

Attributes	Qual Device: MAX232ECPWR	QBS Package: RC4558PWR	QBS Package: SN74LV14APWR	QBS Package: SN74LV14APWR	QBS Package: ULN2003APW	QBS Package: LMV324IPWR	QBS Package: SN74AHC595PWR	QBS Package: SN74CBT3306PWR	QBS Package: SN74CBTLV3245APWR
Assembly Site	ASESH	ASE SHANGHAI	ASESH	ASESH	ASESH	ASE SHANGHAI	ASE SHANGHAI	ASE SHANGHAI	ASE SHANGHAI
Package Family	TSSOP	TSSOP	TSSOP	TSSOP	TSSOP	TSSOP	TSSOP	TSSOP	TSSOP
Flammability Rating	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0
Wafer Fab Process	DFAB	SFAB	SFAB	FFAB	SFAB	FFAB	SFAB	SFAB	FFAB
Wafer Fab Supplier	LBC3S	JI-SLM	EPIC1-S_SLM	P-9750 TLM	JI-SLM	BCB	EPIC1S DLM	50C24X2	ASL3C

- QBS: Qual By Similarity

- Qual Device MAX232ECPWR is qualified at LEVEL1-260C

Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	Test Name / Condition	Duration	QBS Package: RC4558PWR	QBS Package: SN74LV14APWR	QBS Package: SN74LV14APWR	QBS Package: ULN2003APW	QBS Package: LMV324IPWR	QBS Package: SN74AHC595PWR	QBS Package: SN74CBT3306PWR	QBS Package: SN74CBTLV3245APWR
HAST	Biased HAST, 130C/85%RH	96 Hours	1/77/0	1/77/0	1/77/0	1/77/0	2/158/0	1/77/0	1/77/0	1/77/0
THB	Temperature Humidity Bias 85C/85%RH	1000 Cycles	-	-	-	-	-	-	-	-
AC	Autoclave 121C	96 Hours	-	-	-	-	-	-	-	-
UHAST	Unbiased HAST 130C/85%RH	96 Hours	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0
TC	Temperature Cycle, -65/150C	500 Cycles	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0	1/77/0
HTSL	High Temp. Storage Bake 170C	420 Hours	-	-	-	-	1/77/0	1/77/0	1/77/0	1/77/0
HTSL	High Temp. Storage Bake 150C	1000 Hours	1/77/0	1/77/0	1/77/0	1/77/0	-	-	-	-
HTOL	Life Test, 150C	300 hours	1/77/0	1/77/0	1/77/0	1/77/0	2/164/0	1/77/0	1/77/0	1/77/0
WBS	Ball Bond Shear	Wires	-	-	-	-	-	-	-	-
WBP	Bond Pull	Wires	-	-	-	-	-	-	-	-
PD	Physical Dimensions	-	-	-	-	-	-	-	-	-
HBM	ESD - HBM	1000 V	-	-	-	-	-	-	-	-
CDM	ESD - CDM	250 V	-	-	-	-	-	-	-	-
LU	CMOS Latchup	(per JESD78 class II)	-	-	-	-	-	-	-	-
ED	Electrical Characterization	Per Datasheet Parameters	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
	Bond Strength	Wires	1/76/0	1/76/0	1/76/0	1/76/0	2/160/0	1/77/0	1/77/0	1/77/0

- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

- The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

- The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours

- The following are equivalent Temp Cycle options per JESD47 : -65C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

Green/Pb-free Status:

Qualified Pb-Free(SMT) and Green

Qualification Group #2 Data:

Reference Qualification Data: Approved April 2012		
This qualification has been specifically developed for the validation of this change. The qualification data validates that the proposed change meets the applicable released technical specifications.		
Qualification Device: DRV8812A1PWP (MSL1-260C)		
Package Construction Details		
Assembly Site:	TAI A/T	Mold Compound: 4205443
# Pins-Designator, Family:	28-PWP, TSSOP	Mount Compound: 4208458
Lead Frame Material/Finish:	Cu, NiPdAu	Bond Wire: 1.3 Mil Dia., Cu
Qualification: <input type="checkbox"/> Plan <input checked="" type="checkbox"/> Test Results		
Reliability Test	Conditions	Sample Size / Fail
Electrical Characterization	Per Datasheet Limits	Pass
**Autoclave 121C	121C, 2 atm (96 Hrs)	77/0
**T/C -65C/150C	-65C/+150C (500 Cyc)	77/0
ESD HBM	500V, 1000V, 1500V	3/0
ESD CDM	200V, 500V	3/0
Latch-up	(per JESD78)	6/0
Notes: **Tests require preconditioning sequence: MSL1-260C		

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com