



12500 TI Boulevard, MS 8640, Dallas, Texas 75243

**PCN# 20240325002.2**  
**Qualification of RFAB as an additional Fab site option and**  
**additional Assembly BOM options for select devices**  
**Change Notification / Sample Request**

**Date:** March 26, 2024  
**To:** MOUSER PCN

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

Texas Instruments requires acknowledgement of receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance and approval of this change. If samples or additional data are required, requests must be received within **30 days** of this notification.

The changes discussed within this PCN will not take effect any earlier than the proposed first ship date on Page 3 of this notification, unless customer agreement has been reached on an earlier implementation of the change.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the change management team.

For sample requests or sample related questions, contact your local Field Sales Representative.

Sincerely,

Change Management Team  
SC Business Services

**20240325002.2**  
**Attachment: 1**

**Products Affected:**

The devices listed on this page are a subset of the complete list of affected devices. According to our records, you have recently purchased these devices. The corresponding customer part number is also listed, if available.

<b>DEVICE</b>	<b>CUSTOMER PART NUMBER</b>
UCC5320SCDWVR	NULL
UCC5350MCQDWVRQ1	NULL
UCC5390ECQDWVRQ1	NULL

Technical details of this Product Change follow on the next page(s).

<b>PCN Number:</b>	20240325002.2		<b>PCN Date:</b>	March 26, 2024	
<b>Title:</b>	Qualification of RFAB as an additional Fab site option and additional Assembly BOM options for select devices				
<b>Customer Contact:</b>	Change Management team		<b>Dept:</b>	Quality Services	
<b>Proposed 1<sup>st</sup> Ship Date:</b>	September 22, 2024		<b>Sample requests accepted until:</b>	April 25, 2024*	
*Sample requests received after April 25, 2024 will not be supported.					
<b>Change Type:</b>					
<input type="checkbox"/>	Assembly Site	<input type="checkbox"/>	Design	<input type="checkbox"/>	Wafer Bump Material
<input checked="" type="checkbox"/>	Assembly Process	<input type="checkbox"/>	Data Sheet	<input type="checkbox"/>	Wafer Bump Process
<input checked="" type="checkbox"/>	Assembly Materials	<input type="checkbox"/>	Part number change	<input checked="" type="checkbox"/>	Wafer Fab Site
<input type="checkbox"/>	Mechanical Specification	<input type="checkbox"/>	Test Site	<input checked="" type="checkbox"/>	Wafer Fab Material
<input type="checkbox"/>	Packing/Shipping/Labeling	<input type="checkbox"/>	Test Process	<input type="checkbox"/>	Wafer Fab Process
<b>PCN Details</b>					
<b>Description of Change:</b>					
Texas Instruments is pleased to announce the qualification of its RFAB fabrication facility as an additional Wafer Fab option in addition to Assembly BOM options for the devices listed below.					
<b>Current Fab Site</b>			<b>Additional Fab site</b>		
<b>Current Fab Site</b>	<b>Process</b>	<b>Wafer Diameter</b>	<b>Additional Fab site</b>	<b>Process</b>	<b>Wafer Diameter</b>
DP1DM5	LBC8LVISO	200mm	RFAB	LBC8LVISO	300mm
Construction differences are as follows:					
<b>Group 1 device:</b>					
	<b>Current</b>	<b>Proposed</b>			
Wire diam/type	0.96mil Au, 1.0mil Cu	0.80mil Cu			
<b>Group 2 device:</b>					
	<b>Current</b>	<b>Proposed</b>			
Wire diam/type	0.96mil Au	0.80mil Cu			
Qual details are provided in the Qual Data Section.					
<b>Reason for Change:</b>					
Supply Continuity					
<b>Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):</b>					
None					
<b>Impact on Environmental Ratings</b>					

Checked boxes indicate the status of environmental ratings following implementation of this change. If below boxes are checked, there are no changes to the associated environmental ratings.

<input checked="" type="checkbox"/> <b>RoHS</b>	<input checked="" type="checkbox"/> <b>REACH</b>	<input checked="" type="checkbox"/> <b>Green Status</b>	<input checked="" type="checkbox"/> <b>IEC 62474</b>
<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change

**Changes to product identification resulting from this PCN:**

**Fab Site Information:**

Chip Site	Chip Site Origin Code (20L)	Chip Site Country Code (21L)	Chip Site City
DP1DM5	DM5	USA	Dallas
<b>RFAB</b>	<b>RFB</b>	<b>USA</b>	<b>Richardson</b>

**Group 1 Product Affected:**

UCC5320SCDWVR

**Group 2 Product Affected:**

SN5350MCQDWVQ1	UCC5350MCQDWVRQ1
SN5350MCQDWVRQ1	UCC5390ECQDWVRQ1

**Qualification Report**

Automotive Qualification Summary  
 (As per AEC-Q100 Rev. H and JEDEC Guidelines)  
 Approve Date 20-December-2023

**Product Attributes**

Attributes	Qual Device: <u>SN5350MCQDWVRQ1</u>	QBS Package, Process Reference: <u>UCC23513QDWYQ1</u>	QBS Package Reference: <u>UCC21540QDWKRO1</u>
Automotive Grade Level	Grade 1	Grade 1	Grade 1
Operating Temp Range (C)	-40 to 125	-40 to 125	-40 to 125
Product Function	Power Management	Power Management	Power Management
Wafer Fab Supplier	RFAB, RFAB	RFAB, RFAB	MH8, MH8, MH8
Assembly Site	TAI	TAI	TAI
Package Group	SOIC	SOIC	SOIC
Package Designator	DWV	DWY	DWK
Pin Count	8	6	14

QBS: Qual By Similarity  
 Qual Device SN5350MCQDWVRQ1 is qualified at MSL2 260C

**Qualification Results**

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Spec	Min Lot Qty	SS / Lot	Test Name	Condition	Duration	Qual Device:	QBS Package, Process Reference:	QBS Package Reference:
								<u>SN5350MCQDWWRQ1</u>	<u>UCC23513QDWYQ1</u>	<u>UCC21540QDWKRQ1</u>
<b>Test Group A - Accelerated Environment Stress Tests</b>										
PC	A1	JEDEC J-STD-020 JESD22-A113	3	77	Preconditioning	MSL2 260C	-	3/Pass	3/Pass	1/Pass
HAST	A2	JEDEC JESD22-A110	3	77	Biased HAST	130C/85%RH	96 Hours	-	3/231/0	1/77/0
AC/UHAST	A3	JEDEC JESD22-A102/JEDEC JESD22-A118	3	77	Autoclave	121C/15psig	96 Hours	3/231/0	3/231/0	3/231/0
TC	A4	JEDEC JESD22-A104 and Appendix 3	3	77	Temperature Cycle	-65C/150C	500 Cycles	3/231/0	3/231/0	1/77/0
TC-BP	A4	MIL-STD883 Method 2011	1	5	Post Temp Cycle Bond Pull	-	-	1/5/0	-	-
HTSL	A6	JEDEC JESD22-A103	1	45	High Temperature Storage Life	150C	1000 Hours	-	-	1/45/0
HTSL	A6	JEDEC JESD22-A103	1	45	High Temperature Storage Life	175C	500 Hours	-	3/135/0	-
<b>Test Group B - Accelerated Lifetime Simulation Tests</b>										
HTOL	B1	JEDEC JESD22-A108	3	77	Life Test	125C	1000 Hours	-	3/231/0	-
ELFR	B2	AEC Q100-008	3	800	Early Life Failure Rate	125C	48 Hours	-	3/2400/0	-
<b>Test Group C - Package Assembly Integrity Tests</b>										
WBS	C1	AEC Q100-001	1	30	Wire Bond Shear	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0	3/90/0
WBP	C2	MIL-STD883 Method 2011	1	30	Wire Bond Pull	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0	3/90/0
SD	C3	JEDEC J-STD-002	1	15	PB Solderability	>95% Lead Coverage	-	-	1/15/0	-
SD	C3	JEDEC J-STD-002	1	15	PB-Free Solderability	>95% Lead Coverage	-	-	1/15/0	-
PD	C4	JEDEC JESD22-B100 and B108	3	10	Physical Dimensions	Cpk>1.67	-	3/30/0	-	-
<b>Test Group D - Die Fabrication Reliability Tests</b>										
EM	D1	JESD61	-	-	Electromigration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
TDDB	D2	JESD35	-	-	Time Dependent Dielectric Breakdown	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
HCI	D3	JESD60 & 28	-	-	Hot Carrier Injection	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
BTI	D4	-	-	-	Bias Temperature Instability	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
SM	D5	-	-	-	Stress Migration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements

Test Group E - Electrical Verification Tests										
ESD	E2	AEC Q100-002	1	3	ESD HBM	-	2000 Volts	1/3/0	-	-
ESD	E3	AEC Q100-011	1	3	ESD CDM	-	500 Volts	1/3/0	-	-
LU	E4	AEC Q100-004	1	6	Latch-Up	Per AEC Q100-004	-	1/6/0	-	-
ED	E5	AEC Q100-009	3	30	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	3/90/0	-	-

Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours

The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

**Ambient Operating Temperature by Automotive Grade Level:**

Grade 0 (or E): -40C to +150C

Grade 1 (or Q): -40C to +125C

Grade 2 (or T): -40C to +105C

Grade 3 (or I): -40C to +85C

**E1 (TEST): Electrical test temperatures of Qual samples (High temperature according to Grade level):**

Room/Hot/Cold : HTOL, ED

Room/Hot : THB / HAST, TC / PTC, HTSL, ELFR, ESD & LU

Room : AC/uHAST

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

## Qualification Report

Automotive New Product Qualification Summary  
(As per AEC-Q100, AEC-Q006, and JEDEC Guidelines)  
Approve Date 19-OCTOBER -2023

### Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Spec	Min Lot Qty	SS / Lot	Test Name	Condition	Duration	Qual Device: <u>ISO6763QDWRQ1</u>	Qual Device: <u>UCC21540QDWRQ1</u>
<b>Test Group A - Accelerated Environment Stress Tests</b>									
PC	A1	JEDEC J-STD-020 JESD22-A113	3	77	Preconditioning	MSL2 260C	-	3/597/0	1/199/0
PC	A1.1	-	3	22	SAM Precon Pre	Review for delamination	-	3/66/0	1/22/0
PC	A1.2	-	3	22	SAM Precon Post	Review for delamination	-	3/66/0	1/22/0
HAST	A2.1	JEDEC JESD22-A110	3	77	Biased HAST	130C/85%RH	96 Hours	3/231/0	1/77/0
HAST	A2.1.2	-	3	1	Cross Section, post bHAST, 1X	Post stress cross section	Completed	-	-
HAST	A2.1.3	-	3	3	Wire Bond Shear, post bHAST, 1X	Post stress	-	-	-
HAST	A2.1.4	-	3	30	Bond Pull over Stitch, post bHAST, 1X	Post stress	Wires	-	-

HAST	A2.1.5	-	3	3	Bond Pull over Ball, post bHAST, 1X	Post stress	-	-	-
HAST	A2.2	JEDEC JESD22-A110	3	70	Biased HAST	130C/85%RH	192 Hours	3/210/0	1/70/0
HAST	A2.2.1	-	3	22	SAM Analysis, post bHAST 2X	Review for delamination	Completed	3/66/0	1/22/0
HAST	A2.2.2	-	3	1	Cross Section, post bHAST, 2X	Post stress cross section	Completed	3/3/0	1/1/0
HAST	A2.2.3	-	3	3	Wire Bond Shear, post bHAST, 2X	Post stress	-	3/9/0	1/3/0
HAST	A2.2.4	-	3	30	Bond Pull over Stitch, post bHAST, 2X	Post stress	Wires	3/9/0	1/3/0
HAST	A2.2.5	-	3	3	Bond Pull over Ball, post bHAST, 2X	Post stress	-	3/9/0	1/3/0
TC	A4.1	JEDEC JESD22-A104 and Appendix 3	3	77	Temperature Cycle	-65C/150C	500 Cycles	3/231/0	1/77/0
TC	A4.1.1	-	3	22	SAM Analysis, post TC 1X	Review for delamination	Completed	-	-
TC	A4.1.2	-	3	1	Cross Section, post TC, 1X	Post stress cross section	Completed	-	-
TC	A4.1.3	-	3	3	Wire Bond Shear, post TC, 1X	Post stress	-	-	-
TC	A4.1.4	-	3	30	Bond Pull over Stitch, post TC, 1X	Post stress	Wires	-	-
TC	A4.1.5	-	3	3	Bond Pull over Ball, post TC, 1X	Post stress	-	-	-
TC	A4.2	JEDEC JESD22-A104 and Appendix 3	3	70	Temperature Cycle	-65C/150C	1000 Cycles	3/210/0	1/70/0
TC	A4.2.1	-	3	22	SAM Analysis, post TC, 2X	Review for delamination	Completed	3/66/0	1/22/0
TC	A4.2.2	-	3	1	Cross Section, post TC, 2X	Post stress cross section	Completed	3/3/0	1/1/0

Type	#	Test Spec	Min Lot Qty	SS / Lot	Test Name	Condition	Duration	Qual Device: <u>ISO6763QDWRQ1</u>	Qual Device: <u>UCC21540QDWKRQ1</u>
TC	A4.2.3	-	3	3	Wire Bond Shear, post TC, 2X	Post stress	-	3/9/0	1/3/0
TC	A4.2.4	-	3	30	Bond Pull over Stitch, post TC, 2X	Post stress	Wires	3/9/0	1/3/0
TC	A4.2.5	-	3	3	Bond Pull over Ball, post TC, 2X	Post stress	-	3/9/0	1/3/0
HTSL	A6.1	JEDEC JESD22-A103	3	45	High Temperature Storage Life	150C	1000 Hours	3/135/0	1/45/0
HTSL	A6.1.1	-	3	1	Cross Section, post HTSL, 1X	Post stress cross section	Completed	-	-
HTSL	A6.2	JEDEC JESD22-A103	3	44	High Temperature Storage Life	150C	2000 Hours	3/132/0	1/44/0
HTSL	A6.2.1	-	3	1	Cross Section, post HTSL, 2X	Post stress cross section	Completed	3/3/0	1/1/0
<b>Test Group C - Package Assembly Integrity Tests</b>									
WBS	C1	AEC Q100-001	1	30	Wire Bond Shear	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0
WBP	C2	MIL-STD883 Method 2011	1	30	Wire Bond Pull	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	3/90/0	3/90/0

QBS: Qual By Similarity

Qual Device ISO6763QDWRQ1 is qualified at MSL2 260C

Qual Device UCC21540QDWKRQ1 is qualified at MSL3 260C

Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours

The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

**Ambient Operating Temperature by Automotive Grade Level:**

Grade 0 (or E): -40C to +150C

Grade 1 (or Q): -40C to +125C  
Grade 2 (or T): -40C to +105C  
Grade 3 (or I) : -40C to +85C

**E1 (TEST): Electrical test temperatures of Qual samples (High temperature according to Grade level):**

Room/Hot/Cold : HTOL, ED

Room/Hot : THB / HAST, TC / PTC, HTSL, ELFR, ESD & LU

Room : AC/uHAST

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

ZVEI ID reference: SEM-PW-02, SEM-PW-13, SEM-PA-08

For questions regarding this notice, e-mails can be sent to Change Management team or your local Field Sales Representative.

### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.