



**12500 TI Boulevard, MS 8640, Dallas, Texas 75243**

**PCN# 20240613005.1**

**Qualification of RFAB using qualified Process Technology, Die Revision, Datasheet update and additional Assembly Site/BOM options for select devices**  
**Change Notification / Sample Request**

**Date:** June 13, 2024  
**To:** Mouser PCN

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments (TI). The details of this change are on the following pages, and are in alignment with our standard product change notification (PCN) [process](#).

TI requires acknowledgement of receipt of this notification within 30 days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance and approval of this change. If samples or additional data are required, requests must be received within 30 days of this notification, given that samples are not built ahead of the change.

The Proposed First Ship date in this PCN letter is the earliest possible date that customers could receive the changed material. It is our commitment that the changed device will not ship before that date. If samples are requested within the 30 day sample request window, customers will still have 30-days to complete their evaluation regardless of the proposed 1st ship date.

This particular PCN is related to TI's multiyear transition plan for our two remaining factories with 150-millimeter production (DFAB in Dallas, Texas, and SFAB in Sherman, Texas). DFAB will remain open, but will focus on 200-mm production, with a smaller set of technologies. SFAB will close no earlier than 2024 and no later than 2025. As referenced in the "reason for change" below, these changes are part of our multiyear plan to transition these products to newer, more efficient manufacturing processes and technologies, underscoring our commitment to product longevity and supply continuity.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the Change Management team. For sample requests or sample related questions, contact your local Field Sales Representative. As always, we thank you for your continued business.

Change Management Team  
SC Business Services

**20240613005.1**  
**Attachment: 1**

**Products Affected:**

The devices listed on this page are a subset of the complete list of affected devices. According to our records, you have recently purchased these devices. The corresponding customer part number is also listed, if available.

<b>DEVICE</b>	<b>CUSTOMER PART NUMBER</b>
SN74LV4051ADR	NULL
SN74LV4051APWR	NULL
SN74LV4051ARGYR	NULL
SN74LV4052ADR	NULL
SN74LV4052APWR	NULL
SN74LV4052ARGYR	NULL
SN74LV4053ADR	NULL
SN74LV4053APWR	NULL
SN74LV4053ARGYR	NULL

Technical details of this Product Change follow on the next page(s).

<b>PCN Number:</b>	20240613005.1	<b>PCN Date:</b>	June 13, 2024
<b>Title:</b>	Qualification of RFAB using qualified Process Technology, Die Revision, Datasheet update and additional Assembly Site/BOM options for select devices		
<b>Customer Contact:</b>	Change Management Team	<b>Dept:</b>	Quality Services
<b>Proposed 1<sup>st</sup> Ship Date:</b>	September 11, 2024	<b>Sample requests accepted until:</b>	July 13, 2024*
<b>*Sample requests received after July 13, 2024 will not be supported.</b>			
<b>Change Type:</b>			
<input checked="" type="checkbox"/> Assembly Site	<input checked="" type="checkbox"/> Design	<input type="checkbox"/>	Wafer Bump Material
<input checked="" type="checkbox"/> Assembly Process	<input checked="" type="checkbox"/> Data Sheet	<input type="checkbox"/>	Wafer Bump Process
<input checked="" type="checkbox"/> Assembly Materials	<input type="checkbox"/> Part number change	<input checked="" type="checkbox"/>	Wafer Fab Site
<input type="checkbox"/> Mechanical Specification	<input type="checkbox"/> Test Site	<input checked="" type="checkbox"/>	Wafer Fab Material
<input checked="" type="checkbox"/> Packing/Shipping/Labeling	<input type="checkbox"/> Test Process	<input checked="" type="checkbox"/>	Wafer Fab Process

### PCN Details

#### Description of Change:

Texas Instruments is pleased to announce the qualification of its RFAB fabrication facility as an additional Wafer Fab option in addition to Assembly site/BOM options for the devices listed below.

Current Fab Site			Additional Fab Site		
Current Fab Site	Process	Wafer Diameter	Additional Fab Site	Process	Wafer Diameter
SFAB	EPIC1S2	150 mm	RFAB	LBC7	300 mm

The die was also changed as a result of the process change.

Construction differences are as follows:

#### Group 1 - BOM

	Current	Proposed
Wire diam/type	0.96mil Cu	0.8mil Cu

#### Group 2 - ASESH-MLA (PW)

	ASESH	MLA
Mount compound	EY1000063	4147858
Mold compound	EN2000508	4211471
Lead finish	Matte Sn	NiPdAu
ECAT	G3	G4

#### Group 3 - FMX/ASESH-MLA (D)

	FMX	ASESH	MLA
Wire type/diam	0.96mil Cu	0.8mil Cu	0.8mil Cu
Mount compound	4147858	EY1000063	4147858
Mold compound	4211880	EN2000506	4211880
Lead finish	NiPdAu	Matte Sn	NiPdAu
ECAT	G4	G3	G4

#### Group 4 - MLA-CDAT (RGY)

	MLA	CDAT
Wire type/diam	0.96mil Cu	0.8mil Cu
Mount compound	4205846	4207123
Mold compound	4208625	4222198

#### Group 5 - CRS-CDAT (RGY)

	CRS	CDAT

Wire type/diam	1.0mil Cu	0.8mil Cu	
Mount compound	435143	4207123	
Mold compound	435370	4222198	

The datasheets will be changing as a result of the above mentioned changes. The datasheet change details can be reviewed in the datasheet revision history. The links to the revised datasheets are available in the table below.



**SN74LV4051A**

SCLS428J – MAY 1999 – REVISED JUNE 2024

<b>Changes from Revision I (September 2015) to Revision J (June 2024)</b>	<b>Page</b>
• Updated the numbering format for tables, figures, and cross-references throughout the document.....	1
• Added new VIH and VIL Specifications at 1.65V Vcc.....	5
• Increased max ambient temperature max to 125C.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 1.65V Vcc.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 125C.....	5
• Added Timing Specifications at 125C.....	7



**SN74LV4052A**

SCLS429L – MAY 1999 – REVISED JUNE 2024

<b>Changes from Revision K (November 2016) to Revision L (June 2024)</b>	<b>Page</b>
• Updated the numbering format for tables, figures, and cross-references throughout the document.....	1
• Added new VIH and VIL Specifications at 1.65V Vcc.....	5
• Increased max ambient temperature max to 125C.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 1.65V Vcc.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 125C.....	5
• Added Timing Specifications at 125C.....	7



**SN54LV4053A, SN74LV4053A**

SCLS430L – MAY 1999 – REVISED JUNE 2024

<b>Changes from Revision K (April 2005) to Revision L (June 2024)</b>	<b>Page</b>
• Changed the numbering format for tables, figures, and cross-references throughout the document .....	1
• Added new VIH and VIL Specifications at 1.65V Vcc.....	5
• Increased max ambient temperature max to 125C.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 1.65V Vcc.....	5
• Added Ron, Ron Peak, and Delta Ron Specifications at 125C.....	5
• Added Timing Specifications at 125C.....	7

<b>Product Folder</b>	<b>Current Datasheet Number</b>	<b>New Datasheet Number</b>	<b>Link to full datasheet</b>
SN74LV4051A	SCLS428I	<b>SCLS428J</b>	<a href="http://www.ti.com/product/SN74LV4051A">http://www.ti.com/product/SN74LV4051A</a>
SN74LV4052A	SCLS429K	<b>SCLS429L</b>	<a href="http://www.ti.com/product/SN74LV4052A">http://www.ti.com/product/SN74LV4052A</a>
SNx4LV4053A	SCLS430K	<b>SCLS430L</b>	<a href="http://www.ti.com/product/SN54LV4053A">http://www.ti.com/product/SN54LV4053A</a>

Qual details are provided in the Qual Data Section.

#### **Reason for Change:**

These changes are part of our multiyear plan to transition products from our 150-millimeter factories to newer, more efficient manufacturing processes and technologies, underscoring our commitment to product longevity and supply continuity.

#### **Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):**

None

#### **Impact on Environmental Ratings:**

Checked boxes indicate the status of environmental ratings following implementation of this

change. If below boxes are checked, there are no changes to the associated environmental ratings.

RoHS	REACH	Green Status	IEC 62474
<input checked="" type="checkbox"/> No Change			

#### Changes to product identification resulting from this PCN:

##### Fab Site Information:

Chip Site	Chip Site Origin Code (20L)	Chip Site Country Code (21L)	Chip Site City
SH-BIP-1	SHE	USA	Sherman
<b>RFAB</b>	<b>RFB</b>	<b>USA</b>	<b>Richardson</b>

##### Die Rev:

###### Current

###### New

Die Rev [2P]	<b>Die Rev [2P]</b>
H	<b>B</b>

##### Assembly Site Information:

Assembly Site	Assembly Site Origin (22L)	Assembly Country Code (23L)	Assembly City
TI Mexico	MEX	MEX	Aguascalientes
Carsen	CRS	MYS	Jelapang, Ipoh
ASESH	ASH	CHN	Shanghai
<b>TI Malaysia</b>	<b>MLA</b>	<b>MYS</b>	<b>Kuala Lumpur</b>
<b>CDAT</b>	<b>CDA</b>	<b>CHN</b>	<b>Chengdu</b>

Sample product shipping label (not actual product label):



##### Product Affected:

###### Group 1: BOM change

SN74LV4051APWR	SN74LV4052APWR	SN74LV4053APWR
----------------	----------------	----------------

###### Group 2: ASESH-MLA

SN74LV4051APWR	SN74LV4052APWR	SN74LV4053APWR
----------------	----------------	----------------

###### Group 3: FMX/ASESH-MLA

SN74LV4051ADR	SN74LV4052ADR	SN74LV4053ADR
---------------	---------------	---------------

###### Group 4: MLA-CDAT

SN74LV4051ARGYR	SN74LV4052ARGYR	SN74LV4053ARGYR
-----------------	-----------------	-----------------

###### Group 5: CRS-CDAT

SN74LV4051ARGYR

For alternate parts with similar or improved performance, please visit the product page on [TI.com](http://TI.com)

### Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4051APWR	Qual Device: SN74LV4052APWR	Qual Device: SN74LV4053APWR	Qual Device: SN74LV4051APWR	Qual Device: SN74LV4052APWR	Qual Device: SN74LV4053APWR	QBS Reference: SN74LV4053ADR
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	-	-	-	-	-	-	1/76/0
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	-	-	-	-	-	-	1/76/0
ESD	E2	ESD CDM	-	250 Volts	-	-	1/3/0	-	-	-	1/3/0
ESD	E2	ESD HBM	-	1000 Volts	-	-	-	-	-	-	1/3/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	-	-	-	1/30/0	1/30/0	1/30/0	1/30/0

- QBS: Qual By Similarity
- Qual Device SN74LV4051APWR is qualified at MSL1 260C
- Qual Device SN74LV4052APWR is qualified at MSL1 260C
- Qual Device SN74LV4053APWR is qualified at MSL1 260C
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

TI Qualification ID: R-CHG-2208-027

### Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4052ADR	Qual Device: SN74LV4051ADR	Qual Device: SN74LV4051ADR	Qual Device: SN74LV4051ADR	QBS Reference: SN74HCS74QDRQ1	QBS Reference: TMUX1134PWR
HAST	A2	Biased HAST	130C/85%RH	96 Hours	-	-	-	-	3/231/0	3/231/0
UHAST	A3	Autoclave	121C/15psig	96 Hours	-	-	-	-	3/231/0	-
UHAST	A3	Unbiased HAST	130C/85%RH	96 Hours	-	-	-	-	3/231/0	3/231/0
TC	A4	Temperature Cycle	-65C/150C	500 Cycles	-	-	-	-	3/231/0	3/231/0
HTSL	A6	High Temperature Storage Life	150C	1000 Hours	-	-	-	-	3/135/0	3/231/0
HTOL	B1	Life Test	125C	1000 Hours	-	-	-	-	1/77/0	3/231/0
ELFR	B2	Early Life Failure Rate	125C	48 Hours	-	-	-	-	-	3/2400/0
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	1/76/0	1/76/0	-	-	-	-
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	1/76/0	1/76/0	-	-	-	-
SD	C3	PB Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes)	-	-	-	-	-	3/45/0	-

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4052ADR	Qual Device: SN74LV4051ADR	Qual Device: SN74LV4051ADR	Qual Device: SN74LV4051ADR	QBS Reference: SN74HCS74QDRQ1	QBS Reference: TMUX1134PWR
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes)	-	-	-	-	-	3/45/0	-
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB-Free Solder;	-	-	-	-	-	-	1/22/0
PD	C4	Physical Dimensions	Cpk>1.67	-	-	-	-	-	3/30/0	-
ESD	E2	ESD CDM	-	250 Volts	-	-	-	-	-	1/3/0
ESD	E2	ESD CDM	-	500 Volts	-	-	-	-	1/3/0	-
ESD	E2	ESD HBM	-	1000 Volts	-	-	-	-	-	1/3/0
ESD	E2	ESD HBM	-	2000 Volts	1/3/0	1/3/0	-	-	1/3/0	-
LU	E4	Latch-Up	Per JESD78	-	1/3/0	1/3/0	-	-	1/6/0	1/3/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	-	-	1/30/0	1/30/0	-	1/30/0
CHAR	E5	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	-	-	-	-	3/90/0	-

- QBS: Qual By Similarity
- Qual Device SN74LV4052ADR is qualified at MSL1 260C
- Qual Device SN74LV4051ADR is qualified at MSL1 260C
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

TI Qualification ID: R-CHG-2208-028

#### Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4051ARGYR	Qual Device: SN74LV4052ARGYR	Qual Device: SN74LV4053ARGYR	Qual Device: SN74LV4051ARGYR	Qual Device: SN74LV4052ARGYR	Qual Device: SN74LV4053ARGYR	QBS Reference: TS3A5017QRGYRQ1	QBS Reference: TMUX1134PWR
HAST	A2	Biased HAST	130C/65%RH	96 Hours	-	-	-	-	-	-	3/231/0	3/231/0
UHAST	A3	Autoclave	121C/15psig	96 Hours	-	-	-	-	-	-	3/231/0	-
UHAST	A3	Unbiased HAST	130C/65%RH	96 Hours	-	-	-	-	-	-	-	3/231/0
TC	A4	Temperature Cycle	-65C/150C	500 Cycles	-	-	-	-	-	-	3/231/0	3/231/0
HTSL	A6	High Temperature Storage Life	150C	1000 Hours	-	-	-	-	-	-	3/135/0	3/231/0
HTOL	B1	Life Test	125C	1000 Hours	-	-	-	-	-	-	3/231/0	3/231/0
ELFR	B2	Early Life Failure Rate	125C	48 Hours	-	-	-	-	-	-	-	3/2400/0
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	1/76/0	1/76/0	1/76/0	-	-	-	-	-
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	1/76/0	1/76/0	1/76/0	-	-	-	-	-
SD	C3	PB Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes)	-	-	-	-	-	-	-	1/15/0	-
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB-Free Solder;	-	-	-	-	-	-	-	1/15/0	-
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB-Free Solder;	-	-	-	-	-	-	-	-	1/22/0
PD	C4	Physical Dimensions	Cpk>1.67	-	-	-	-	-	-	-	3/30/0	-

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4051ARGYR	Qual Device: SN74LV4052ARGYR	Qual Device: SN74LV4053ARGYR	Qual Device: SN74LV4051ARGYR	Qual Device: SN74LV4052ARGYR	Qual Device: SN74LV4053ARGYR	QBS Reference: TS3A5017QRGYRQ1	QBS Reference: TMUX1134PWR
ESD	E2	ESD CDM	-	1500 Volts	-	-	-	-	-	-	1/3/0	-
ESD	E2	ESD CDM	-	250 Volts	-	-	-	-	-	-	-	1/3/0
ESD	E2	ESD CDM	-	750 Volts	1/3/0	-	-	-	-	-	-	-
ESD	E2	ESD HBM	-	1000 Volts	-	-	-	-	-	-	-	1/3/0
ESD	E2	ESD HBM	-	2000 Volts	-	-	-	-	-	-	1/3/3	-
LU	E4	Latch-Up	Per JESD78	-	-	-	-	-	-	-	1/6/0	1/3/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	-	-	-	1/3/0	1/3/0	1/3/0	-	1/3/0
CHAR	E5	Electrical Distributions	CpIo1.67 Room, hot and cold	-	-	-	-	-	-	-	3/9/0	-

- QBS: Qual By Similarity
- Qual Device SN74LV4051ARGYR is qualified at MSL1 260C
- Qual Device SN74LV4052ARGYR is qualified at MSL1 260C
- Qual Device SN74LV4053ARGYR is qualified at MSL1 260C
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

TI Qualification ID: R-CHG-2208-030

### Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4053ADR	Qual Device: SN74LV4053ADR	QBS Reference: SN74HCS74QDRQ1	QBS Reference: TMUX1134PWR
HAST	A2	Biased HAST	130C/85%RH	96 Hours	-	-	3/231/0	3/231/0
UHAST	A3	Autoclave	121C/15psig	96 Hours	-	-	3/231/0	-
UHAST	A3	Unbiased HAST	130C/85%RH	96 Hours	-	-	3/231/0	3/231/0
TC	A4	Temperature Cycle	-65C/150C	500 Cycles	-	-	3/231/0	3/231/0
HTSL	A6	High Temperature Storage Life	150C	1000 Hours	-	-	3/135/0	3/231/0
HTOL	B1	Life Test	125C	1000 Hours	-	-	1/77/0	3/231/0
ELFR	B2	Early Life Failure Rate	125C	48 Hours	-	-	-	3/2400/0
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	1/76/0	-	-	-
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	1/76/0	-	-	-
SD	C3	PB Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes)	-	-	-	3/45/0	-

Type	#	Test Name	Condition	Duration	Qual Device: SN74LV4053ADR	Qual Device: SN74LV4053ADR	QBS Reference: SN74HCS74QDRQ1	QBS Reference: TMUX1134PWR
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes)	-	-	-	3/45/0	-
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB-Free Solder;	-	-	-	-	1/22/0
PD	C4	Physical Dimensions	Cpk>1.67	-	-	-	3/30/0	-
ESD	E2	ESD CDM	-	250 Volts	1/3/0	-	-	1/3/0
ESD	E2	ESD CDM	-	500 Volts	-	-	1/3/0	-
ESD	E2	ESD HBM	-	1000 Volts	1/3/0	-	-	1/3/0
ESD	E2	ESD HBM	-	2000 Volts	-	-	1/3/0	-
LU	E4	Latch-Up	Per JESD78	-	-	1/3/0	1/6/0	1/3/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	1/30/0	-	-	1/30/0
CHAR	E5	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	-	-	3/90/0	-

- QBS: Qual By Similarity
- Qual Device SN74LV4053ADR is qualified at MSL1 260C
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

TI Qualification ID: R-CHG-2301-057

For questions regarding this notice, e-mails can be sent to the Change Management team or your local Field Sales Representative.

### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.