

PCN# 20240628009.2
Qualification of RFAB using qualified Process Technology, Die Revision, and
Assembly BOM options for select devices
Change Notification / Sample Request

Date: June 28, 2024
To: MOUSER PCN

Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments (TI). The details of this change are on the following pages, and are in alignment with our standard product change notification (PCN) [process](#).

TI requires acknowledgement of receipt of this notification within 30 days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance and approval of this change. If samples or additional data are required, requests must be received within 30 days of this notification, given that samples are not built ahead of the change.

The Proposed First Ship date in this PCN letter is the earliest possible date that customers could receive the changed material. It is our commitment that the changed device will not ship before that date. If samples are requested within the 30 day sample request window, customers will still have 30-days to complete their evaluation regardless of the proposed 1st ship date.

This particular PCN is related to TI's multiyear transition plan for our two remaining factories with 150-millimeter production (DFAB in Dallas, Texas, and SFAB in Sherman, Texas). DFAB will remain open, but will focus on 200-mm production, with a smaller set of technologies. SFAB will close no earlier than 2024 and no later than 2025. As referenced in the "reason for change" below, these changes are part of our multiyear plan to transition these products to newer, more efficient manufacturing processes and technologies, underscoring our commitment to product longevity and supply continuity.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the Change Management team. For sample requests or sample related questions, contact your local Field Sales Representative. As always, we thank you for your continued business.

Change Management Team
SC Business Services

20240628009.2
Attachment: 1

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, you have recently purchased these devices. The corresponding customer part number is also listed, if available.


DEVICE	CUSTOMER PART NUMBER
TL720M05GQKVURQ1	NULL
TL720M05QKVURQ1	NULL

Technical details of this Product Change follow on the next page(s).

PCN Number:	20240628009.2	PCN Date:	June 28, 2024																		
Title:	Qualification of RFAB using qualified Process Technology, Die Revision, and Assembly BOM options for select devices																				
Customer Contact:	Change Management team	Dept:	Quality Services																		
Proposed 1st Ship Date:	December 25, 2024	Sample requests accepted until:	July 28, 2024*																		
*Sample requests received after July 28, 2024 will not be supported.																					
Change Type:																					
<input type="checkbox"/>	Assembly Site	<input checked="" type="checkbox"/>	Design																		
<input checked="" type="checkbox"/>	Assembly Process	<input type="checkbox"/>	Data Sheet																		
<input checked="" type="checkbox"/>	Assembly Materials	<input type="checkbox"/>	Part number change																		
<input type="checkbox"/>	Mechanical Specification	<input type="checkbox"/>	Test Site																		
<input checked="" type="checkbox"/>	Packing/Shipping/Labeling	<input type="checkbox"/>	Test Process																		
<input type="checkbox"/>		<input type="checkbox"/>	Wafer Bump Material																		
<input type="checkbox"/>		<input type="checkbox"/>	Wafer Bump Process																		
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	Wafer Fab Site																		
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	Wafer Fab Materials																		
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	Wafer Fab Process																		
PCN Details																					
Description of Change:																					
Texas Instruments is pleased to announce the addition of RFAB using the LBC9 qualified process technology and additional Assembly BOM options for the devices listed below.																					
<table border="1"> <thead> <tr> <th colspan="3">Current Fab Site</th> <th colspan="3">Additional Fab Site</th> </tr> <tr> <th>Current Fab Site</th> <th>Process</th> <th>Wafer Diameter</th> <th>Additional Fab Site</th> <th>Process</th> <th>Wafer Diameter</th> </tr> </thead> <tbody> <tr> <td>SFAB</td> <td>J12</td> <td>150 mm</td> <td>RFAB</td> <td>LBC9</td> <td>300 mm</td> </tr> </tbody> </table>				Current Fab Site			Additional Fab Site			Current Fab Site	Process	Wafer Diameter	Additional Fab Site	Process	Wafer Diameter	SFAB	J12	150 mm	RFAB	LBC9	300 mm
Current Fab Site			Additional Fab Site																		
Current Fab Site	Process	Wafer Diameter	Additional Fab Site	Process	Wafer Diameter																
SFAB	J12	150 mm	RFAB	LBC9	300 mm																
The die was also changed as a result of the process change.																					
Construction differences are as follows:																					
	Current	Proposed																			
Wire type	2.0mil Cu	1.0mil Au																			
Mold compound	R-23	R-36																			
Qual details are provided in the Qual Data Section.																					
Reason for Change:																					
These changes are part of our multiyear plan to transition products from our 150-millimeter and 200-millimeter factories to newer, more efficient manufacturing processes and technologies, underscoring our commitment to product longevity and supply continuity.																					
Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):																					
None																					
Impact on Environmental Ratings:																					
Checked boxes indicate the status of environmental ratings following implementation of this change. If below boxes are checked, there are no changes to the associated environmental ratings.																					
RoHS	REACH	Green Status	IEC 62474																		
<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change	<input checked="" type="checkbox"/> No Change																		
Changes to product identification resulting from this PCN:																					
Fab Site Information:																					
Chip Site	Chip Site Origin Code (20L)	Chip Site Country Code (21L)	Chip Site City																		
SH-BIP-1	SHE	USA	Sherman																		
RFAB	RFB	USA	Richardson																		
Die Rev:																					
Current New																					

Die Rev [2P] D	Die Rev [2P] A
-------------------	-------------------


Sample product shipping label (not actual product label)




MADE IN: Malaysia
2DC: 2Q:

MSL 2 / 260C / 1 YEAR	SEAL DT
MSL 1 / 235C / UNLIM	03 / 29 / 04

OPT:
ITEM: 39
LBL: 5A (L)T0:1750





(1P) SN74LS07NSR
(Q) 2000 (D) 0336
(31T) LOT: 3959047MLA
(4W) TKY (1T) 7523483SI2
(P)
(2P) REV: (V) 0053317
(20L) CSO: SHE (21L) CCO:USA
(22L) ASO: MLA (23L) ACO: MYS

Product Affected:	
TL720M05GQKVURQ1	TL720M05QKVURQ1

For alternate parts with similar or improved performance, please visit the product page on [TI.com](https://www.ti.com)

TI Information
Selective Disclosure

Automotive Qualification Summary
(As per AEC-Q100 Rev. J and JEDEC Guidelines)

TL720M05-Q1
Approve Date 02-April -2024

Product Attributes

Attributes	Qual Device:	Qual Device:	QBS Package Reference:	QBS Process Reference:	QBS Product Reference:	QBS Product Reference:
	TL720M05GQKVURQ1M3	TL720M05QKVURQ1M3	TPS7B8250QKVURQ1	TLC8C5816QPWPRQ1	TPS7B8850QKVURQ1	TPS7B8650QKVURQ1
Automotive Grade Level	Grade 1	Grade 1	Grade 1	Grade 1	Grade 1	Grade 1
Operating Temp Range (C)	-40 to 125	-40 to 125	-40 to 125	-40 to 125	-40 to 125	-40 to 125
Product Function	Power Management	Power Management	Power Management	Power Management	Power Management	Power Management
Wafer Fab Supplier	RFAB	RFAB	RFAB	RFAB	RFAB	RFAB
Assembly Site	TFME	TFME	TFME	TAJ	TFME	TFME
Package Group	TO	TO	TO	TSSOP	TO	TO
Package Designator	KVU	KVU	KVU	PWP	KVU	KVU
Pin Count	3	3	5	28	3	5

- QBS: Qual By Similarity
- Qual Device TL720M05GQKVURQ1M3 is qualified at MSL3 260C
- Qual Device TL720M05QKVURQ1M3 is qualified at MSL3 260C

Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Type	#	Test Spec	Min Lot Qty	SS / Lot	Test Name	Condition	Duration	Qual Device:	Qual Device:	QBS Package Reference:	QBS Process Reference:	QBS Product Reference:	QBS Product Reference:
								TL720M05GQKVURQ1M3	TL720M05QKVURQ1M3	TPS7B8250QKVURQ1	TLC8C5816QPWPRQ1	TPS7B8850QKVURQ1	TPS7B8650QKVURQ1
Test Group A - Accelerated Environment Stress Tests													
PC	A1	JEDEC J-STD-020 JESD22-A113	3	77	Preconditioning	MSL3 260C	-	-	-	3/AI/0	3/AI/0	-	3/AI/0
HAST	A2	JEDEC JESD22-A110	3	77	Biased HAST	130C/85%RH	96 Hours	-	-	3/231/0	3/231/0	-	-

Type	#	Test Spec	Min Lot Qty	SS/Lot	Test Name	Condition	Duration	Qual Device:		QBS Package Reference:	QBS Process Reference:	QBS Product Reference:	QBS Product Reference:
								TL720M05GQKVURQ1M3	TL720M05QKVURQ1M3				
ACUHAST	A3	JEDEC JESD22-A102/JEDEC JESD22-A118	3	77	Autoclave	121C/15psig	96 Hours	-	-	-	3/231/0	-	-
ACUHAST	A3	JEDEC JESD22-A102/JEDEC JESD22-A118	3	77	Unbiased HAST	130C/85%RH	96 Hours	-	-	3/231/0	-	-	-
TC	A4	JEDEC JESD22-A104 and Appendix 3	3	77	Temperature Cycle	-65C/150C	500 Cycles	-	-	3/231/0	3/231/0	-	3/231/0
TC-BP	A4	MIL-STD883 Method 2011	1	5	Post Temp Cycle Bond Pull	-	-	-	-	1/5/0	1/5/0	-	1/5/0
TC-SAM	A4	-	3	3	Post TC SAM	<50% delamination	-	-	-	-	-	-	3/36/0
PTC	A5	JEDEC JESD22-A105	1	45	PTC	-40/125C	1000 Cycles	-	-	1/45/0	-	-	1/45/0
HTSL	A6	JEDEC JESD22-A103	1	45	High Temperature Storage Life	150C	1000 Hours	-	-	2/154/0	3/135/0	-	1/77/0
HTSL	A6	JEDEC JESD22-A103	1	45	High Temperature Storage Life	175C	500 Hours	-	-	1/77/0	-	-	-
Test Group B - Accelerated Lifetime Simulation Tests													
HTOL	B1	JEDEC JESD22-A108	3	77	Life Test	125C	1000 Hours	-	-	3/231/0	3/231/0	1/77/0	1/77/0
ELFR	B2	AEC Q100-008	3	800	Early Life Failure Rate	125C	48 Hours	-	-	-	3/2400/0	-	-
Test Group C - Package Assembly Integrity Tests													
WBS	C1	AEC Q100-001	1	30	Wire Bond Shear	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	-	-	3/90/0	3/90/0	-	-
WBP	C2	MIL-STD883 Method 2011	1	30	Wire Bond Pull	Minimum of 5 devices, 30 wires Cpk>1.67	Wires	-	-	3/90/0	3/90/0	-	-
SD	C3	JEDEC J-STD-002	1	15	PB Solderability	>95% Lead Coverage	-	-	-	-	1/15/0	-	-
SD	C3	JEDEC J-STD-002	1	15	PB-Free Solderability	>95% Lead Coverage	-	-	-	1/15/0	1/15/0	-	-
PD	C4	JEDEC JESD22-B100 and B108	3	10	Physical Dimensions	Cpk>1.67	-	-	-	3/30/0	3/30/0	-	-
Test Group D - Die Fabrication Reliability Tests													
Type	#	Test Spec	Min Lot Qty	SS/Lot	Test Name	Condition	Duration	Qual Device:		QBS Package Reference:	QBS Process Reference:	QBS Product Reference:	QBS Product Reference:
								TL720M05GQKVURQ1M3	TL720M05QKVURQ1M3				
EM	D1	JESD61	-	-	Electromigration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
TDD	D2	JESD35	-	-	Time Dependent Dielectric Breakdown	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
HCI	D3	JESD60 & 28	-	-	Hot Carrier Injection	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
BTI	D4	-	-	-	Bias Temperature Instability	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
SM	D5	-	-	-	Stress Migration	-	-	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements	Completed Per Process Technology Requirements
Test Group E - Electrical Verification Tests													
ESD	E2	AEC Q100-002	1	3	ESD HBM	-	2000 Volts	-	-	1/3/0	-	1/3/0	1/3/0
ESD	E3	AEC Q100-011	1	3	ESD CDM	-	500 Volts	-	-	1/3/0	-	1/3/0	1/3/0
LU	E4	AEC Q100-004	1	6	Latch-Up	Per AEC Q100-004	-	-	-	1/6/0	1/6/0	1/6/0	1/3/0
ED	E5	AEC Q100-009	3	30	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	-	-	3/90/0	3/90/0	1/300	3/90/0

- Additional Tests**
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
 - The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
 - The following are equivalent HTSL options based on an activation energy of 0.7eV : 150C/1k Hours, and 170C/420 Hours
 - The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles

Ambient Operating Temperature by Automotive Grade Level:

- Grade 0 (or E) : -40C to +150C
- Grade 1 (or Q) : -40C to +125C
- Grade 2 (or T) : -40C to +105C
- Grade 3 (or I) : -40C to +85C

E1 (TEST): Electrical test temperatures of Qual samples (High temperature according to Grade level):

- Room/Hot/Cold : HTOL, ED
- Room/Hot : THB / HAST, TC / PTC, HTSL, ELFR, ESD & LU

- Room : ACU/HAST

Quality and Environmental data is available at TI's external Web site: <http://www.ti.com/>

TI Qualification ID: R-NPD-2402-165

ZVEI ID's: SEM-DE-01, SEM-DE-03, SEM-PW-02, SEM-PW-09, SEM-PW-13, SEM-PA-08, SEM-PA-11

For questions regarding this notice, e-mails can be sent to the Change Management team or your local Field Sales Representative.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.