

Title of Change:	Datasheet Update for NTMFSC1D6N06CTWG
Effective date:	16 Dec 2025
Contact information:	Contact your local onsemi Sales Office
Type of notification:	This Product Bulletin is for notification purposes only. onsemi will proceed with implementation of this change upon publication of this Product Bulletin.
Change Category:	Datasheet
Change Sub-Category(s):	Datasheet/Product Doc change

Sites Affected:

onsemi Sites	External Foundry/Subcon Sites
None	None

Description and Purpose:

This Product Bulletin announces that onsemi is updating the datasheet for NTMFS0D6N04XMT1G.

The changes are listed below:

	From	To																																																																																																								
<ol style="list-style-type: none"> Pin 9 is not relevant for this device, so it must be corrected This symbol diagram is confusing, so it will be removed Exposed top metal source pad needs to be indicated 	<p>1. Pin 9 is not relevant for this device, so it must be corrected</p> <p>2. This symbol diagram is confusing, so it will be removed</p> <p>3. Exposed top metal source pad needs to be indicated</p>	<p>N-Channel MOSFET</p> <p>DFN8 5x6.15, 1.27P, DUAL COOL CASE 506EG</p>																																																																																																								
<ol style="list-style-type: none"> IDA and PDA removal Add Pulsed Source Current (Body Diode parameter) 	<p>MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)</p> <table border="1"> <thead> <tr> <th>Parameter</th> <th>Symbol</th> <th>Value</th> <th>Unit</th> </tr> </thead> <tbody> <tr> <td>Drain-to-Source Voltage</td> <td>V_{DSS}</td> <td>60</td> <td>V</td> </tr> <tr> <td>Gate-to-Source Voltage</td> <td>V_{GS}</td> <td>± 20</td> <td>V</td> </tr> <tr> <td rowspan="2">Continuous Drain Current</td> <td rowspan="2">I_D</td> <td>$T_C = 25^\circ\text{C}$</td> <td>238 A</td> </tr> <tr> <td>$T_C = 100^\circ\text{C}$</td> <td>168</td> </tr> <tr> <td>Power Dissipation</td> <td>P_D</td> <td>166</td> <td>W</td> </tr> <tr> <td>Continuous Drain Current $R_{\theta JA}$</td> <td>$T_A = 25^\circ\text{C}$</td> <td>I_{DA}</td> <td>36 A</td> </tr> <tr> <td>Power Dissipation $R_{\theta JA}$</td> <td>$T_A = 25^\circ\text{C}$</td> <td>P_{DA}</td> <td>3.9 W</td> </tr> <tr> <td>Continuous Drain Current $R_{\theta JA}$</td> <td>$T_A = 100^\circ\text{C}$</td> <td>I_{DA}</td> <td>26 A</td> </tr> <tr> <td>Power Dissipation $R_{\theta JA}$</td> <td>$T_A = 100^\circ\text{C}$</td> <td>P_{DA}</td> <td>1.9 W</td> </tr> <tr> <td>Pulsed Drain Current</td> <td>$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$</td> <td>I_{DM}</td> <td>676 A</td> </tr> <tr> <td>Operating Junction and Storage Temperature Range</td> <td>T_J, T_{stg}</td> <td>-55 to +175</td> <td>$^\circ\text{C}$</td> </tr> <tr> <td>Continuous Source-Drain Current (Body Diode)</td> <td>I_S</td> <td>209</td> <td>A</td> </tr> <tr> <td>Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)</td> <td>E_{AS}</td> <td>192</td> <td>mJ</td> </tr> <tr> <td>Lead Temperature for Soldering Purposes (1/8" from case for 10 s)</td> <td>T_L</td> <td>260</td> <td>$^\circ\text{C}$</td> </tr> </tbody> </table>	Parameter	Symbol	Value	Unit	Drain-to-Source Voltage	V_{DSS}	60	V	Gate-to-Source Voltage	V_{GS}	± 20	V	Continuous Drain Current	I_D	$T_C = 25^\circ\text{C}$	238 A	$T_C = 100^\circ\text{C}$	168	Power Dissipation	P_D	166	W	Continuous Drain Current $R_{\theta JA}$	$T_A = 25^\circ\text{C}$	I_{DA}	36 A	Power Dissipation $R_{\theta JA}$	$T_A = 25^\circ\text{C}$	P_{DA}	3.9 W	Continuous Drain Current $R_{\theta JA}$	$T_A = 100^\circ\text{C}$	I_{DA}	26 A	Power Dissipation $R_{\theta JA}$	$T_A = 100^\circ\text{C}$	P_{DA}	1.9 W	Pulsed Drain Current	$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$	I_{DM}	676 A	Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$	Continuous Source-Drain Current (Body Diode)	I_S	209	A	Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)	E_{AS}	192	mJ	Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	T_L	260	$^\circ\text{C}$	<p>MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)</p> <table border="1"> <thead> <tr> <th>Parameter</th> <th>Symbol</th> <th>Value</th> <th>Unit</th> </tr> </thead> <tbody> <tr> <td>Drain-to-Source Voltage</td> <td>V_{DSS}</td> <td>60</td> <td>V</td> </tr> <tr> <td>Gate-to-Source Voltage</td> <td>V_{GS}</td> <td>± 20</td> <td>V</td> </tr> <tr> <td rowspan="2">Continuous Drain Current</td> <td rowspan="2">I_D</td> <td>$T_C = 25^\circ\text{C}$</td> <td>238 A</td> </tr> <tr> <td>$T_C = 100^\circ\text{C}$</td> <td>168</td> </tr> <tr> <td>Power Dissipation</td> <td>$T_C = 25^\circ\text{C}$</td> <td>P_D</td> <td>166 W</td> </tr> <tr> <td>Pulsed Drain Current</td> <td>$T_C = 25^\circ\text{C}$</td> <td>I_{DM}</td> <td>676 A</td> </tr> <tr> <td>Pulsed Source Current (Body Diode)</td> <td>$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$</td> <td>I_{SM}</td> <td>676 A</td> </tr> <tr> <td>Operating Junction and Storage Temperature Range</td> <td>T_J, T_{stg}</td> <td>-55 to +175</td> <td>$^\circ\text{C}$</td> </tr> <tr> <td>Continuous Source-Drain Current (Body Diode)</td> <td>I_S</td> <td>209</td> <td>A</td> </tr> <tr> <td>Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)</td> <td>E_{AS}</td> <td>192</td> <td>mJ</td> </tr> <tr> <td>Lead Temperature for Soldering Purposes (1/8" from case for 10 s)</td> <td>T_L</td> <td>260</td> <td>$^\circ\text{C}$</td> </tr> </tbody> </table>	Parameter	Symbol	Value	Unit	Drain-to-Source Voltage	V_{DSS}	60	V	Gate-to-Source Voltage	V_{GS}	± 20	V	Continuous Drain Current	I_D	$T_C = 25^\circ\text{C}$	238 A	$T_C = 100^\circ\text{C}$	168	Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	166 W	Pulsed Drain Current	$T_C = 25^\circ\text{C}$	I_{DM}	676 A	Pulsed Source Current (Body Diode)	$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$	I_{SM}	676 A	Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$	Continuous Source-Drain Current (Body Diode)	I_S	209	A	Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)	E_{AS}	192	mJ	Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	T_L	260	$^\circ\text{C}$
Parameter	Symbol	Value	Unit																																																																																																							
Drain-to-Source Voltage	V_{DSS}	60	V																																																																																																							
Gate-to-Source Voltage	V_{GS}	± 20	V																																																																																																							
Continuous Drain Current	I_D	$T_C = 25^\circ\text{C}$	238 A																																																																																																							
		$T_C = 100^\circ\text{C}$	168																																																																																																							
Power Dissipation	P_D	166	W																																																																																																							
Continuous Drain Current $R_{\theta JA}$	$T_A = 25^\circ\text{C}$	I_{DA}	36 A																																																																																																							
Power Dissipation $R_{\theta JA}$	$T_A = 25^\circ\text{C}$	P_{DA}	3.9 W																																																																																																							
Continuous Drain Current $R_{\theta JA}$	$T_A = 100^\circ\text{C}$	I_{DA}	26 A																																																																																																							
Power Dissipation $R_{\theta JA}$	$T_A = 100^\circ\text{C}$	P_{DA}	1.9 W																																																																																																							
Pulsed Drain Current	$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$	I_{DM}	676 A																																																																																																							
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$																																																																																																							
Continuous Source-Drain Current (Body Diode)	I_S	209	A																																																																																																							
Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)	E_{AS}	192	mJ																																																																																																							
Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	T_L	260	$^\circ\text{C}$																																																																																																							
Parameter	Symbol	Value	Unit																																																																																																							
Drain-to-Source Voltage	V_{DSS}	60	V																																																																																																							
Gate-to-Source Voltage	V_{GS}	± 20	V																																																																																																							
Continuous Drain Current	I_D	$T_C = 25^\circ\text{C}$	238 A																																																																																																							
		$T_C = 100^\circ\text{C}$	168																																																																																																							
Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	166 W																																																																																																							
Pulsed Drain Current	$T_C = 25^\circ\text{C}$	I_{DM}	676 A																																																																																																							
Pulsed Source Current (Body Diode)	$T_C = 25^\circ\text{C}$, $t_p = 100 \mu\text{s}$	I_{SM}	676 A																																																																																																							
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$																																																																																																							
Continuous Source-Drain Current (Body Diode)	I_S	209	A																																																																																																							
Single Pulse Avalanche Energy ($I_{PK} = 62 \text{ A}$)	E_{AS}	192	mJ																																																																																																							
Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	T_L	260	$^\circ\text{C}$																																																																																																							



There is no technical change to the product, only a datasheet correction. The changes being made are solely to remove unnecessary symbols and align with the current datasheet formatting to avoid confusion for customers.

List of Affected Standard Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

NTMFSC1D6N06CTWG		
------------------	--	--