

# RoEnDi Safety Information

**IMPORTANT: PLEASE RETAIN THIS INFORMATION FOR FUTURE REFERENCE**

## **WARNINGS**

- This product shall only be connected to an external power supply rated at 5V dc, and a maximum current of 200-400mA. Any external power supply used with RoEnDi shall comply with relevant regulations and standards applicable in the country of intended use.
- This product should be operated in a well ventilated environment and should not be covered.
- This product should be placed on a stable, flat, non-conductive surface in use and should not be contacted by conductive items.
- The connection of unapproved devices to the GPIO connector may affect compliance or result in damage to the unit and invalidate the warranty.

## **INSTRUCTIONS FOR SAFE USE**

To avoid malfunction or damage to your RoEnDi please observe the following:

- Do not expose it to water, moisture or place it on a conductive surface whilst in operation.
- Do not expose it to heat from any source
- Take care whilst handling to avoid mechanical or electrical damage to the printed circuit board and connectors.
- Only handle by the edges to minimize the risk of electrostatic discharge damage.
- All peripherals used with the RoEnDi should comply with relevant standards for the country of use and be marked accordingly to ensure that safety and performance requirements are met.
- RoEnDi is not designed to be powered from both the USB port and external power supply. If this is attempted it may malfunction.