



This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

MARKETING SALES DRAWING **DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING** **DIMENSIONS IN METRIC - []**



**Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.**



NOTES:

1. TUSONIX STANDARD PART NUMBER: 7606-551.
TUSONIX RoHS COMPLIANT PART NUMBER: 7606-551 LF.
CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
2. LEAD FINISH: MATTE TIN.
3. PLATE MATERIAL: COPPER ALLOY, MATTE TIN FINISH.
4. PART MARKING: PART NUMBER, DATE CODE AND UL RECOGNITION: WHITE INK.
RoHS PART: GREEN INK DOT ON TOP OF GROUND PLATE AS SHOWN.
5. MAX. SOLDERING TEMPERATURE 500°F (260°C).
6. GROUNDING STANDOFF MOUNTING TORQUE 3.0 - 3.8 in. lbs. [0.34 - 0.43 Nm].
7. MOLDED MATERIAL: HIGH TEMPERATURE THERMOPLASTIC (PBT), UL RATED 94 V-O.
8. UL RECOGNITION PENDING.

Cx (pF)	WVDC -55°C TO +105°C	I _{DC}	I.R. MIN. @ 100 (VDC)	DWV (VDC 1 MIN.)	TYPICAL NO LOAD INSERTION LOSS (dB) @ 25°C PER MIL-STD-220			
					10 MHz	100 MHz	1 GHz	10 GHz
2500/5000	100	20 Amps	10 G Ω	2121	5	50	60	65

REVISION RECORD	Original Release C.O.	WAS SK 8192-000. S.M. 06-01-05	20050524-2-14	ADDED AND REVISED NOTES. ADDED GREEN DOT. S.M. 02-21-06	20060202-10-14	TOLERANCES unless otherwise specified	Title		REAR-PANEL MOUNT FILTERED TERMINAL BLOCK, 6 POSITION UL RECOGNIZED			
							2 PLC. DECIMAL ± N/A					
							3 PLC. DECIMAL ± .030 [0.76]					
							ANGLES ± N/A		Drawn	S.M. 06-01-05	Scale	FULL
							TUSONIX TUCSON, ARIZONA		Approved		R.C. 06-01-05	
									A	7606-551		