



2. Material and Finish:


- Receptacle Housing (with Flange): Zinc Die-Cast,

Finish: Nickel Plated

- Panel Gasket: NBR, Color: Black
- M3 Mounting Hardware: Stainless Steel Includes 4 x (Screw + Nut + Flat Washer + Spring Lock Washer)
- USB Adaptor Insulator: PBT, UL94 V-0, Black
- USB Adaptor Metal Shell: Copper Alloy, Nickel Plated
- USB Adaptor Overmold material: PBT UL94 V-0, Color: Black
- USB Contacts: Copper Alloy, Finish: 30 u" Gold min. over Nickel
- 3. Connector can be front or rear mounted to a maximum panel thickness of 3.2 mm.
- 4. IP67 rated when fully mated with appropriate mating connector
- 5. Hardware shipped unassembled
- (b) 6. Recommended mounting torque is 8 to 10 lb-inch







Pin-Assianment

Type A	Type A
Female	Female
Pin1	Pin1
Pin2	Pin2
Pin3	Pin3
Pin4	Pin4
Shell	Shell

Directive 2002/95/EC RoHS Compliant

DRAWINS MAY NOT BE COPIED OR REPRODU YMY, AND MAYNOT BE ASSED ON TO A TH WITHOUT WRITTEN PERMISSION. ISSHIP AND COPPRIENT OF CONEC CORPOR NOT ALTER CAD INDAMINIS BY H	HAND	Customer:				Tolerance Unless otherwise specified 0 PLC ± 0.30		 	Scale: Dim. in mm		
	ING BY	Na	ame	Title	Approval Date	1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1'		Autodesk Inventor	Material: See Notes	terial: See Notes	
	8 8					2012	Date	Name	IP67 USB Type	A E/E Adapte	\r_
	<u> </u>					Draw.	Sept. 27	Vincent Ke		•	
	8 S					Appd.	Sept. 27	J. Chaudry	Receptacle (with Fl	,	Kit
						Norm			Nickel Plated Zinc		
	립	С	1 x c	May/22/201	Vincent ke	D-old			Drowing No : 47K4A26	- 1	DIN
	計 計	Ь	1 x b	Mar/05/201	3 Vincent Ke				Drawing No.: 17K1A354		A3
	OT N	а	original						Part No.: 17-210111		Sheet
± 3 ₹ ≥ C							771 1		alt NO / - Z U		1/1