







Detail contact area




view with dust cover





M 1:1



Lochbild für Leiterplatte (Bestückungsseite)
Board hole pattern (component mounting side)



daughter card layout



Layout proposal is in accordance with the PCI Express specification

NOTES:

Material: LCP GF 30 schwarz
Material: LCP GF 30 black

Galvanik: min. 1,27 µm Unternickelung
über gesamten PIN - Bereich
Gold - Flash im Lötbereich
Plating: min. 1,27 µm Ni entire contact
Gold - Flash plating on contact tails


1.) Fertiglochdurchmesser
finished viadiameter (PTH)

Package: Tray (20 pcs.)

Connector printing / labeling:
according to drawing 294775

85 Ohm	009801	14,7	11,18	3,18	min. 0,8 µm Au
	009701	14,7	11,18	3,18	min. 0,127 µm Au
	009601	14,7	11,18	2,54	min. 0,8 µm Au
	009501	14,7	11,18	2,54	min. 0,127 µm Au
	009401	9,4	5,84	3,18	min. 0,8 µm Au
	009301	9,4	5,84	3,18	min. 0,127 µm Au
	009201	9,4	5,84	2,54	min. 0,8 µm Au
100 Ohm	009101	9,4	5,84	2,54	min. 0,127 µm Au
	009062	20,3	16,69	3,18	min. 0,8 µm Au
	009061	14,7	11,18	3,18	min. 0,8 µm Au
	009060	9,4	5,84	3,18	min. 0,8 µm Au
	009042	20,3	16,69	2,54	min. 0,8 µm Au
	009041	14,7	11,18	2,54	min. 0,8 µm Au
	009040	9,4	5,84	2,54	min. 0,8 µm Au
	009022	20,3	16,69	3,18	min. 0,127 µm Au
	009021	14,7	11,18	3,18	min. 0,127 µm Au
	009020	9,4	5,84	3,18	min. 0,127 µm Au
	009002	20,3	16,69	2,54	min. 0,127 µm Au
	009001	14,7	11,18	2,54	min. 0,127 µm Au
	009000	9,4	5,84	2,54	min. 0,127 µm Au

Ident.-Nr. Part - No.	Maß "A" Dim "A"	Maß "B" Dim "B"	Maß "C" Dim "C"	Oberfläche Steckbereich plating contact area
--------------------------	--------------------	--------------------	--------------------	---

Information / Tolerances: Sofern nichts anderes angegeben / unless otherwise noted			Tolerances		 All Dimensions in mm	Scale		2:1	
±0.254 [0.010"]		±0.127 [0.005"]	±0.05 [0.002"]						
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.			Subject to modification without prior notice. Drawing will not be updated.			Designation			
						Abgew. PCI Express STV 36pol. <i>RT. Angle PCI Express 36 pins</i>			
			 www.ERNI.com			284623			I
									A2
h		16.02.2016				Class	PCIEXP		
Index		Date							

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16061 to be observed.