



A
B
C
D
E
F




CRIMP CONTACT INSERTION DRAWING




PART NO.	CODE NO.	NUMBER OF CONTACT	A	B
DF4- 2P-2C	544-0003-4	2	4.5	2.0
DF4- 3P-2C	544-0004-7	3	6.5	4.0
DF4- 4P-2C	544-0005-0	4	8.5	6.0
DF4- 5P-2C	544-0006-2	5	10.5	8.0
DF4- 6P-2C	544-0007-5	6	12.5	10.0
DF4- 7P-2C	544-0008-8	7	14.5	12.0
DF4- 8P-2C	544-0009-0	8	16.5	14.0
DF4- 9P-2C	544-0010-0	9	18.5	16.0
DF4-10P-2C	544-0011-2	10	20.5	18.0
DF4-11P-2C	544-0012-5	11	22.5	20.0
DF4-12P-2C	544-0013-8	12	24.5	22.0
DF4-13P-2C	544-0014-0	13	26.5	24.0
DF4-14P-2C	544-0015-3	14	28.5	26.0
DF4-15P-2C	544-0016-6	15	30.5	28.0

RECOMMENDED PATTERN(BOARD THICKNESS $t=1.6\text{mm}$)



1 SQUARE MARKS ARE INDICATED IN RELIEF
ON THE PART OF FOLLOWING CONTACT NO. :
NO. 5, 10, 15

				1		POLYAMIDE		BLACK, UL94V-0							
NO.		MATERIAL		FINISH , REMARKS		NO.		MATERIAL		FINISH , REMARKS					
UNITS mm				SCALE 5 : 1		 COUNT 5		DESCRIPTION OF REVISIONS		DESIGNED YK. NAKATSU		CHECKED TS. KUMAZAWA		DATE 08. 03. 28	
 HIROSE ELECTRIC CO., LTD.				APPROVED :KJ. KATAYOSE		05. 01. 05		DRAWING NO.		EDC3-160365-00					
				CHECED :TY. OMA		05. 01. 05		PART NO.		DF4-*P-2C					
				DESIGNED :IO. DENPOUYA		05. 01. 05		CODE NO.		CL544-					
				DRAWN :IO. DENPOUYA		05. 01. 05				 					

A
B
C
D
E
F