

ITEM	PART NO	QTY	DESCRIPTION
9	13812568	1	SEAL RETAINER
8	13812566	1	CABLE SEAL
7	13812560	1	INNER FERRULE
6	15514994	1	OUTER FERRULE
5	1381592	1	RIGHT ANGLE TERMINAL

CABLE ASSEMBLY
35MM² HV SHIELDED CABLE PER M6040

- NOTE:
- THE ASSEMBLY SHOWN ON THIS DRAWING REQUIRES THE USE OF 35MM² HIGH VOLTAGE SHIELDED CABLE PER M6040. FERRULES MUST BE CRIMPED AND ORIENTED WITH RESPECT TO THE TERMINAL AS SHOWN & MEET FULL REQUIREMENTS OF USCAR 37.
 - CABLE MUST BE INSERTED THROUGH THE SEAL RETAINER (9) AND CABLE SEAL (8) BEFORE APPLICATION OF INNER (7) AND OUTER (6) FERRULES AND BEFORE APPLICATION OF TERMINAL ASSEMBLY (5).
 - CABLE MUST BE PARTIALLY STRIPPED AND NO CORE STRANDS OR BRAID STRANDS ARE TO BE EXPOSED WHEN APPLYING THE SEAL RETAINER (9) AND CABLE SEAL (8).
 - ALL LEADS MUST BE HI-POT TESTED TO 3000 VOLTS (AC RMS) FOR 10 SECONDS.
 - CABLE ASSEMBLY MUST BE VALIDATED TO CUSTOMER REQUIREMENTS FOR THE APPLICATION.

15503140

ITEM	PART NO	QTY	DESCRIPTION
4	13824777	1	TERM SHUNT
3	13955587	1	LOCK MECH ASST LEVER
2	13956875	1	LOCK IN/CONNECT
1	15522427	1	COV CONN PWR PACK

LEVER LOCK PRESTAGE POSITION

LEVER LOCK MATED POSITION

LEVER LOCK SHIPPING POSITION

ITEM	PART NO	QTY	DESCRIPTION
4	13824777	1	TERM SHUNT
3	13955587	1	LOCK MECH ASST LEVER
2	13956875	1	LOCK IN/CONNECT
1	15522427	1	COV CONN PWR PACK

APTIV

CONNECTION SYSTEMS

ARMANDO HERNANDEZ

15503140

15503140

04130221