•			
,			
:			
•			
,			
:			
•			
•			
:			
•			
,			
•			
١			
•			
•			
,			
;			
•			
:			
ï			
ï			
•			
:			
٦			
•			
•			
٠			
٠			
í			
í			
•			
:			
)			
)			
1			
1			
•			
į			
•			
•			
)			
)			
١			
i			
ï			
١			
1			
,			
•			
;			
inches of the control			
income of the second			
the same of the sa			
incident of the control of the contr			
in the contract of the contrac			
in the contract of the contrac			
in the contract of the contrac			
consists of the contract of th			
contract of the contract of the			
common of famous contractions and			
inning the common of the commo			
common common (formation common commo			
common of the co			
common common (formation or control of			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			
6			

, .h k	Applicable standard Operating		40.00 to 105.00 Store					05 00 (
Rating	temperature	e range	-40 °C to +85 °C		temperature	range	range -25 °C to +70 °C			ng)
	-	-	- Cno	oificati						
			•	cification	7118		Danie		ОТ	
Item Test method Structure					Requirements				QT	AT
		Vigual cho	ock Maasuramant instr	rumonte					Х	Х
General examination Marking		Visual Crie	Visual check , Measurement instruments			According to drawing				^
		Visual che	Visual check							Х
						1			1	
COUN	NT C	DESCRIPTION	OF REVISIONS	D	ESIGNED			CHECKED	DA [*]	TE
<u>Æ</u> REMARK						4 DDD 0	\/ED			
KEWAKK						APPRO		MT. SHIBUTANI	17. 1	
						CHEC		YY. HIYAMA	17. 1	
						DESIG		SI. MATSUMOTO	17. 1	
Note OT ()uolification T	oot AT.Asse	rongo Toot ViAnninghin	Toot	DDAM	1	VIN	SI. MATSUMOTO	17. 1	
Note QT:Qualification Test AT:Assurance Test , X:Applicable Test				ı est	DRAWIN	RAWING NO. ELC-375171-00-01				
HS	5	SPECIFIC	ECIFICATION SHEET PAR		ART NO.		UJ-J1			
\boldsymbol{C} $\boldsymbol{\Gamma}$		POSE ELECTRIC CO. LTD.				01.710.0000.0.00			Α	

CL719-0003-0-00

CODE NO.

1/1

HIROSE ELECTRIC CO., LTD.

