

09 66 123 6801	M3	2					Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	D-Sub male standard 9 poles with solder pins and nuts	Maßstab/ Scale 1,5:1
09 66 123 7801	M3	3				Detail.	23-NOV-01	JB			
09 66 123 5801	M3	0,76 µm Au				Insp.					
09 66 123 6802	4-40 UNC	2				Stand.					
09 66 123 7802	4-40 UNC	3				HARTING EURL F-95972 Paris				TB 09 66 123 X80X	Blatt/ Page 1 /
09 66 123 5802	4-40 UNC	0,76 µm Au	29733	23-NOV-01	JB						
Part number	nut thread	Performance level	Mod.	Dat.	Name				Sub.		

09 66 123 6802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 123 5802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 123 6801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 123 5801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

09 66 123 7801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 123 7802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	9 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF