

09 66 462 6816
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 462 5816
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 462 5815
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats
2D files

Typenblatt

Typenblatt

09 66 462 7815
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 462 7816
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 462 6815
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins - low profile
shell	tinned metal shell with dimples
Number of contacts	37 way
Board fixing	with snap-in-clips
Grounding	with grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF