

09 66 423 6801	M3	2			
09 66 423 7801	M3	3			
09 66 423 5801	M3	0,76 µm Au			
09 66 423 6802	4-40 UNC	2			
09 66 423 7802	4-40 UNC	3			
09 66 423 5802	4-40 UNC	0,76 µm Au	29733	23-NOV-01	JB
Part number	nut thread	Performance level	Mod.	Dat.	Name

HARTING EURL
F-95972 Paris



D-Sub male standard 37 poles
with solder pins and nuts

TB 09 66 423 X80X

Maßstab/
Scale

1, 5:1

Blatt/ Page

09 66 423 7801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 423 7802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 423 5801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

09 66 423 6802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 423 6801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 423 5802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	37 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF