

1335CCN-272J=P3


In Production

RoHS

REACH

AEC-Q200

Appearance & Shape



(in mm)

Features

Features

- High reliability conforms to automotive applications.
- Encapsulated core and winding for anti-shock proof.
- High Q and high sensitivity due to optimized magnetic material and electrode structure.
- Wide inductance range for design flexibility.
- Triaxial LF antenna coil.
- Applicable to reflow soldering.
- AEC-Q200 compliant

Applications

- Suitable as a Transponder Antenna Coil for Remote Keyless Entry System. (Vehicle application)
- Wide operating temperature range :- 40 ~ +85°C

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	330mm Embossed Tape	500

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1335CCN-272J=P3



Specifications


Series	SA3D12
Size(LxWxT)	11.9×11.9×3.2mm
Test Frequency	125kHz
X axis:Inductance	2.7mH
X axis:Unloaded Q(min.)	20
Y axis:Inductance	2.7mH
Y axis:Unloaded Q(min.)	20
Z axis:Inductance	2.7mH
Z axis:Unloaded Q(min.)	20
Inductance Tolerance	±5%
Operating Temperature Range	-40°C to 85°C

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1335CCN-272J=P3

Product Data



Sensitivity graph




Figure of terminal placement

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.