HI-D SWITCH® PC MOUNT SWITCHES

SERIES H-100, H-100PC, H-200, H-200PC

Compact, momentary switches mount on .625" (15.87 mm) centers in rows or matrix arrays and are the same height and panel size as Switchcraft's Hi-D Jack. Rugged "box" body protects contact springs against mechanical damage and keys them in precise alignment. Precision springs produce high contact pressure, smoother wear-reducing actuation, and positive "make-break". Recommended where contact resistance is not critical.

MOUNTING

Rear of panel mount in .375" (15.87 mm) diameter hole in panels up to .156" (3.96 mm) thick. Behind panel space: 1.094" (27.79 mm) minimum. Mounting hardware supplied. Switches with PC terminals mount directly to PC boards, and may also be panel mounted with threaded bushing.

SPECIFICATIONS

Switch Housing: Molded plastic.

Mounting Bushing: Copper alloy, plated.

Pushbutton/Actuator: Thermoplastic, red or black with

concave face.

Contact Springs: Copper alloy, silver or gold-plated. Contacts: Integral, 1-A, 1-B, 1-C, or 1-D, 0. 25 A, 30 W

maximum, non-inductive load.

Contactor: Copper alloy, plated.

Locknut: Copper alloy, plated. P10001 (supplied). Washer: Steel, nickel-plated. S10221 (supplied).

SPECIAL ORDER FEATURES

- · Other pushbutton colors.
- · Legends (see page 270).



DA-SWITCH SWITCHES

SERIES DA

Enclosed momentary pushbutton switch. Designed to meet switching requirements of computers, data processors, ground support systems, machine and process controls, test equipment and intercoms. Anodized aluminum body protects switch contacts from dirt, dust and bending during mounting. Terminals accept AMP Series 53 taper pins. Mount in .375" (9.5 mm) hole on .531" (13.5mm) centers. Behind panel depth .938" (23.8mm) minimum.

SPECIFICATIONS

Housing: Aluminum, black anodized.

Button: Thermoplastic, black.

Terminal Base: Thermoset black phenolic. Terminals: Copper alloy, gold-plated. Contacts: Integral. 500 mA, 5 W maximum.


non-inductive load.

Contactor: Copper alloy, plated.

Hardware: Supplied with one, ◊P1970 aluminum, black anodized knurled mounting nut, and one,

P1971 parkerized lockwasher.






SERIES H100, H200

PART NUMBERS

Solder Lug Terminals Pushbutton Color/Part Number		PC Terminals Pushbutton Color/Part Number		Circuit	Schematic
H101	H201	♦H101PC	0H201PC	1-A	
♦H102	♦H202	♦H102PC	♦H202PC	1-B	See Below
H103	H203	H103PC	H203PC	1-C	
♦H103D	♦H203D	parlm 1		1-D	


♦ Special order only; contact factory for price and delivery.



PART NUMBERS

Series DA	Button Color	Circuit	Schematic		
♦DA013	Red	A-B	A-B contacts may be externally wired to provide a 1-C circuit as illustrated below		
♦DA023	Black	A-B			
◊DA033	Green	A-B			
♦DA043	Blue	A-B	C		
♦DA053	White	A-B	Q KEY		
♦DA083	Yellow	A-B			

Special order only; contact Switchcraft for price and delivery.



DIMENSIONS ARE FOR REFERENCE ONLY