Tyco Electronics Our commitment. Your advantage.

• Products

- O By Type
 - Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays
 - Tubing, Molded and Harnessing Products
 - Wire, Cable and Cable Assemblies
 - List all product types...
- O <u>By Industry</u>
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Communications
 - Computer & Consumer Electronics
 - Industrial & Commercial
 - Instrumentation & Medical
- O By Brand
- O A to Z
- O Product News

Documentation

- O Find Documents & Drawings
- O Find CAD Models
- O SPICE/Electrical Models
- O NAFTA Certificate of Origin
- O White Papers

• Resources

- O RoHS Compliance & Alternates
- O Cross Reference Products
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors

• My Account

- O Sign In
- O Register

• Customer Support

- O <u>Support</u>
- O RoHS Support Center

8-1393305-4 Product Details



8-1393305-4
Active





Product Highlights:

- Nominal Voltage = 24 VDC
- Rated Current @ 85 C = 15/20 Amps.
- Plug-In Relays
- With Mounting Bracket(s)
- Contact Arrangement = 1 Form C, SPDT, 1 C/O

View all Features | Find Similar Products

Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

• Power Relays F4 / VF4, Plug-In Relays, Mini ISO (PDF, English)

Product Specifications:

• None Available

Application Specifications:

None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

Product Line Information

Previous 1 ... [16] 17 18 19 20 Next

Check Pricing & Availability
Search for Tooling

Contact Us About This Product

Product Feature Selector
Compare Products

Quick Links

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Designation = Plug-In Relays
- Product Type = Power Relay F4/VF4

Electrical Characteristics:

- Nominal Voltage (VDC) = 24
- Rated Current @ 85 C (Amps.) = 15/20
- Coil Resistance (?) = 360
- Switching Current Min. (mA) = 1000
- Switching Voltage Max. (VDC) = See Load Limit Curve
- Switching Voltage Min. (mV) = 5000
- Coil Power, Nominal (W) = 1.60

Termination Related Features:

• Height (mm[in]) = 25.20[0.992]

Body Related Features:

- Mounting Bracket(s) = With
- Series = V23134-A/-B/-C/-M and VF4
- Length (mm[in]) = 26.20[1.031]
- Width (mm[in]) = 26.20[1.031]
- Weight (g [oz]) = 35.00 [1.236]
- Bracket Type = Metal

Contact Related Features:

- Contact Material = Silver Based
- Contact Type = Make, Break or Changeover Contact

Housing Related Features:

- Enclosures (Sealing) Type = Dust Protected
- Version = Diode with cathode at 86
- Mounting Bracket Location = Near Pin 30
- Number of Contacts = 1

Configuration Related Features:

- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Coil Magnetic System = Monostable

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

• Application = Cross Carline

Other:

Brand = Tyco Electronics

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
2008 Tyco Electronics Corporation All Rights Reserved