# 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position14526-EZHB-XXX-0QC



- 10 shielded pairs plus 4 individual wires for high bandwidth applications
- The solution for high speed datacom and telecom applications
- Each differential pair is shielded with foil; entire cable bundle is shielded with foil and braid for additional signal protection
- Rugged MDR ribbon type contact
- Quick release latches
- RoHS\* compliant

Date Modified: October 11, 2005

TS-0891-07 Sheet 1 of 3

### Physical

#### **Connector Contact Plating**

0	
Wiping Area:	30 μ" [ 0.76 μm ] Min. Gold
Shell	
Color:	Parchment/Beige
Material:	Acrylonitrile Butadiene Styrene (ABS)
Cable	
Color:	Parchment/Beige
Jacket Material:	Polyvinyl Chloride (PVC)
Flammability:	AWM VW-1

### Electrical

Voltage Rating:	30 V
Current Rating:	1 A
<b>Insulation Resistance:</b>	$> 1 \times 10^8 \Omega$ at 100 VDC
Withstanding Voltage:	350 Vrms for 1 minute
Individually Shielded Twisted Pairs	
Characteristic Impedance:	$100 \pm 10\Omega$ (USB 90 $\Omega$ )
Conductor Size:	28 AWG Stranded
<b>Propogation Velocity:</b>	1.25 ns/ft [4.1 ns/m ]

### **Environmental**


**Temperature Rating:** -20°C to +75°C

"RoHS compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or prolybromianted diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based upon information provided by third party suppliers to 3M.

UL File No.: E86982


## 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position14526-EZHB-XXX-0QC



## 3M<sup>™</sup> Mini D Ribbon (MDR) Cable Assembly

.050" High Speed Digital Data Transmission System - 26 Position14526-EZHB-XXX-0QC



3M Interconnect Solutions http://www.3M.com/interconnects/

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.



Electronics

6801 River Place Blvd. Austin, TX 78726-9000 800/328-1368 www.3M.com/electronics

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

Minimum 10% Post-Consumer Fiber

Printed in USA.

© 3M 2005

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

**3M**:

14526-EZHB-100-0QC 14526-EZHB-500-0QC