3M

1339 Electrical Tape

Polyester Film/Glass Filament Reinforced with Acrylic, Pressure-Sensitive Adhesive Data Sheet

- Excellent conformability
- High tensile strength
- High dielectric strength
- Class B (130°C)
- UL recognition

3M™ Electrical Tape 1339 is a polyester film/glass filament tape coated with a pressure-sensitive acrylic adhesive system. The polyester film/glass backing has excellent physical and electrical characteristics. The back side of the tape has a special coating which allows for an even, controlled unwind. It also promotes permanent anchoring in application. Typical applications for 1339 include lead anchoring, banding of coils, lead tape anchoring and other uses where tensile strength is needed.

UL Component Recognition

Temperatures not exceeding 130°C

UL File Number E17385 A and B, Guide OANZ2. Underwriters Laboratories (UL) recognized products have been evaluated for use as components of end-product equipment that is listed or classified by UL. To achieve Underwriters Laboratories recognition, component construction must meet UL specifications and conditions of acceptability for proper and safe use of the component or product.

| Properties | Typical Value* |
|------------|----------------|
| | |

| Thickness ¹ | 6.5 mils (0,165 mm) |
|--------------------------------------------|--------------------------|
| Breaking Strength ¹ | 275 lb./in (481 N/10 mm) |
| Elongation | 5% |
| Adhesion to Steel ¹ | 35 oz/in (3,81 N/10 mm) |
| Dielectric Strength ¹ | 5,500V |
| Temperature Class | 130°C |
| Insulation Resistance ¹ | 1x10⁵ megohms |
| Electrolytic Corrosion Factor ² | 1.0 |

^{*}Not recommended for specification purposes. Product specifications will be provided upon request.

¹ASTM D-1000 Test Method

²3M Test Method

3M is a trademark of 3M.

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties,

expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.



Electrical Products Division 6801 River Place Blvd. Austin, TX 78726-9000 800 676 8381 http://www.3m.com/elpd

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

<u>3M 1345 2SQ-100</u> <u>3M 1339 1 X 60YD</u> <u>3M 1339 2 X 60YD</u> <u>1339-1"x60yd</u> <u>1339-1/2"x60yd</u> <u>1339-3/4"x60yd</u> <u>1339-3/4"x60yd</u> <u>1339-3/4"x60yd</u>