# **3M<sup>TM</sup> Scotchlok<sup>TM</sup> Terminals** MNG18BC thru MNG10BC

Butt Connector, Nylon Insulated with Insulation Grip

### Data Sheet



July 2010

Product Number	Wire Range (AWG)	L	Barrel I.D.	Max. Insulation Diameter
MNG18BC	22-18	1.08 in.	0.07 in.	0.14 in.
MNG14BC	16-14	1.10 in.	0.09 in.	0.17 in.
MNG10BC	12-10	1.23 in.	0.135 in.	0.25 in.

### **Agency Approvals** & Self Certifications

UL Listed, Standard No. UL 486C, 3M File No. E23438

CSA Certified, Standard No. C22.2 No. 0.65, 3M File No. LR22190

RoHS 2002/95/EC



RoHS Compliant 2002/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2002/618/EC, unless the substance is in an application that is exempt under RoHS. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

### :6: -....

Specifications	Wire Size:	See Table Above
	Barrel Seam:	Butted with Insulation Grip
	Max. Voltage Rating:	600 V Building Wire
		1000 V Signs, Fixtures (Luminaires)
	Max. Operating Temp:	221°F (105°C)
	Max. Current:	Same as Wire
	Insulator Material:	Nylon
	Terminal Material:	Copper
	Insulation Grip Material:	Brass
	Plating:	Tin

## **3M<sup>TM</sup> Scotchlok<sup>TM</sup> Terminals MNG18BC thru MNG10BC**

Installation Information											
information	Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.   UL Listed and CSA Certified for use on stranded copper (AWG) wire only.   Strip away the end 3/8 inch of wire insulation.   Make the crimp in the proper station of a recommended 3M <sup>™</sup> Scotchlok <sup>™</sup> Crimp Tool: TH-440, TH-450 (scissor style), or TR-482, TR-490 (ratchet style) hand tools.										
							Barrel Crimp (Electrical)				
						Engineering Specification	Crimp-type terminals shall connect, electrically and mechanically, to the pre- stripped end of two stranded copper wires.				
							The connector line shall offer barrel variations in wire (AWG) size (22-18, 16-14 and 12-10) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated with insulation grip, etc.).				
	The insulator shall be color coded and sized for a specified (AWG) wire range (22-18 16-14 and 12-10).										
Shelf Life & Storage	This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).										
Availability	Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1-800-472-1190.										
Important Notice	All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.										
Warranty; Limited Remedy; Limited Liability	This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.										

3M and Scotchlok are trademarks of 3M Company.



Electrical Markets Division 6801 River Place Blvd. Austin, TX 78726-9000 800 472.1190 FAX: 800.262.6329 www.3M.com/electrical

Please recycle © 3M 2010 All rights reserved 78-8125-9662-1 B

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>3M</u>:

MNG18BCK MNG14BCK MNG10BCK