

3M

Lapping Film

Chrome Oxide 061X

Technical Data

December, 2004

Product Description Tightly graded chromium oxide minerals slurry coated onto a polyester film backing.

Applications

- Used for final finishing of magnetic audio and video tape heads.
- Chrome oxide aids the final polishing of bi- or tri-metal substrates used in magnetic heads.

Key Features

- Produces excellent surface finish
- Reduces overall process time
- Produces high yields
- Non-slurry processing

Product I.D.	Product ID (plain back)	Mineral Size (nominal)	Backing	Color
	0.61X	0.5 micron	3 mil polyester	Forest Green

**not all products are available in all grades*

Converted Forms Sheets, Discs and Rolls.
Maximum width 26".

Backing Polyester Film
Nominal thickness: 3 mil.

Storage and Shelf Life Recommended Storage Conditions:
Temperature: 50-90°F
Relative humidity: 30-70%
(There is no degradation with time. It is recommended that product be used within 24 months of purchase.)

3M™ Lapping Film

Chrome Oxide 061X

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-251-8634. Address correspondence to: 3M Electronics Markets Materials Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-733-9175. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Markets Materials Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
1-800-251-8634 phone
651-733-9175 fax
www.3M.com/electronicmaterials



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2004 60-5002-0077-3 (12/04)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

7000118249