




# Scotchlok™ Terminals

## MVI18-187DF, MVI14-187DF

### Female Disconnect, Vinyl Insulated, Interlock Barrel



## Data Sheet

| Product Number | Wire Range (AWG) | Mates with Male Tab Width (W') x Thickness | L    | Barrel Length | Barrel I.D. | Maximum Insulation Diameter |
|----------------|------------------|--|------|---------------|-------------|-----------------------------|
| MVI18-187DF    | 22-18            | 0.187 x 0.020                              | 0.77 | 0.25          | 0.080       | 0.145                       |
| MVI14-187DF    | 16-14            | 0.187 x 0.020                              | 0.77 | 0.25          | 0.080       | 0.145                       |



UNDERWRITERS  
LABORATORIES  
STANDARD NO. UL 486C  
3M FILE NO. E70512



CANADIAN STANDARDS  
ASSOCIATION  
STANDARD NO. 22.2  
NO. 0, 65  
3M FILE NO. LR22190

## Specifications

|                         |  |
|-------------------------|--|
| Wire Size:              | See Table Above  |
| Barrel Seam:            | Interlock  |
| Maximum Voltage Rating: | 600V Building Wire<br>1000 V Signs or<br>Fixtures (Luminaires) |
| Maximum Operating Temp: | 221°F, (105°C)   |
| Maximum Current:        | Same as Wire   |
| Insulator Material:     | Vinyl  |
| Terminal Material:      | Brass  |
| Plating:                | Tin  |

## Installation Information


### ⚠ WARNING


Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style), or TR-490 (ratchet style) hand tools.



 Barrel Crimp (Electrical)

Suitable for factory installation on steel or brass tabs, UL and CSA.

Suitable for field application on brass tabs, strain relief is required, UL only.

## Engineering Specification

Crimp-Type Female Disconnect Terminals shall, electrically and mechanically, connect permanently to the prestripped end of a stranded copper wire: and have a tongue portion with fingers which grip a Male Disconnect in a separable, reusable manner, forming a Quick Connect Wiring Termination.

The connector line shall offer variations (sized to secure male tabs: 0.250" x 0.032" or 0.187" x 0.020" per ANSI/NEMA CD-2), and barrel variations in wire (AWG) size: (22-18, 16-14, 12-10) and construction (non-insulated, vinyl insulated, nylon fully insulated etc.). The tongue portion shall be marked with the wire range and manufacturer's symbol (↑).

The Vinyl Insulated 0.187" x 0.020" Female Quick-Slide with interlocking barrel shall be tin plated 0.020" thick brass with a tongue for gripping 0.187" x 0.020" male tab per ANSI/NEMA CD-2 and a 0.25" long barrel covered by a molded vinyl sleeve, color coded and sized for a specified (AWG) wire range (22-18, 16-14).

Insulated connectors shall be UL Listed and CSA Certified for 600 V building wire: 1000 V signs or lighting fixtures (luminaires) and temperature rated 221°F (105°C) maximum.

3M and Scotchlok are trademarks of 3M Company.



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

### IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

**Warranty; Limited Remedy; Limited Liability.** This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

# 3M

Electrical Products Division

6801 River Place Blvd.  
Austin, TX 78726-9000  
<http://www.3M.com/elpd>

Litho in USA.  
© 3M 2003 78-8126-0608-1-B

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[3M:](#)

[MVI14-187DFK](#)