


3M™ TWIN AXIAL CABLE, SL8800 SERIES



- NOTES
- DIMENSIONS ARE IN MILLIMETERS.
 - PHYSICAL:
COLOR: SILVER
MARKING:
3M (part number) 30 AWG (signal plating) [VW1] (lot code)

EXAMPLE:
3M SL8801/12-10DA5-00 30 AWG SILVER TW602-1

EXAMPLE VW1:
3M SL8801/12-1FDG5-00 30 AWG SILVER VW1 TW602-1
 - REGULATORY INFORMATION:
ROHS COMPLIANT. SEE THE REGULATORY INFORMATION APPENDIX (RIA) IN THE "ROHS COMPLIANCE" SECTION OF WWW.3MCONNECTORS.COM FOR COMPLIANCE INFORMATION (RIA E1 & C1 APPLY)

UL FILE NUMBER: E42769
 - THE OUTER SURFACE OF THE RIBBON CABLE HAS A METALLIC APPEARANCE, BUT IS NOT CONDUCTIVE. THERE IS A TRANSLUCENT POLYESTER OUTER LAYER OVER AN ALUMINUM SHIELDING LAYER, WHICH GIVES THIS APPEARANCE.

THIS CABLE CONSTRUCTION HAS A THIN ALUMINUM LAYER AT EACH EDGE. USER SHOULD EVALUATE ITS USE IN THEIR APPLICATION AND, IF NECESSARY, INSULATING TAPE MAY BE APPLIED TO COVER THE ALUMINUM LAYER, AS USER DEEMS APPROPRIATE.
 - FOIL AND INSULATOR STRIPPING BLADE DESIGN DRAWINGS ARE AVAILABLE UPON REQUEST.
TOOLING REFERENCE NUMBER: NU6D
 - (C) DENOTES CRITICAL DIMENSION.

		HORIZONTAL FLAME VERSION	VW1 VERSION
SIGNAL WIRE PLATING	SILVER	SL8801/12-10DA5-00	SL8801/12-1FDG5-00
	TIN	SL8801/12-11DA5-00	SL8801/12-1GDG5-00
PRODUCT SPEC.		PS-0105	PS-0163
IMPEDANCE SPEC.		100 ±5 OHMS	95 ±5 OHMS

Visit <http://www.3mconnectors.com>

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
ACCESS CODES		DRFT	MWL	DATE MAR 04, 2011	MFG	DATE
		CHKD	RE	DATE MAR 04, 2011	APPVL	DATE
DIVISION	DIVISION CODE	3M 3M Center St. Paul, MN 55144				
DO NOT SCALE DRAWING	SCALE 15 1	© 3M COPYRIGHT 2018 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.				
THIRD ANGLE PROJECTION	INTERPRET PER ASME Y14.5 - 2009	TITLE SL8801/12-1XDX5-00, 100 OHM, 30 AWG, 4PR, 4SBC				
MAX SURFACE ROUGHNESS 125	ALL SURFACES MARKED ONLY	CAGE NUMBER	SIZE	DRAWING NO.	REV.	
				78-5100-2412-4	E	
		MODEL		DET. LISTS	YES NO	SHT 1 OF 2

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.



Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Electronics Materials Solutions Division
6801 River Place Blvd.
Austin, TX 78726-9000
1-800-225-5373
www.3M.com/interconnect

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD		
ACCESS CODES				DRFT	MWL	DATE	MAR 04,2011	MFG	DATE		
				CHKD	RE	DATE	MAR 04,2011	APPVL	DATE		
DIVISION		DIVISION CODE		 <div>3M Center St. Paul, MN 55144</div>				© 3M COPYRIGHT 2018 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.			
DO NOT SCALE DRAWING		SCALE 1/1								TOLERANCES EXCEPT AS NOTED	
		THIRD ANGLE PROJECTION		INCHES		TITLE SL8801/12-1XDX5-00, 100 OHM, 30 AWG, 4PR, 4SBC					
INTERPRET PER ASME Y14.5 - 2009		MILLIMETERS		.0 ± .00 ± .000 ± .0000 ±							
MAX SURFACE ROUGHNESS 125		ALL SURFACES MARKED ONLY		.00 ± 0.10 .000 ±		CAGE NUMBER		SIZE	DRAWING NO.	REV.	
				ANGLES ±1°		C		78-5100-2412-4	E		
						MODEL		DET. LISTS		YES NO	SHT 2 OF 2

E

79896

AUG 07,2018

ADDED CRITICAL DIM SYMBOLS

ADDED NOTE 6

REVISED TOLERANCE

LDS

MML

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

[SL8801/12-11DA5-00](#) [SL8801/12-10DA5-00](#)