

PowerFilm[®]

MADE IN THE USA

SOLAR

30W Foldable Solar Panel

The 30W Foldable Solar Panel is lightweight, durable and extremely portable.

The solar panels are mounted to weather resistant fabric that quickly folds for storage and unfolds for use.

Unmatched durability allows for use in the harshest environments and a panel that works even after a portion is damaged.

This compact panel fits easily into most backpacks and is the perfect accessory to provide power for a wide range of electronics.

The 30W Foldable Solar Panel keeps you connected and helps you get more out of your outdoor adventures.

Tips For Best Use:

- Angle the solar panel toward the sun for best results.
- Always store in a cool dry environment.
- Not designed for use in the rain.
- Allow time to air dry before packing if the panel is wet.
- Routinely clean the solar panel to ensure best performance.



Benefits Include:

- Compact, lightweight, durable - military tested (MIL-STD-810G).
- Easy to deploy and easy to store.
- Provides some power even in hazy and shaded environments.
- Light sensitive technology turns on early in the day and stays on later in the day.
- Multiple charging adapters to fit your needs and charge a wide range of devices.
- Designed, engineered and manufactured in the United States.

Foldable Charging Capabilities:

Devices:	20W	30W	60W	100W	120W	220W
Cell Phone	✓	✓	✓	✓	✓	✓
Tablet		✓	✓	✓	✓	✓
Laptop			✓	✓	✓	✓
400Wh Battery			✓	✓	✓	✓
1kWh Battery					✓	✓

Certifications:

- CE
- MIL-STD-810G
- RoHS
- Berry Amendment Compliance

PowerFilm[®]

MADE IN THE USA

SOLAR

30W Foldable Solar Panel

Electrical Characteristics

Rated Voltage at Pmax	15.4V
Rated Current at Pmax	1.8A
Open Circuit Voltage	21.9V
Short Circuit Current	2.3A

Physical Characteristics

Part Number	F16-1800
Folded Dimensions	13.0 x 7.5 x 1.7 inches 330.2 x 190.5 x 43.2 mm
Unfolded Dimensions	47.0 x 25.5 inches 1,193.8 x 647.7 mm
Weight	1.4 lbs 0.6 kg

Thermal Characteristics

Temperature Coefficient for Power	- 0.200 (%/C)
Temperature Coefficient for Voltage	- 0.240 (%/C)
Temperature Coefficient for Voc	- 0.300 (%/C)
Temperature Coefficient for Isc	0.109 (%/C)

Connectors

Standard Connector:

Aptiv Weather Pack

Custom Connectors:

SAE


Barrel

Anderson Powerpole

Customer Specified



47.0 inches



25.5 inches

Standard Colors:

Black

Custom Colors:


Digicam

Desert Camo

Khaki

Woodland

IV Curve



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[PowerFilm:](#)

[F16-1800](#)