

DIN 46237

VINYL-INSULATED RING TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14
AMP.	9	12	17	18	30


MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL

INSULATION COLOR:

22-16 A.W.G.: RED 16-14 A.W.G.: BLUE

TERMINAL MATERIAL: COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION mm						CRIMPING TOOL	Q'TY BOX		
	BRAZED SEAM	BUTTED SEAM	d2		d3	I	d1	d4	a	S				
22-16 A.W.G. 0.5-1.5 mm ²	DRVB2-1	DRV2-1	#2	2.2	6.0	16.0	1.6	4.0	10.0	0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J KSTLY-2004 KSTLY-2005 WITH DIE INDEX COLOR:RED	1000		
	DRVB2.5-1	DRV2.5-1	#3	2.7								1000		
	DRVB3-1	DRV3-1	#4	3.2								1000		
	DRVB3.5-1	DRV3.5-1	#6	3.7								1000		
	DRVBS4-1	DRVS4-1	#8	4.3	7.0	16.5						8.0	17.0	1000
	DRVB4-1	DRV4-1	#8	4.3	17.5	1000								
	DRVBS5-1	DRVS5-1	#10	5.3	10.0	18.0						1000		
	DRVB5-1	DRV5-1	#10	5.3								1000		
	DRVB6-1	DRV6-1	1/4	6.5	14.0	22.0						1000		
	DRVBL6-1	DRVL6-1	1/4	6.5								11.0	20.0	1000
	DRVB8-1	DRV8-1	5/16	8.4	14.0	22.0						1000		
	DRVB10-1	DRV10-1	3/8	10.5								18.0	24.0	1000
	DRVBL10-1	DRVL10-1	3/8	10.5	18.0	24.0						1000		
	16-14 A.W.G. 1.5-2.5 mm ²	DRVB3-2.5	DRV3-2.5	#4	3.2	6.0						16.0	2.3	4.5
DRVB3.5-2.5		DRV3.5-2.5	#6	3.7	1000									
DRVBS4-2.5		DRVS4-2.5	#8	4.3	8.0	16.6	1000							
DRVB4-2.5		DRV4-2.5	#8	4.3		17.0	1000							
DRVBS5-2.5		DRVS5-2.5	#10	5.3	10.0	18.5	1000							
DRVB5-2.5		DRV5-2.5	#10	5.3		19.0	1000							
DRVB6-2.5		DRV6-2.5	1/4	6.5	11.0	21.0	1000							
DRVB8-2.5		DRV8-2.5	5/16	8.4		22.0	1000							
DRVB10-2.5		DRV10-2.5	3/8	10.5			15.0	1000						
DRVBL10-2.5		DRVL10-2.5	3/8	10.5	18.0	23.5	2.3	4.5	10.0	0.8	K.S. MODEL KST2000A HRI-126J KSTLY-2004 KSTLY-2005 WITH DIE INDEX COLOR:BLUE	1000		
DRVB12-2.5		DRV12-2.5	1/2	13.0		25.0					1000			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KS Terminals:

[DRV10-2.5](#) [DRV2.5-1](#) [DRV3-1](#) [DRV4-1](#) [DRV4-2.5](#) [DRV5-1](#) [DRV5-2.5](#) [DRV6-1](#) [DRV6-2.5](#) [DRV8-1](#) [DRV8-2.5](#)
[DRVL10-2.5](#) [DRVS4-1](#) [DRVS4-2.5](#) [DRVS5-2.5](#)