


VINYL-INSULATED (EASY ENTRY) FLANGE SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	9	12	17	18	30	35	50

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

 22-16 A.W.G.: RED ■ 16-14 A.W.G.: BLUE ■ 12-10 A.W.G.: YELLOW ■
TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION ^{inch} mm							CRIMPING TOOL	Q'TY BOX																																						
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	A			T																																					
22-16 A.W.G. 0.5-1.5 mm ²	FSVEB1-2	FSVE1-2	#2	.087 2.2	.252 6.4	.205 5.2							IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000																																					
	FSVEB1-3.2	FSVE1-3.2	#4	.126 3.2	.295 7.5														1000																																
	FSVEBS1-3.2	FSVES1-3.2	#4	.126 3.2	.252 6.4																			1000																											
	FSVEB1-3.7	FSVE1-3.7	#6	.146 3.7	.295 7.5																								1000																						
	FSVEBS1-3.7	FSVES1-3.7	#6	.146 3.7	.252 6.4																										1000																				
	FSVEBL1-3.7	FSVEL1-3.7	#6	.146 3.7	.335 8.5	.283 7.2								1.012 25.7												1000																									
	FSVEB1-4	FSVE1-4	#8	.169 4.3	.295 7.5	.201 5.1								.795 20.2																				1000																	
	FSVEBL1-4	FSVEL1-4	#8	.169 4.3	.335 8.5	.283 7.2								1.012 25.7																										1000											
	FSVEB1-5	FSVE1-5	#10	.209 5.3	.295 7.5	.201 5.1								.795 20.2																																1000					
	FSVEBL1-5	FSVEL1-5	#10	.209 5.3	.335 8.5	.283 7.2								1.012 25.7														1000																							
16-14 A.W.G. 1.5-2.5 mm ²	FSVEB2-3.7	FSVE2-3.7	#6	.146 3.7	.295 7.5	.205 5.2	.827 21.0							IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLUE					1000																																
	FSVEBL2-3.7	FSVEL2-3.7	#6	.146 3.7	.335 8.5	.283 7.2	.965 24.5																							1000																					
	FSVEB2-4	FSVE2-4	#8	.169 4.3	.295 7.5	.205 5.2	.827 21.0																														1000														
	FSVEBM2-4	FSVEM2-4	#8	.169 4.3	.315 8.0	.268 6.8	.984 25.0																																					1000							
	FSVEBL2-4	FSVEL2-4	#8	.169 4.3	.335 8.5	.283 7.2	.965 24.5																																												1000
	FSVEB2-5	FSVE2-5	#10	.209 5.3	.295 7.5	.205 5.2	.827 21.0																																												
	FSVEBL2-5	FSVEL2-5	#10	.209 5.3	.335 8.5	.283 7.2	.965 24.5																																												
12-10 A.W.G. 4-6 mm ²	FSVEB5-3.7	FSVE5-3.7	#6	.146 3.7	.335 8.5	.295 7.5	1.106 28.1							IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:YELLOW					500																																
	FSVEBS5-3.7	FSVES5-3.7	#6	.146 3.7	.299 7.6	.244 6.2	1.047 26.6																							500																					
	FSVEB5-4	FSVE5-4	#8	.169 4.3	.335 8.5	.295 7.5	1.106 28.1																														500														
	FSVEBS5-4	FSVES5-4	#8	.169 4.3	.299 7.6	.244 6.2	1.047 26.6																																					500							
	FSVEB5-5	FSVE5-5	#10	.209 5.3	.335 8.5	.295 7.5	1.106 28.1																																												500
	FSVEBS5-5	FSVES5-5	#10	.209 5.3	.299 7.6	.244 6.2	1.047 26.6								500																																				

(UL) (UL) ALL LISTED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KS Terminals:

[FSVE1-3.7](#) [FSVE1-4](#) [FSVE1-5](#) [FSVE2-3.7](#) [FSVE2-5](#) [FSVE5-4](#) [FSVE5-5](#) [FSVEL1-4](#) [FSVEL2-3.7](#) [FSVEL2-5](#)
[FSVEM2-4](#) [FSVES1-3.2](#) [FSVES1-3.7](#) [FSVES5-4](#) [FSVES5-5](#)