


VINYL-INSULATED (MOLDED EASY ENTRY) FLANGE SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	9	12	17	18	30	35	50

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.
INSULATION MATERIAL: VINYL
INSULATION COLOR:

 22-16 A.W.G.: RED ■ 16-14 A.W.G.: BLUE ■ 16-14 A.W.G.: YELLOW ■
TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.		STUD SIZE		DIMENSION inch mm							CRIMPING TOOL	Q'TY BOX																																						
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	A			T																																					
22-16 A.W.G. 0.5-1.5 mm ²	FSVYB1-2	FSVY1-2	#2	.087 2.2	.252 6.4	.205 5.2							IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:RED	1000																																					
	FSVYB1-3.2	FSVY1-3.2	#4	.126 3.2	.295 7.5														1000																																
	FSVYBS1-3.2	FSVYS1-3.2	#4	.126 3.2	.252 6.4																				1000																										
	FSVYB1-3.7	FSVY1-3.7	#6	.146 3.7	.295 7.5																										1000																				
	FSVYBS1-3.7	FSVYS1-3.7	#6	.146 3.7	.252 6.4																																1000														
	FSVYBL1-3.7	FSVYL1-3.7	#6	.146 3.7	.335 8.5														.283 7.2	1.004 25.5							1000																								
	FSVYB1-4	FSVY1-4	#8	.169 4.3	.295 7.5														.201 5.1	.787 20.0																			1000												
	FSVYBL1-4	FSVYL1-4	#8	.169 4.3	.335 8.5														.283 7.2	1.004 25.5																									1000						
	FSVYB1-5	FSVY1-5	#10	.209 5.3	.295 7.5														.201 5.1	.787 20.0																															1000
	FSVYBL1-5	FSVYL1-5	#10	.209 5.3	.335 8.5														.283 7.2	1.004 25.5									1000																						
16-14 A.W.G. 1.5-2.5 mm ²	FSVYB2-3.7	FSVY2-3.7	#6	.146 3.7	.295 7.5	.205 5.2	.807 20.5							IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:BLUE	1000																																				
	FSVYBL2-3.7	FSVYL2-3.7	#6	.146 3.7	.335 8.5	.283 7.2	.945 24.0																							1000																					
	FSVYB2-4	FSVY2-4	#8	.169 4.3	.295 7.5	.205 5.2	.807 20.5																														1000														
	FSVYBM2-4	FSVYM2-4	#8	.169 4.3	.315 8.0	.268 6.8	.965 24.5																																					1000							
	FSVYBL2-4	FSVYL2-4	#8	.169 4.3	.335 8.5	.283 7.2	.945 24.0																																												1000
	FSVYB2-5	FSVY2-5	#10	.209 5.3	.295 7.5	.205 5.2	.807 20.5																																												
	FSVYBL2-5	FSVYL2-5	#10	.209 5.3	.335 8.5	.283 7.2	.945 24.0																																												
12-10 A.W.G. 4-6 mm ²	FSVYB5-3.7	FSVY5-3.7	#6	.146 3.7	.335 8.5	.295 7.5	1.063 27.0							IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A HRI-126J WITH DIE INDEX COLOR:YELLOW	500																																				
	FSVYBS5-3.7	FSVYS5-3.7	#6	.146 3.7	.299 7.6	.244 6.2	1.004 25.5																							500																					
	FSVYB5-4	FSVY5-4	#8	.169 4.3	.335 8.5	.295 7.5	1.063 27.0																														500														
	FSVYBS5-4	FSVYS5-4	#8	.169 4.3	.299 7.6	.244 6.2	1.004 25.5																																					500							
	FSVYB5-5	FSVY5-5	#10	.209 5.3	.335 8.5	.295 7.5	1.063 27.0																																												500
	FSVYBS5-5	FSVYS5-5	#10	.209 5.3	.299 7.6	.244 6.2	1.004 25.5																					500																							

(UL) c(UL) ALL LISTED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[KS Terminals:](#)

[FSVY1-3.7](#) [FSVY2-3.7](#) [FSVY2-4](#) [FSVY2-5](#) [FSVY5-5](#)