


HEAT SHRINKABLE-RING TERMINALS

"HB"(BRAZED TYPE)

MAXIMUM ELECTRIC CURRENT:

A.W.G.	16	14
AMP.	18	30

MAXIMUM ELECTRICAL RATING: 600 VOLTS MAX.
SHRINK TEMP.: 150°C OPERATING TEMP.: -40°C~+105°C
INSULATION MATERIAL: HIGH DENSITY PE.
TERMINAL MATERIAL: COPPER


WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION						INSULATED COLOR	CRIMPING TOOL	Q'TY BOX
		d2		W		L				
		inch	mm	inch	mm	inch	mm			
16-14 A.W.G.	RHB2-2	#2	2.2	.260	6.6	1.051	26.7	BLUE	K.S. MODEL KST2000G WITH DIE INDEX NO:2	1000
	RHBS2-3.2	#4	3.2	.217	5.5	1.067	27.1			1000
	RHB2-3.2	#4	3.2	.260	6.6	1.042	26.5			1000
	RHBL2-3.2	#4	3.2	.335	8.5	1.004	25.5			1000
	RHBS2-3.7	#6	3.7	.260	6.6	1.043	26.5			1000
	RHBM2-3.7	#6	3.7			1.106	28.1			1000
	RHBL2-3.7	#6	3.7	.335	8.5	1.201	30.5			1000
	RHBS2-4	#8	4.3	.260	6.6	1.106	28.1			1000
	RHBL2-4	#8	4.3	.335	8.5	1.201	30.5			1000
	RHBS2-5	#10	5.3							1000
1.5-2.5 mm ²	RHBL2-5	#10	5.3	.374	9.5	1.398	35.5			1000
	RHB2-6	1/4	6.4	.472	12.0					1.406
	RHB2-7	※ 5/16	7.4			1.398	35.5			500
	RHB2-8	5/16	8.4			.535	13.6			1.346
	RHB2-9	5/16	9.8	1.476	37.5					500
	RHB2-10	3/8	10.5	.756	19.2	1.744	44.3			500
	RHBL2-10	3/8	10.5			1.736	44.1			500
	RHB2-12	1/2	13.0	1.063	27.0	2.087	53.0			500
	RHB2-14	9/16	15.0							500
	RHB2-16	5/8	17.0							500
	RHB2-20	3/4	21.0					500		



ALL LISTED

※ : DEVELOPING ON DEMAND

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KS Terminals:

[RHB2-10](#) [RHB2-6](#) [RHB2-8](#) [RHBL2-4](#) [RHBL2-5](#) [RHBS2-3.7](#)