

[Features]

- High contrast (900:1)
- 16.77M/262K colors (LVDS RGB 8-bit/6-bit)
- Reversible-scan direction
- Wide temperature range (-30°C to +80°C)
- Long-life LED backlight*¹



Pixel	1,024 (H) x 768 (V)
Display area	245.76 (H) x 184.32 (V) mm 12.1inches (31cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.24 (H) x 0.24 (V) mm
Luminance	450cd/m ² (typ.)
Contrast ratio	900:1 (typ.)
Viewing angle* ²	Up: 80°, Down: 80°, Left: 80°, Right: 80°
Response time* ³	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	5.2W (typ.)
Operating temperature	-30°C to +80°C
Storage temperature	-30°C to +80°C
Polarizer surface	Clear
Module size	W 260.5 (typ.) x H 203.0 (typ.) x D 9.2 (max.) mm
Weight	490g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	104PW03F

*1 70k hours long life LED

*2: Contrast ratio ≥ 10:1

*3: Ton+Toff (10%←→90%)

*All information is subject to change without notice.

*Screen images are simulated.

<Tianma Japan web site>

Japanese <https://www.tianma.co.jp/jp>

English <https://www.tianma.co.jp/en>

Published date: Jul. 2017

©Tianma Japan, Ltd. 2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tianma:

[NL10276BC24-21](#)